INCH-POUND
MIL-P-24441A(SH)
AMENDMENT 3
23 January 1989
SUPERSEDING
AMENDMENT 2
31 October 1986

MILITARY SPECIFICATION

PAINT, EPOXY-POLYAMIDE
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-P-24441A(SH), dated 15 July 1980, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.2 Other publications. Delete "D 2801 - Leveling Characteristics of Paint by Draw Down Method, Test for."

PAGE 4

Add as new paragraph 3.5.1:

"3.5.1 Certificate of compliance. When specified in the contract or order, a certificate of compliance shall be required (see 6.2.2), to show that the paint is asbestos-free."

PAGE 8

TABLE I: Under "Item" column, opposite "Sag 1/": Add "3/".

Under "Applicable method in FED-STD-141" column, opposite "Sag 1/": Add "4494.1".

Under "Applicable ASTM test method" column, opposite "Sag 1/": Delete "D 2801".

Following footnote 2/, add: "3/ Per FED-STD-141".

AMSC N/A FSC 8010
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:55Z
Check the source to verify that this is the current version before use.

PAGE 9

4.6.6, line 2: Delete "ASTM D 2801" and substitute "4494.1 of FED-STD-141".

PAGE 12

4.6.15.1: Delete and substitute:

"4.6.15.1 Preparation of panels. Panels shall be mild steel conforming to QQ-S-698, cold rolled, 6 inches by 10 inches by 1/8 inch blasted to a uniform white appearance with a minimum surface profile of 1.0 to 2.0 mils peak to valley. Panels shall be cleaned after blasting using clean, dry compressed air or vacuum. Prepare six test panels for each of the following systems:

Type I

	System A	System B	System C
Coat No. 1 0.076 - 3 to 4 mils	F.1/150	F.150	F.150
Coat No. 2 0.05 - 2 to 3 mils	F.151	F.151	F.151
* Coat No. 3 0.05 - 2 to 3 mils	F.152	F.156 or 157	F.153, 154, or 155

Type II

	System A	System B	System C
Coat No. 1 (3 to 4 mils)	F. 150R66	F. 150R66	F. 150R66
Coat No. 2 (2 to 3 mils)	F. 151R66	F. 151R66	F. 151R66
Coat No. 3 (2 to 3 mils)	F. 152R66	F. 156R66 or 157R66	F. 153R66, 154R66, or 155R66

Total film thickness, 7 to 9 mils dry film shall be applied to both sides of panel. Apply paint using standard spray equipment allowing 16 to 24 hours drying time between coats at 73.4 ± 5°F. Condition coated panels for 1 week after application of final coat at 73.4 ± 5°F. Measure and report the dry film thickness for each side of each panel.

1/ F. indicates formula number."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:55Z
Check the source to verify that this is the current version before use.

PAGE 15

5.3.1(j), line 2: Delete "bath" and substitute "batch".

5.3.1.1.2, line 6: Delete "6-hours" and substitute "5-hours".

PAGE 16

6.2.2: Delete and substitute:

"6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

Paragraph no.	Data requirement title	Applicable DID no.	Option
3.5.1	Certificate of compliance	DI-E-2121	----
4.5.1	Certification data report	UDI-A-23264	----

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5010.12-L., AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)"

PAGE 17

6.7: Delete and substitute:

"6.7 Composition variation. The value specified for thixotrope is a maximum value. Amounts less than this can be used if so indicated by the manufacturers experience (see 6.4). The manufacturer will have the choice of (1) the amount and type of thixotrope required for long term storage stability; (2) specification consistency requirements and (3) acceptable application properties consistent with the specification requirements. The quantitative requirements are not intended as target values at which to aim, but are intended to allow for slight variation in manufacture. Where analysis shows values outside of the specified limits, it is an indication of poor quality control and may be cause for removal from the Qualified Products List."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:55Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 8010-N377)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T21:55Z
Check the source to verify that this is the current version before use.