NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/11D
1 May 1997
SUPERSEDING
MIL-D-3943/11C
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, SILVER STAR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

MATERIAL:
BASE: Red Brass
SUPERIMPOSED STAR: Sterling Silver

DASH NO.
-1: Regular Size
-2: Miniature Size

FINISH:
BASE: Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.
SUPERIMPOSED STAR: Polished.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:45Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

BASE:		
	HEIGHT (Overall):	
		-1: 1-3/4 inches (4.45 cm) (REF)
		-2: 7/8 inch (2.22 cm) (REF)
	WIDTH (Overall):	
		-1: 1-1/2 inch (3.81 cm) (REF)
		-2: 3/4 inch (1.91 cm) (REF)
STAR:		
	DIAMETER:	
		-1: 3/16 inch (0.48 cm) (REF)
		-2: 3/32 inch (0.24 cm) (REF)
	THICKNESS (Overall):	
		-1: 1/16 inch $\pm$ 1/64 inch (0.16 cm $\pm$ 0.04 cm)
		-2: 3/64 inch $\pm$ 1/64 inch (0.12 cm $\pm$ 0.04 cm)
ASSEMBLED THICKNESS (Including Superimposed Star):		
		-1: 0.200 inch $\pm$ 0.010 inch (0.508 cm $\pm$ 0.025 cm)
		-2: 0.125 inch $\pm$ 0.010 inch (0.318 cm $\pm$ 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The star shall be centered on and soldered to the obverse face of the base.

3. The pendant ribbon ring is an integral part of the pendant and may be split to facilitate the attachment of the pendant ribbon.

4. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

5. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/136.

6. The lapel button shall conform to MIL-DTL-11484/9.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0887)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:45Z
Check the source to verify that this is the current version before use.