NOT MEASUREMENT SENSITIVE


MIL-D-3943/12C
12 June 1992
SUPERSEDING
MIL-D-3943/12B
31 March 1987

MILITARY SPECIFICATION SHEET


DECORATION, LEGION OF MERIT, CHIEF COMMANDER


This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE





REVERSE

MATERIAL: Gilding Metal

FINISH: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:46Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

DIAMETER:
BASE: 2-15/16 inches (7.46 cm) (REF)
CENTER DEVICE: 1-1/8 inches (2.86 cm) (REF)

THICKNESS (At thickest point):
BASE: 0.185 inch ± 0.005 inch (0.470 cm ± 0.012 cm)
DEVICE: 0.140 inch ± 0.005 inch (0.356 cm ± 0.012 cm)
OVERALL: 0.325 inch ± 0.005 inch (0.826 cm ± 0.012 cm)

NOTES:

1. Attaching device shall be the pin and catch type.

2. The attaching device shall be located and soldered on a horizontal line 1-1/8 inch + 1/32 inch - 0 (2.86 cm + 0.08 cm - 0) below the top of the decoration. The pin shall be formed from 0.057 inch ± 0.002 inch (1.45 cm ± 0.005 cm) diameter nickel silver wire and shall be 2-1/32 inches ± 1/32 inch (5.16 cm ± 0.08 cm) in finished length.

3. Pierced areas shall be as indicated.

4. The enamel colors shall be as indicated. The color shall conform to TIOH Color Chip Numbers listed below or the standard sample. The white enamel areas of the five (5) rays shall be convex within the dikes.

COLOR	CHIP NO.
Red	4
Green	11
Blue	20
White	28

5. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. The epoxy resin shall be a stoning epoxy, have a shore D hardness of no less than 85 and incorporate an ultraviolet inhibitor.

6. The base shall be spherically dapped to a radius of 3-1/32 inch ± 1/16 inch (7.70 cm ± 0.16 cm). The center device shall be dapped so as to fit flush on the base.

7. The center device shall be secured to the base by means of two brass tubular rivets.

8. Unless otherwise specified, the finished decoration shall be wrapped in three thicknesses of tissue paper and placed in a unit box. The dimensions of the unit box shall be determined by the contractor.

9. Type I Decoration set shall consist of a chest pin, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Style 5, Type VI with a Class 1 or 1A pad.

10. The ribbon for the service ribbon shall conform to MIL-R-11589/80.

11. The lapel button shall conform to MIL-L-11484/10.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T22:46Z
Check the source to verify that this is the current version before use.

12. The term (REF) refers to the measurements taken from the Government furnished hub or die.

Custodians:
Army - IH
Navy - NU
Air Force - 11

Review activities:
Air Force - 82,99
Navy - MC
DLA - CT

User activity:
Air Force - 45
Navy - CG

Preparing activity:
Army - IH

(Project No. 8455-0669)

Source: https://assist.dla.mil - Downloaded: 2026-10-16T22:46Z
Check the source to verify that this is the current version before use.