INCH-POUND

MIL-DTL-3943/12H
27 June 2016
SUPERSEDING
MIL-DTL-3943/12G
29 May 2007

DETAIL SPECIFICATION SHEET

DECORATION, LEGION OF MERIT, CHIEF COMMANDER

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE

REVERSE

MATERIAL: Gilding Metal 95/5 (UNS Alloy No. C-210)

FINISH: Epoxy resin, 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8

DIMENSIONS:
DIAMETER:
BASE: 2-15/16 inches (REF)
CENTER DEVICE: 1-1/8 inches (REF)
THICKNESS (At thickest point):
BASE: 0.185 inch ± 0.005 inch
DEVICE: 0.140 inch ± 0.005 inch
OVERALL: 0.325 inch ± 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:45Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1: Attaching device shall be the pin and catch type.

2: The attaching device shall be located and soldered on a horizontal line 1-1/8 inch + 1/32 inch - 0 below the top of the decoration. The pin shall be formed from 0.057 inch 0.002 inch diameter nickel silver wire and shall be 2-1/32 inches ± 1/32 inch in finished length.

DECORATION SET: Decoration set shall consist of a chest pin, a service ribbon with a ribbon attachment and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type VI, Style 5 with a Class 1 or 1A pad.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Pierced areas shall be as indicated.

3. The base shall be spherically dapped to a radius of 3-1/32 inch ± 1/16 inch. The center device shall be dapped so as to fit flush on the base.

4. The center device shall be secured to the base by means of two brass tubular rivets.

5. Unless otherwise specified, the finished decoration shall be wrapped in three thicknesses of tissue paper and placed in a unit box. The dimensions of the unit box shall be determined by the contractor.

6. The specification slash sheet for the ribbon for the service ribbon is MIL-DTL-11589/80.

7. The specification slash sheet for the lapel button is MIL-DTL-11484/10.

8. The specification slash sheet for the ribbon attachment is MIL-DTL-41819/1.

EPOXY: Epoxy resin shall be applied to the Decoration as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
Red	#4
Green	#11
Blue	#20
White	#28

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:45Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11
Navy - MC

Preparing activity:
Army - IH

Review activities:
Navy - CG1
DLA - CT

(Project No. 8455-2016-531)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:45Z
Check the source to verify that this is the current version before use.