NOT MEASUREMENT SENSITIVE


MIL-D-3943/7D
9 November 1992
SUPERSEDING
MIL-D-3943/7C
31 March 1987

MILITARY SPECIFICATION SHEET


DECORATION, DISTINGUISHED SERVICE MEDAL, ARMY


This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE





REVERSE

MATERIAL: Gilding Medal

DASH NO:
-1: Regular Size
-2: Miniature Size

FINISH:
-1: PENDANT: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights
SUSPENSION BAR: Gold Plated, Matte Finish, Polished Highlights

-2: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights

DIMENSIONS:
PENDANT:
HEIGHT (Overall):
-1: 1-31/32 inches (5.00 cm) (REF)
-2: 1 inch (2.54 cm) (REF) (Pendant and Suspension Bar)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:43Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1: 1-1/2 inches (3.81 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

THICKNESS:
-1: 0.215 inch ± 0.010 inch (0.546 cm ± 0.025 cm)
-2: 0.110 inch ± 0.010 inch (0.279 cm ± 0.025 cm)

SUSPENSION BAR (Dash No. 1 only):
HEIGHT (Overall): 9/32 inch (0.71 cm) (REF)
WIDTH (Overall): 1-3/8 inches (3.49 cm) (REF)
THICKNESS (At thickest point): 0.160 inch ± 0.010 inch (0.406 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.
2. The device shall be soldered to the base.
3. Dash No. 2 is one piece construction.
4. The suspension ribbon bar for Dash No. 1 shall be made from brass wire 0.045 inch ± 0.002 inch (0.114 cm ± 0.005 cm) in diameter and shall be riveted to the suspension bar at each end.
5. The pendant shall be secured to the suspension bar by a swivel joint formed by a round bar from the pendant passing completely through the suspension bar and the end peened.
6. Enamel color shall be blue as indicated. The enamel color shall conform to the TIOH chip number 20 or the standard sample.
7. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85 and incorporate an ultraviolet inhibitor.
8. Pierced areas shall be as indicated.
9. Decoration set shall consist of a regular size medal, a miniature size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Style 5, Type V with a Class 2 or 2A pad.
10. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/52.
11. The lapel button shall conform to MIL-L-11484/4.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0689)

Source: https://assist.dla.mil - Downloaded: 2026-10-16T22:43Z
Check the source to verify that this is the current version before use.