INCH-POUND

MIL-DTL-3943/7J
6 June 2007
SUPERSEDING
MIL-DTL-3943/7H
11 May 1999

DETAIL SPECIFICATION SHEET

DECORATION, DISTINGUISHED SERVICE MEDAL, ARMY


This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE





REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Gilding Metal

FINISH:

-1: PENDANT: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

SUSPENSION BAR: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:42Z
Check the source to verify that this is the current version before use.

-2: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:

PENDANT:

HEIGHT (pendant and suspension bar):

-1: 1-31/32 inches (REF)

-2: 1 inch (REF)

DIAMETER:

-1: 1-1/2 inches (REF)

-2: 3/4 inch (REF)

THICKNESS:

-1: 0.215 inch ± 0.010 inch

-2: 0.110 inch ± 0.010 inch

SUSPENSION BAR (Dash No. 1 only):

HEIGHT (overall): 9/32 inch (REF)

WIDTH (overall): 1-3/8 inches (REF)

THICKNESS (at thickest point): 0.160 inch ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Dash No. -2 is one piece construction.

3. The suspension ribbon bar for Dash No. -1 shall be made from brass wire 0.045 inch ± 0.002 inch in diameter and shall be riveted to the suspension bar at each end.

4. The pendant shall be secured to the suspension bar by a swivel joint formed by a round bar from the pendant passing completely through the suspension bar and the end peened.

5. Enamel color shall be blue as indicated. The enamel color shall conform to TIOH Hard Enamel Color Chip Number 20.

6. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

7. Pierced areas shall be as indicated.

8. Decoration set shall consist of a regular size medal, a miniature size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Style 5, Type V with a Class 2 or 2A pad.

9. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/52.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:42Z
Check the source to verify that this is the current version before use.

10. The lapel button shall conform to MIL-DTL-11484/4.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Review activities:
DLA – CT

Preparing activity:
Army - IH
(Project No. 8455-2007-060)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:42Z
Check the source to verify that this is the current version before use.