INCH-POUND

MIL-C-39014/2H
AMENDMENT 1
19 April 1991

MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC
(GENERAL PURPOSE),
ESTABLISHED RELIABILITY,
STYLE CKR06, NATO TYPE DESIGNATION NCC62

This amendment forms a part of MIL-C-39014/2H, dated 5 May 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Voltage-temperature limits, delete and substitute:

"

Capacitance change with reference to 25°C	
Steps A through D of MIL-C-39014, voltage-temperature limit cycle table Bias = 0 volt	Steps E through G of MIL-C-39014, voltage-temperature limit cycle table Bias = rated voltage

"

Resistance to soldering heat: Add "The immersion depth for capacitors with standoffs shall be .024 inch minimum."

PAGE 7

Marking: Add the sentence, "At the option of the manufacturer, marking may be on one side of the capacitor."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - TD
Air Force - 99

User activities:
Army - AT, AV, ME
Navy - MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1738)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:24Z
Check the source to verify that this is the current version before use.