INCH-POUND

MIL-H-48620(AR)
AMENDMENT 2
17 June 1991
SUPERSEDING
AMENDMENT 1
29 August 1980

MILITARY SPECIFICATION

HEAD ASSEMBLY
(PERISCOPE M32CE1)

This amendment forms a part of Military Specification MIL-H-48620(MU), dated 30 April 1979, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.7.1, Delete and substitute:

"3.7.1 Pre-vibration/pre-shock, daylight viewing area. The incident line of sight shall emerge perpendicular to Datum Plane "Y" in deflection within 0.20 mil and be elevated 20 mils ± 0.30 mil "above" the deflection plane as defined. The deflection direction is defined by the plane which is perpendicular to Datum Plane "Y" and parallel to the intersection of Datum Planes "Y" & "W". The term "above" indicates that the emerging line of sight is rotated away from Datum Plane "W"."

PAGE 7

* 3.12, Delete and substitute:

"3.12, Sealing.- The head assembly shall show no evidence of leakage in excess of 0.1 pounds per square inch (psi) when subjected to an internal pressure of 5 ± 0.10 psi for a minimum of 1 hour. The interior atmosphere of the accepted head assembly shall contain nitrogen (having a dew point of at least as low as minus 25°F at atmospheric pressure) between 0.25 and 0.50 pound

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

4.6.4.1, Delete and substitute:

"4.6.4.1 Collimation, pre-vibration/pre-shock, daylight viewing area.

Prior to performing this test and the following tests of 4.6.4.2 and 4.6.4.3, disengage the index pin "D" from the index plate "E" of the test fixture and place the 10 second level on surface "C" of the leveling base. The bubble of the level shall be centered within its graduation lines. If it is not, then adjustment is required in accordance with the procedures specified in paragraphs 7 and 8 of the set -up instructions contained on Drawing F8247391. With the index pin "D" disengaged from the index plate an surface "C" of the leveling base level, view through the auto-collimator of the Support Assembly Collimator 10548767 positioned at the daylight viewing area and observe the projected target image. The center of the target image (apparent intersecting point of the horizontal and verticle reticle lines) leaving the penta prism shall be elevated 20 mils above the reference line of sight of the viewing auto-collimator within the tolerance specified in 3.7.1, when measured by means of the target image graduations and the auto-collimator's micrometer knobs. Record this measurement for use in the subsequent test of 4.6.8.

NOTE: If the auto-collimator contains an erecting system, the center of the target image will appear 20 mils below the reference lines of sight of the auto-collimator. If it does not contain an erecting system, the center of the target will appear 20 mils above the reference line of sight of the auto-collimator."



* 4.6.10, line 2, Delete "0.25 and 0.50" and substitute "0.0 and 0.50"

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1240-AB30)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.