INCH-POUND

MIL-S-48461B(AR)
AMENDMENT 2
5 July 1993
SUPERSEDING
AMENDMENT 1
14 SEPTEMBER 1987

MILITARY SPECIFICATION

SENSOR, CANT ANGLE: 11732800

This amendment forms a part of MIL-S-48461B(AR), dated 30 June 1981, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* Add "REF" following the Inspection Equipment drawing numbers.

* 3.3.4, delete in its entirety and substitute:

"3.3.4 Peaking frequency. Periodic signal components plus harmonics of the input signal, except for the 400 Hz signal, shall be less than 2% peak of the E_{EH} and E_{JM} signals over the bandwidth from 10 Hz to 1 MHz. (See 4.6.2.4)"

PAGE 13

* TABLE II:

Item 7, delete "Spurious signal components" and substitute "Peaking frequency"

Item 9, delete in its entirety and substitute:

"9	Sealing B	3.4	4.6.4.3 "

AMSC N/A FSC 1220
Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.

PAGE 14

* TABLE III:

Item 101, delete "101" and substitute "* 101"

Item 104, delete "Spurious signal components" and substitute "Peaking frequency"

* Below TABLE III, add:

"* NOTE: Performance of this test at ± 15° pitch shall be performed at monthly sample and first article test only."

PAGE 15

* Delete paragraph 4.6.1 in its entirety and substitute:

"4.6.1 Test equipment. The test equipment in Table VI may be used where specified to perform the required test. If alternate test equipment is to be used, the design shall be submitted for review and approval to U.S. ARMY ARDEC, PICATINNY ARSENAL, NJ 07806-5000, ATTN: SMCAR-QAF-I."

PAGE 16

* 4.6.2.1, delete in its entirety and substitute:

"4.6.2.1 Rotor output voltages. Use items 2 and 3 of Table VI to verify compliance with the requirements of 3.3.1, with the exception of performance at ± 15° of pitch, which shall not apply to 100 % inspection. (See 4.5.4.1 and Table III, Item 101)."

* 4.6.2.4, delete "Spurious signal components" and substitute "Peaking frequency"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.

PAGE 17

* 4.6.3.6, delete in its entirety and substitute:

"4.6.3.6 Humidity. Place the assembly in a humidity chamber and subject it to the humidity test specified in MIL-STD-810, method 507.1, Procedure IV. During steps 4,6, and 8 of procedure IV, subject the assembly to the performance tests of 4.6.2.1 and 4.6.2.2 at zero degree (0°F) only. After exposure, subject the assembly to the performance tests of 4.6.2."

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing Activity:
Army - AR

(Project 1220-A403)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.