INCH-POUND

MIL-W-70467 (AR)
AMENDMENT 7
15 October 1996
SUPERSEDING
AMENDMENT 6
24 February 1995

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, PRACTICE: XM274

This amendment forms a part of MIL-W-70467(AR), dated 15 May 1986, and is approved for use by the US Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete "XM274" and substitute "M274".

1.1: Delete "XM274" and substitute "M274".

2.1.1, Under Specifications/Military:

Add "QAC-1415 Rocket/2.75 Inch/Hydra 70: Assembly, Packing and Testing
MIL-F-50548 Fuzes, Rocket, M423 and M427 Less Booster and Booster Lead".

PAGE 2

2.1.2: Delete "XM274" and substitute "M274".

Delete

"Missile Interim Specification
MIS-30862 Rocket, 2.75 Inch, Complete Round with MK66 Motor: Assembling, Packing, and Testing
MIS-50263 Rocket, 2.75 Inch, Complete Round with MK40 and MK 4 Motor: Assembling, Packing, and Testing".

After DRAWINGS, add

"12937864 Packing and Marking for Container, Metal, for 2.75 Inch Rocket, M151/M274
9215617-1 Device, Safety and Arming (Loading)".


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 202640-23T03:29Z
Check the source to verify that this is the current version before use.

Delete

"INSPECTION EQUIPMENT DRAWINGS
9201212 Envelope Drawing, Safety, and Arming Inspection Equipment".

PAGE 3

3.3: Delete in its entirety and substitute

"3.3 M423 safe & arm. All M423 S&A devices, prior to assembly, shall have been subjected to and passed all applicable requirements of MIL-F-50548."

Delete paragraphs 3.3.1 through 3.3.8 in their entirety.

PAGE 6

4.3.1: Delete "XM274" and substitute "M274".

Delete

| | | |
|---|---|---|
| "Plug | 937[illegible]245 | 15 |
| Device, Safety and Arming | 921[illegible]619-1 | 25 |
| Device, Safety and Arming (Detonator only) | 921[illegible]617-1 | 10 |
| Device, Safety and Arming | 921[illegible]619-1 | 75 |
| Rotor Housing Assembly | 888[illegible]719 | 10 |
| Spring, Detent | 888[illegible]713 | 10 |
| Spring, Setback Weight | 888[illegible]718 | 10 |
| Gear and Pinion Assembly No. 1 | 8883703 | 25 |
| Gear and Pinion Assembly No. 2 | 8883700 | 25 |
| Escapement Gear and Pinion Assembly | 8883710 | 25 |
| Lever Assembly | 8883706 | 30 |
| Rotor Assembly | 8883744 | 20 |
| Inner Plate Assembly | 9260804 | 20 |
| Escapement and Gear Assembly | 8883692 | 20" |

Add

| | | |
|---|---|---|
| "Washer, Felt | 12599973 | 15 |
| Cap, Smoke Tube | 12599974 | 15 |
| Tube, Smoke | 12599976 | 15 |
| Smoke, Tube Assembly | 12599977 | 25" |

PAGE 7

TABLE I: Delete "XM274" and substitute "M274".

PAGE 8

TABLE I: Delete "XM274" and substitute "M274".



Source: https://assist.dla.mil - Downloaded: 202640-23T03:29Z
Check the source to verify that this is the current version before use.

Delete

| | | | |
|---|---|---|---|
| "Plug (Dwg. 9370245) Examination for defects | 15 | 3.2 | 4.4.2.8 |
| Device, Safety and Arming (9215619-1) Examination for defects | 25 | 3.2 | 4.4.2.11 |
| Device, Safety and Arming (Detonator only) (9215617-1) Examination for defects | 10 | 3.2 | 4.4.2.12". |

PAGES 9, 10 and 11

TABLE I: Delete in their entirety.

PAGE 12

TABLE I: Delete "XM274" and substitute "M274".

| | | | |
|---|---|---|---|
| Delete "Load test of pillars | 20 | 3.2 | 4.5.5.13" |

Add the following:

| | | | |
|---|---|---|---|
| "Tube, Smoke (Dwg. 12599976) Examination for defects | 16 | 3.2 | 4.4.2.25 |
| Cap, Smoke Tube (Dwg. 12599974) Examination for defects | 15 | 3.2 | 4.4.2.26 |
| Washer, Felt (Dwg. 12599973) Examination of defects | 15 | 3.2 | 4.4.2.27 |
| Smoke Tube Assembly (Dwg. 12599977) Examination for defects | 25 | 3.2 | 4.4.2.28" |

PAGE 13

4.4.1: Delete "XM274" and substitute "M274".

PAGE 18

4.4.2.5, Under Major 101:

Delete "Diameter" and substitute "Outside Diameter".

Add Major 103 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

| | | | |
|---|---|---|---|
| "103 Location of Hole | 0.40% | 3.2 | Gage". |

Add Minor 202 as follows:

| | | | |
|---|---|---|---|
| "202 Inside Diameter | 0.65% | 3.2 | Gage". |

PAGE 21

4.4.2.8: Delete in its entirety.

PAGE 22

4.4.2.9: Delete Major 104 in its entirety.

Add Minor 204 as follows:

| | | | |
|---|---|---|---|
| "204 Diameter of partition hole | 0.65% | 3.2 | Gage". |

PAGE 23

4.4.2.10: Delete Major 107 in its entirety.

Add Majors 111 and 112 as follows:

| | | | |
|---|---|---|---|
| "111 Retainer groove diameter | 0.40% | 3.2 | Gage |
| 112 Retainer groove location | 0.40% | 3.2 | Gage". |

PAGES 24 through 36

TABLE I: Delete in their entirety.

PAGE 37

4.4.2.23: Delete Minor 201 in its entirety.

PAGE 38

4.4.2.24: Delete "XM274" and substitute "M274".

Under Major 103, Ballistic Test: Delete "36" and substitute "24".

PAGE 39

Add 4.4.2.25 enclosed as Page 5 (38a).
Add 4.4.2.26 enclosed as Page 6 (38b).
Add 4.4.2.27 enclosed as Page 7 (38c).
Add 4.4.2.28 enclosed as Page 8 (38d).

PAGE 41

4.5.5: Delete "4.5.5" and substitute "4.5.4".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.25 | Tube, Smoke | SHEET 1 OF 1 | 12599976 |
| | | | NEXT HIGHER ASSEMBLY 12599977 |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined. | | | |
| Major | | | | |
| 101 | Wall thickness of radius end | .40% AQL | 3.2 | Gage |
| Minor | | | | |
| 201 | Total length | .65% AQL | 3.2 | Gage |
| 202 | Outside diameter | .65% AQL | 3.2 | Gage |
| 203 | Wall thickness | .65% AQL | 3.2 | Gage |
| 204 | Thread pitch | .65% AQL | 3.2 | Gage |
| 205 | Evidence of poor workmanship | .65% AQL | 3.1B | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.26 | Cap, Smoke Tube | SHEET 1 OF 1 | 12599974 |
| | | | NEXT HIGHER ASSEMBLY 12599977 |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined. | | | |
| Major | None defined. | | | |
| Minor | | | | |
| 201 | Height | .65% AQL | 3.2 | Gage |
| 202 | Inside diameter | .65% AQL | 3.2 | Gage |
| 203 | Thread pitch | .65% AQL | 3.2 | Gage |
| 204 | Evidence of poor workmanship | .65% AQL | 3.2 | Visual |

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570a, 1 Feb 85, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.27 | Washer, Felt | SHEET 1 OF 1 | 12599973 |
| | | | NEXT HIGHER ASSEMBLY 9370252 |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined. | | | |
| Major | None defined. | | | |
| Minor | | | | |
| 201 | Thickness | .65% AQL | 3.2 | Gage |
| 202 | Hole diameter | .65% AQL | 3.2 | Gage |
| 203 | Evidence of poor workmanship | .65% AQL | 3.18 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

# CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.28 | Smoke Tube Assembly | SHEET 1 OF 1 | 12599977 |
| | | | NEXT HIGHER ASSEMBLY 9370252 |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined. | | | |
| Major | None defined. | | | |
| 101 | Joint of smoke tube cap and smoke tube taped incorrectly (note 4) | .40% AQL | 3.2 | Visual |
| 102 | Smoke tube cap installed incorrectly | .40% AQL | 3.2 | Visual |
| Minor | | | | |
| 201 | Weight of smoke composition | .65% AQL | 3.2 | Gage |
| 202 | Evidence of poor workmanship | .65% AQL | 3.18 | Visual |

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570a, 1 Feb 85, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

PAGE 42

4.5.5: Delete in its entirety.

Delete paragraphs 4.5.5.1 through 4.5.5.5 in their entirety.

PAGE 43

Delete paragraphs 4.5.5.6 through 4.5.5.12 in their entirety.

PAGE 44

Delete paragraphs 4.5.5.13 through 4.5.5.17 in their entirety.

PAGE 45

4.5.5.18: Delete in its entirety.
4.5.5.19: Delete in its entirety.
4.5.5.20: Delete in its entirety.

PAGE 46

4.5.7: Delete "MIS-30862" and substitute "QAC-1415".

Delete "or MIS-50263, or whichever is applicable".

Delete "box" or "boxes" and substitute "box or metal container" or boxes or metal containers" where applicable, at 7 places.

Third paragraph, 7th line, after containers: Add

"(fiber containers are not required if fastpac is used)".

PAGE 47

4.5.7: Delete "or MIS-50263, or whichever is applicable".

4.5.8: Delete second paragraph and substitute:

"The sample warheads shall be packed and packaged in accordance with QAC-1415 except that dummy 2.75 inch rocket motors shall be substituted. The warheads shall be equally divided and temperature conditioned to -50° ± 5°F, 70° ± 15°F and 160° ± 5°F. The conditioning time shall be 8 hours minimum and 24 hours maximum."

Delete "box" or "boxes" and substitute "box or metal container" or boxes or metal containers".



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

4.5.12: Delete and substitute:

"4.5.12 Ballistic test. The requirements for the warhead is to provide a visible signature, at impact, with a functional reliability of greater than 93.7% when fired with MK66 motors. Performance shall be evaluated by ground launching a sample of 36 M274 warheads. Twelve rockets shall be conditioned at -50°F + 5°F, 12 rockets at 70°F ± 15°F, 12 rockets at 150°F - 5°F for a minimum period of 6 hours. All 36 rockets shall be fired from an M260 or M261 launcher to impact at 6000 meters. If three or more warheads fail to function, the lot shall be rejected."

PAGE 51

5.: Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Unit packaging

5.1.1 S&As. When shipping the loaded S&As to the warhead assembly site, the S&As shall be packaged Level A, B, or C as required by the procuring activity, in accordance with MIL-STD-2073-1, meeting the requirements of the Code of Federal Regulations, Title 49 (49CFR).

5.1.2 M274 warhead. The M274 Practice Warhead shall be packaged in accordance with drawing 8886811.

5.1.3 Rocket (M274 warhead with MK66 motor). The M274 warhead with MK66 motor configuration shall be packaged in accordance with drawing 9335613.

5.2 Packing

5.2.1 S&As. When shipping the loaded S&As to the warhead assembly site, the S&As shall be packed Level A, B, or C as required by the procuring activity, in accordance with MIL-STD-2073-1, meeting 49CFR.

5.2.2 M274 warhead. The M274 Practice Warhead shall be packed in accordance with drawing 8886810.

5.2.3 Rocket (M274 warhead with MK66 motor). The M274 warhead with MK66 motor configuration shall be packed in accordance with drawing 9340713. Specification PAC-1415 shall also apply.

5.3 Marking.

5.3.1 Unit packaging.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

5.3.1.1 S&As. The Level A, B, or C unit packages shall be marked in accordance with MIL-STD-129 and the following:

a. Nomenclature and quantity
b. National stock number (or part number)
c. Lot number

5.3.1.2 M274 warhead. The M274 Practice Warhead shall be marked in accordance with drawing 8886811.

5.3.1.3 Rocket (M274 warhead with MK66 motor). The M274 warhead with MK66 motor configuration shall be marked in accordance with drawing 9335613.

5.3.2 Packing

5.3.2.1 S&As. Item identification marking for the Level A, B, or C packing shall be in accordance with MIL-STD-129 and as required in 49CFR, part 172, subpart D, paragraph 172.301(A) and the following:

a. Nomenclature and quantity
b. National stock number (or part number)
c. Lot number
d. Gross weight
e. Any other special marking
f. POP marking (see note)

Note: After completion of the requirements of 5.4, POP marking shall be applied to the pack as specified by the Government.

5.3.2.2 M274 warhead. The M274 Practice Warhead shall be marked in accordance with drawing 8886810.

5.3.2.3 Rocket (M274 warhead with MK66 motor). The M274 warhead with MK66 motor configuration shall be marked in accordance with drawing 9340713.

5.4 Performance oriented packaging (POP). Packaging and packing as specified above shall be in accordance with the applicable packing method as specified in the 49CFR. Further, it shall be demonstrated that the pack meets all of the POP test requirements in accordance with 49CFR. A POP test shall be generated in accordance with DI-PACK- 81059 following the tests. POP testing may be waived if an acceptable analogy in accordance with 49CFR, to another pack which has successfully completed the testing, can be made. An analogy must also be documented in accordance with DI-PACK-81059. When completed, either POP test report must be kept on file by the contractor and must also be submitted to the US Army Armament Research, Development and Engineering Center, Attn.: AMSTA-AR-AEP, Picatinny Arsenal, NJ 07806-5000 (Note: IF a POP test is prepared against an acceptable analogy, the analogous POP test report must also be submitted to AMSTA-AR-AEP.). The POP marking to be applied to the exterior pack shall be as specified by the Government after review and acceptance of the submitted POP reports.


Source: https://assist.dla.mil -- Downloaded: 202610-23T03:29Z
Check the source to verify that this is the current version before use.

5.5 Item hazard classification. All US manufacturers shall make certain that the item is tested in accordance with Part 173, Subpart C, Section 173.58(A) of 49CFR Parts 106-180 to assign the proper class and division for all explosives (Division 1.1, 1.2, 1.3, and 1.4 explosives). Registration with the Associate Administrator of Hazardous Materials Safety is required in accordance with Part 173, Subpart C, Section 173.56(B) (1) or 173.56 (C) of 49 CFR so that markings in accordance with 172, Subpart D, Section 172.301(A) and 172.320(A) are met.
All foreign manufacturers shall make certain that the dangerous goods are tested in accordance with United Nations Committee of Experts on the Transportation of Dangerous Goods (as published in UN Document ST/SG/AC.10.1, latest revision, Recommendations on the Transport of Dangerous Goods - Test and Criteria) to determine the proper division (Class 1-9 and division 1.1 - 1.6 for explosives). Registration for air and vessel transport is required for each manufacturing country's National Competent Authority. The Hazard Classification Letter of Competent Authority is issued in accordance with part 2, para. 1.3 of the International Civil Aviation Organization (ICAO) Technical Instructions and approves the hazard classification and compatibility group assignment and assigns the appropriate shipping name to the dangerous goods. The proper packaging, marking and labeling is contained in the United Nations Committee of Experts on the Transportation of Dangerous Goods (as published in UN Document ST/SG/AC.10.1, latest revision, Recommendations on the Transport of Dangerous Goods).
For air transport, the dangerous goods must comply with the provisions of the International Air Transport Association (IATA) Dangerous Goods Regulations and for vessel transport, the dangerous goods must comply with the provisions of the Intergovernmental Maritime Organization's International Maritime Dangerous Goods Code (IMDG Code).
These documents shall be forwarded to the US Army Armament Munitions and Chemical Command (AMCCOM), Attn.: AMSMC-PC and AMSMC-SFS (Rock Island, IL 51299-6000).

5.6 Ammunition data cards. Data card information shall be as specified in accordance with MIL-STD-1167."



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A993)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.