MIL-L-11484 / 86
26 September 1969

# MILITARY SPECIFICATION SHEET

## Lapel Button, ACTIVE RESERVIST, Army

This specification is mandatory for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-L-11484.

MATERIAL: RED BRASS

DIMENSIONS (INCHES):
- BASE:
  - HEIGHT (OVERALL): 45/64 (REF)
  - WIDTH (OVERALL): 7/32 (REF)
  - THICKNESS (AT THICKEST POINT): .050 ± .005
- DEVICE:
  - HEIGHT (OVERALL): 29/64 (REF)
  - WIDTH (OVERALL): 11/64 (REF)
  - THICKNESS (AT THICKEST POINT): .050 (REF)
- ASSEMBLED THICKNESS (THICKEST POINT): .100 ± .010

FINISH:
- BASE (FASCES): COPPER FLASH, OXIDIZED LIGHTLY RELIEVED
- DEVICE (MINUTE MAN): GOLD PLATED POLISHED

NOTES:
1. THE DEVICE SHALL BE SUPERIMPOSED ON THE BASE IN THE LOCATION SHOWN BY SOLDERING OR WITH A MINIMUM OF TWO RIVETS.

2. THE ATTACHING DEVICE SHALL BE A REGULAR PRONG AND A REGISTERING PRONG. BOTH PRONGS SHALL BE LOCATED ON THE VERTICAL CENTERLINE OF THE BASE WITH THE REGULAR PRONG LOCATED 5/16 ± 1/32 INCH ABOVE THE BOTTOM OF THE INSIGNIA AND THE REGISTERING PRONG LOCATED 7/64 ± 1/32 INCH BELOW THE TOP OF THE INSIGNIA. THE REGISTERING PRONG SHALL BE .044 ± .002 INCH IN DIAMETER AND 3/32 ± 1/64 INCH IN LENGTH.

3. THE LAPEL BUTTON SHALL BE LACQUERED AFTER ASSEMBLY.

CUSTODIAN:
ARMY - IH
REVIEW ACTIVITY:
OTHER - DP
USER ACTIVITY:
ARMY - SM

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY,
UNITED STATES ARMY

FSC 8455

Project No. 8455-A278



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:35Z
Check the source to verify that this is the current version before use.