NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/90D
26 October 1998
SUPERSEDING
MIL-DTL-11484/90C
27 September 1996

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, LENGTH OF SERVICE (15, 20, 25, and 30 YEARS), NATIONAL TRANSPORTATION SAFETY BOARD, DEPARTMENT OF TRANSPORTATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

-1, -2



-1, -2



-3, -4



-5, -6, -7, -8

-3 thru -8

DASH NO.
-1: 30 Years (Male)
-2: 30 Years (Female)
-3: 25 Years (Male)
-4: 25 Years (Female)
-5: 20 Years (Male)
-6: 20 Years (Female)
-7: 15 Years (Male)
-8: 15 Years (Female)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:36Z
Check the source to verify that this is the current version before use.

MATERIAL: Gilding Metal

FINISH:

BASE:
-1 thru -6: Hard Enameled, Gold Plated, Mirror-Like Polished and shall match TIOH Metal Finish Chip Number 6.
-7, -8: Hard Enameled, Nickel Plated, Silver Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 12.

DEVICE: Hard Enameled, Nickel Plated, Silver Plated, Oxidized, Relieved, Polished Highlights and shall match TIOH Metal Finish Chip Number 15.

DIMENSIONS:

BASE:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Edge): 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

DEVICE:
HEIGHT (Overall): 5/16 inch (0.79 cm) (REF)
WIDTH (Overall): 3/8 inch (0.95 cm) (REF)
THICKNESS (At Shield): 0.070 inch ± 0.010 inch (0.178 cm ± 0.025 cm)

THICKNESS (Assembled): 0.120 inch ± 0.010 inch (0.305 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The colors shall conform to the TIOH color chip numbers listed below or the standard sample.

COLOR	CHIP NO.
Red	1
Blue	18
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The device shall be located as shown and shall be secured to the base by means of two rivets located on the horizontal center line of the device.

5. Dash No. -1 and -2 shall have a minimum 2 point, Grade A diamond set in a three bead setting located as shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:36Z
Check the source to verify that this is the current version before use.

6. The designs shown are illustrative of the female lapel buttons. The male designs are identical to the female except for the omission of the lugs and the addition of a prong and pick with flat ball type catch.

7. The lug for Dash No. -2, -4, -6, and -8 shall be an integral part of the base and shall be cut into the working die. The lug shall be 1/8 inch ± 1/64 inch (0.318 cm ± 0.04 cm) outside diameter with a 1/16 inch ± 1/64 inch (0.159 cm ± 0.04 cm) diameter hole centered inside the lug. Each lapel button shall have a jump ring 3/16 inch ± 1/64 inch (0.476 cm ± 0.04 cm) outside diameter wire mounted through the lug. The jump ring shall be formed from 0.035 inch ± 0.005 inch (0.089 cm ± 0.013 cm) diameter brass wire. The ends of the wire shall be either straight or bias cut and shall be aligned and together. The jump ring shall have the same finish as the base.

8. Attaching device for Dash No. -1, -3, -5, and -7 shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0959)

Civil Agency Coordinating Activity:
DOT

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:36Z
Check the source to verify that this is the current version before use.