NOT MEASUEREMENT SENSITIVE

MIL-DTL-11484/90G(IH)
30 April 2025
SUPERSEDING
MIL-DTL-11484/90F(IH)
30 June 2020

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, LENGTH OF SERVICE (15, 20, 25, AND 30 YEARS), NATIONAL TRANSPORTATION SAFETY BOARD, DEPARTMENT OF TRANSPORTATION

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



DASH NO.
-1: 30 Years (Male)
-2: 30 Years (Female)
-3: 25 Years (Male)
-4: 25 Years (Female)
-5: 20 Years (Male)
-6: 20 Years (Female)
-7: 15 Years (Male)
-8: 15 Years (Female)

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:36Z
Check the source to verify that this is the current version before use.

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
BASE:
-1 thru -6: Epoxy resin (Stoning epoxy) 24 K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
-7, -8: Epoxy resin (Stoning) Nickel Plated, Silver Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 12.
DEVICE: Epoxy resin (Stoning epoxy) Nickel Plated, Silver Plated, Oxidized, Relieved, Polished Highlights and shall match TIOH Metal Finish Chip Number 15.

DIMENSION:
BASE:
DIAMETER: 5/8 inch (REF)
THICKNESS (At edge): 0.050 inch ± 0.005 inch
DEVICE:
HEIGHT (Overall): 5/16 inch (REF)
WIDTH (Overall): 3/8 inch (REF)
THICKNESS (At edge): 0.070 inch ± 0.005 inch
THIKNESS (Assembled): 0.120 inch ± 0.010 inch

ATTACHING DEVICE:
1. The device shall be located as shown and shall be secured to the base by means of two rivets located on the horizontal center line of the device.

2. The designs shown are illustrative of the female lapel buttons. The male designs are identical to the female except for the omission of the lugs and the addition of a prong and pick with flat ball type catch.

3. The lug for -2, -4, -6, and -8 shall be an integral part of the base and shall be cut into the working die. The lug shall be 1/8 inch ± 1/64 inch outside diameter with a 1/16 inch ± 1/64 inch diameter hole centered inside the lug. Each lapel button shall have a jump ring 3/16 inch ± 1/64 inch outside diameter wire mounted through the lug. The jump ring shall be formed from 0.035 inch ± 0.005 inch diameter brass wire. The ends of the wire shall be either straight or bias cut and shall be aligned and together. The jump ring shall have the same finish as the base.

4. Attaching device for -1, -3, -5, and -7 shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:36Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy resin shall be applied to the lapel button as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
Red	#1
Blue	#18
Black	#26
White	#28

NOTES:

1. The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

2. For -1 and -2 shall have a minimum 2 point, Grade A diamond set in a three bead setting located as shown.

3. If hard cloisonné enamel is used, the base material must be Gilding Metal 95/5 (UNS Alloy No. C-210).

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2025-088)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:36Z
Check the source to verify that this is the current version before use.