INCH-POUND

MIL-F-48863C (AR)
Amendment 3
02 October 1999
SUPERSEDING
Amendment 2
17 April 1989

MILITARY SPECIFICATION

FUZE, GUIDED MISSILE, M934E6 PARTS
ASSEMBLY, LOADING AND PACKING FOR

This amendment forms a part of Military Specification MIL-F-48863C (AR), dated 01 July 1985, and is approved for use by the U.S. Army Armaments, Research, Development, and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1 Specifications and Standards:

Specifications, Military:

* Delete “MIL-S-45743” in its entirety.

PAGE 2

2.1.1 Specifications and Standards:

* Specifications, Military: Delete “MIL-S-46860” in its entirety.

* Standards: add the following:

“ANSI J-STD-001 - Requirements for Soldered Electrical and Electronic Assemblies

ANSI/ASQC Z1.4-1993 - Sampling Procedures and Tables for Inspection”

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

Standards, Military:

* Delete “MIL-STD-105” and “MIL-STD-794” in their entirety.

* Add “MIL-STD-2073-1 - Standard Practice for Military Packaging”.

PAGE 3

2.2:

CODE OF FEDERAL REGULATIONS:

* Delete in its entirety and substitute the following:

49 CFR 100-180 - Department of Transportation Rules for Regulations for the Transportation of Explosive and Other Dangerous Articles.

Title 49 CFR is available from the Superintendent of Documents, Government Printing Office, Washington, D.C. Orders for the above publication should cite “49 CFR 100-180 (latest revision)”.”

PAGE 9

* 3.2.13, TABLE I, Line 13, Pin 6, change “950K” to “300K”

PAGE 13

3.3.2, Add the following:

“3.3.2.1 Process control documents. Where adhesives, sealants or lubricants are permitted or required by the drawings, a process control document is required in accordance with MIL-A-48078.”

3.3.3, Line 4, after “… in the contract” add, “and shall include an analysis of Critical Defect material handling (see 3.5).”

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

* 3.3.4, Delete in its entirety and add the following:

"3.3.4 Workmanship. The fuze and its components shall be fabricated and finished in a thorough, workmanlike manner. It shall be free of surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning methods used shall not be injurious to any part nor shall any part be contaminated by the cleaning agents. Solder joints shall be in accordance with the visual inspection standards of ANSI/J-STD-001. Soldering of metallic ribbon leads to solder coated conductors by the reflow process shall also be in accordance with the quality assurance standards of ANSI/J-STD-001."

PAGE 14

* 3.4.1, TABLE II, Line 13, Pin 6, change "900K" to "280K"

PAGE 15

Add the following:

"3.5 Critical defect material handling. An analysis of Critical Defect material handling shall be made in accordance with MIL-A-48078. This analysis shall be provided to the Government prior to First Article Submission."

PAGE 18

4.3.2.1.1/b, Delete "(SD)" after "Static Detonator Safety".

Under req/method paragraph column: Delete "3.2.9.3"

Delete "SD – Initiate detonator by self destruct mode."

PAGE 22

* 4.4.2, Delete "MIL-STD-105" and substitute "ANSI/ASQC Z1.4-1993"

PAGE 31

4.4.2.8, Major 101, Delete ".25%" and substitute "--".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

PAGE 34

4.2.2.11, Minor 204, Delete “UNF-28” and substitute “UNF-2B”.

PAGE 35

4.4.2.12, Add new major category:

“Category Major	Exam or Test	AQL or 100%	Req. Para.	Para. Ref/ Insp. Meth.
102	Adhesive on shoulder-stop pins missing or improperly applied following cure.”	.40%	3.3.1.3	Visual

PAGE 36

4.4.2.13, Add new major category:

“Category Major	Exam or Test	AQL or 100%	Req. Para.	Para. Ref/ Insp. Meth.
106	Sealant on 22 g lock screw missing or improperly applied.”	100%	3.3.1.3	Visual

PAGE 39

4.4.2.16, Minor 203, In Column labeled Paragraph Reference/Inspection Method delete “Gage” and substitute “Visual”.

* Minor 204, In Column labeled examination or test: Replace “MIL-S-45743” with ANSI/J-STD-001”.

Minor 205, In Column labeled examination or test add “1/”.

Notes: Add “1/ cracks are permitted in part number 9297032 after potting provided they do not alter the physical integrity and profile of the potted module and epoxy has

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

not exuded beyond the surface of 9297032. The cracks may be of any configuration in any location on the module."

PAGE 41

4.4.2.18, Major 105, Delete "Slope, diameter, and true position of window recess to outside diameter" and substitute "Slope and virtual condition of the window recess".

PAGE 47

4.4.2.24, Major 111, Delete "Actuator" and substitute "Lever".

PAGE 49

4.4.2.26, Major 101, Delete "B-B" and substitute "A-A".

Major 104, Delete "A-A" and substitute "B-B".

PAGE 50

4.4.2.26, Minor 201, Delete "from centerline large" and substitute "centerline to the large"

Minor 205, Delete "breaks in to" and substitute "breaks into".

Minor 206, Delete "size and true position" and substitute "maximum and minimum virtual condition".

PAGE 51

4.4.2.26, Minor 208, Delete "size and true position" and substitute "maximum virtual condition".

Minor 209, Delete "size and true position" and substitute "maximum and minimum virtual condition".

PAGE 54

4.4.2.27, Major 116, Delete "Large radius and true position shown in section P-P" and minimum virtual condition inspected with respect to Datums C-D and E-F of the large radius shown in section P-P".

Major 117, Delete "angled large threaded hole, Datum H," and substitute "Datum H".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

Minor 203, Delete “Depth of second deepest recess” and substitute “Depth of third deepest recess”.

PAGE 57

4.4.2.30, Major 101, Delete “Dimension and location” and substitute “Maximum and minimum virtual condition”.

PAGE 61

4.4.2.34, Major 101, Delete “lens height” and substitute “Distance from tab to end opposite the lens”.

PAGE 62

4.4.2.35, Major 101, Delete “lens height” and substitute “Distance from tab to end opposite the lens”.

PAGE 65

4.4.2.38, Major 106, Under Column labeled Paragraph Reference/Inspection Method delete “3.2.13.8”

Major 106, Under Column labeled Requirements Paragraph add “3.2.13.8”

PAGE 67

* 4.4.3, Delete “MIL-STD-105” and substitute “ANSI/ASQC Z1.4-1993”

PAGE 73

4.5.20.1, Line 3, Delete “Move” and substitute “With the rotor locked in the armed position, move”.

PAGE 74

* 5.1, Change 49CFR171-190 to 49CFR171-180

* 5.1.1, Delete in it’s entirety and substitute the following:

“5.1.1 Protection. The fuzes shall be packed in fiberboard cartons with fiberboard partitions in accordance with MIL-STD-2073-1.”

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

* 6.3, Delete “US Army Armament, Munitions, and Chemical Command, ATTN: AMSMC-QAR-I, Dover, NJ 007801.” and substitute “US Army TACOM-ARDEC, ATTN: AMSTA-AR-QAA-R, Picatinny Arsenal, NJ, 07806-5000.”

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for nay inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Preparing activity:
Army-AR

(Project 1336-0034)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.