INCH-POUND

MIL-F-48877A (AR)
AMENDMENT 3
19 October 2001
SUPERSEDING
AMENDMENT 2
25 April 2000

MILITARY SPECIFICATION

FUZE, ROCKET: M439 PARTS AND ASSEMBLY WITH DETONATOR

MIL-F-48877 was inactivated after 12 March 1998 for new design.

This Amendment forms a part of Military Specification MIL-F-48877A (AR**),** dated 13 October 1994**,** and is approved for use by the U.S**.** Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of Defense.

PAGE 4

* 3.13.3: Delete "12.0 +/- 0.5 g's minimum for a period of 5 seconds" and substitute " 11.5 g's minimum for a minimum of 5 seconds".

PAGE 6

* 3.20: Delete "Figure 1" and substitute " Figure 2".

PAGE 17

Table II, under Molded Electronics Assembly, delete "Table VI" and substitute " Table III", two places.

PAGE 20

4.4.2a: Delete "III" and substitute "IIA".

DISTRIBUTION STATEMENT A. Approved for public release- distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

4.4.2a: Title block, delete “III” and substitute “IIA”.

PAGE 26

4.4.2.5: Under Major 101, delete “Level III” and substitute “Level lI”.

PAGE 29

4.4.2.8: Delete “(70 deg +5 deg)” and substitute “(72 deg 30 min +/- 2 deg 30 min)”.

PAGE 30

4.4.2.9: delete “(82 deg + 6 deg)” and substitute “(85 deg +/- 3 deg)”.

Delete “(61 deg +6 deg)” and substitute “(64 deg +/- 3 deg)”.

Delete “(64 deg +6 deg)” and substitute “(67 deg +/- 3 deg)”.

PAGE 31

4.4.2.10: Delete “(86 deg +6 deg)” and substitute “(89 deg +/- 3 deg)”.

Delete “(64 deg +6 deg)” and substitute “(67 deg +/- 3 deg)”.

PAGE 32

4.4.2.11: Delete “(45 deg + 6 deg)” and substitute “(48 deg +/- 3 deg)”.

Delete “(86 deg + 6 deg)” and substitute “(89 deg +/- 3 deg)”.

Delete “(64 deg + 6 deg)” and substitute “(67 deg +/- 3 deg)”.

PAGE 33

4.2.12: Delete “(90 deg + 4 deg)” and substitute “(92 deg +/- 2 deg)”.

Delete “(64 deg +6 deg)” and substitute “(67 deg +/- 3 deg)”.

PAGE 42

4.4.2.21: Under Major 101, delete “Level III” and substitute “Level lI”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

PAGE 48

4.4.2.26: Major 110, delete “Alignment of detonator cavity with the outside diameter” and substitute “Alignment of detonator cavity with the outside diameter across the rotor housing posts”.

Add Major 104: “114 3.10 Distance from rotor flat to edge of base minimum Gage” Level III

PAGE 64

4.5.2: Tenth line, delete “week” and substitute “month”.

PAGE 68

* 4.5.15: Delete “12.0 g’s” and substitute “11.5 g’s”.

PAGE 69

4.5.17: Third line, delete “Table VI” and substitute “Table III”.

4.5.18: Fourth line, delete “4.5.18” and substitute “4.5.17”.

PAGE 74

* 4.5.29: Delete “ three (3) seconds” and substitute “five (5) seconds”.

PAGE 79

4.5.35: Seventh line, add:

“For permanent record, an accurate means of capturing and storing the charge signature in digital form shall be used. The reproduced charge signature shall be accurate to the nearest hundredth of a volt, with a sample rate of 100 samples per millisecond, minimum. The charge signatures in digital form shall be submitted with the FAT and LAT reports.”

PAGE 80

4.5.35.3.1: Delete in its entirety and substitute:

“ 4.5.35.3.1 First article sample. The acceptance of the first article sample is based on meeting the acceptance criteria specified below.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

Failure category		Accept	Reject
Function time delay (para. 4.5.35.2)	3	4	
Charge circuit continuity **(**para. 4.5.20**)**	3	4	
Function upon S&A arming *	0	1	
Dud **		2	3
Total failures (Combined failures from above categories)		3	4

*Functions upon S&A arming: Any unit that functions at less than 1 second after motor ignition.
** Duds **:** Any unit that fails to function."

PAGE 81

4.5.35.3.2: Delete in its entirety and substitute:

" 4.5.35.3.2 Lot acceptance sample. The acceptance of the lot acceptance sample is based on meeting the acceptance criteria specified below.

Failure category	Accept	Reject
Function time delay (para. 4.5.35.2)	4	5
Charge circuit continuity (para. 4.5.20**)**	4	5
Function upon S&A arming*	0	1
Dud * *	2	3
Total failures (Combined failures from above categories)	4	5

*Functions upon S&A arming: Any unit that functions at less than 1 second after motor ignition.
** Duds **:** Any unit that fails to function."

The margins of this amendment are marked with asterisks to indicate where changes to the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-1024)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.