INCH - POUNDS

MIL-W-48856B (AR)
AMENDMENT 4
25 September 2002
SUPERSEDING
AMENDMENT 3
11 May 1989

MILITARY SPECIFICATION

WARHEAD SECTIONS, GUIDED MISSILE, H.E.
M258E6 LOADING, ASSEMBLING, AND PACKING

This amendment forms a part of MIL-W-48865B (AR), dated 7 August 1985, and is approved for use by the US Army Armament, Research, Development, and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Title, delete “WARHEAD SECTIONS” and substitute “WARHEAD SECTION”

* 1.1, Line 3, delete “Sections” and substitute “Section”

PAGE 2

* 2.1.1, Standards, delete “MIL-STD-105” and “MIL-STD-453” in their entirety.

* 2.1.2, Delete “US ARMY ARMAMENT, RESEARCH AND DEVELOPMENT CENTER (ARDC)” and substitute “US ARMY ARMAMENT, RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER (ARDEC)”

* 2.2:

Title 49, line 2, delete “for” and substitute “and”

Add the following:

“AMERICAN SOCIETY FOR QUALITY CONTROL (ASQC)

Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Application for copies should be addressed to the American Society for Quality Control, 611 East Wisconsin Ave, Milwaukee, WI 53202)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E 1742 – Standard Practice for Radiographic Examination

(Application for copies should be addressed to the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959)"

PAGE 3

* 3.3, Line 2, delete "MIL-STD-453" and substitute "ASTM E 1742"

PAGE 4

3.4, Line 3, after "requirements" add "prior to loading of explosives and after machining of explosives"

PAGE 5

* 3.5.2, Line 2, delete "greater than or equal to 950K OHMS" and substitute "greater than or equal to 300K OHMS"

PAGE 6

3.5.6:

Add at the bottom, "6(+) 8 0.25uA ≥ 300K**"

PAGE 7

3.6.2, under "RESISTANCE (OHMS)", delete "=" and substitute "≥" in two places.

PAGE 9

* 4.4.2a, Sampling plans, last line, delete "MIL-STD-105, Inspection Level II" and substitute "ANSI/ASQC Z1.4, Inspection Level II"

PAGE 11

* Paragraph Reference/Inspection Method column, Delete "MIL-STD-331 Test III 5/" and substitute "MIL-STD-331 Test 111 5/".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

PAGE 13

4.4.2.2:

Major defects 101, 109 and 110, delete and substitute:

"101 Continuity does not conform to requirements prior to loading 100% 3.4 4.5.3/4.5.5/Gage
109 J1 connector damaged, not secure 1/, or misaligned prior to loading 100% 3.2 Visual/Manual/Gage
110 P3 connector damaged prior to loading 100% 3.2 Visual/Manual"

Add new major defects 111 and 112 as follows:

"111 Continuity does not conform to requirements after loading 100% 3.4 4.5.3/4.5.5/Gage
112 P3 connector damaged after loading 100% 3.2 Visual/Manual"

PAGE 16

4.4.2.5:

Major 109 and 110, delete "100%" and substitute "2/"

Add new note 2/ as follows:

"2/ The units shall be sampled in accordance with paragraph 4.5.8."

PAGE 17

* 4.5.2, Line 2, delete "MIL-STD-453" and substitute "ASTM E 1742"

PAGE 19

Add new paragraph 4.5.8 as follows:

"4.5.8 Center of gravity and roll unbalance. These tests shall be conducted 100% until 1000 consecutive defect-free units have been tested. After 1000 consecutive defect-free units have been tested, the sampling frequency shall be reduced to 1 in 25 units. If a defect is encountered in the reduced sample, the previous 50 units and the next 250 units shall be inspected 100%. If no defects are found during the screening, then the sampling shall be reduced to 1 in 25 units."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

* 5.1, add “and 6.4 herein.” At the end.

* 6.3, Delete line 3 and 4 in their entirety and substitute the following “Commander, TACOM-ARDEC, ATTN: AMSTA-AR-QAA-R, Picatinny Arsenal, NJ 07806-5000.”

* Add new paragraph 6.4 as follows:

6.4 Performance oriented packaging (POP). Prior to shipment, the manufacturer shall make sure the container has been tested by a Government approved POP test laboratory for compliance with the POP requirements in accordance with Title 49 Code of Federal Regulations. Test will be to a weight at least 10% greater than the actual gross weight to be marked on the tested container. POP marking shall not be applied to the container until verified by the Government. The POP test report shall be generated by the manufacturer/laboratory in accordance with DI-PACK-81059 (Data Item Description) following the test. The report must be kept on file by the contractor and must also be submitted in accordance with DI-PACK-81059 to the US Army TACOM-ARDEC, ATTN: AMSTA-AR-WEP, Picatinny Arsenal, NJ 07806-5000. For multi-year contracts, the contractor shall re-perform POP testing at a certified test laboratory if: (a) the initial POP test report expires before the end of the contract or (b) there is a change in container manufacturer or design of the exterior shipping container. No re-test is needed if all packaging is purchased while under an unexpired POP test.”

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in the notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and the relationship to the last previous amendment.

Custodian:
Army – AR

Preparing activity:
Army- AR

(Project 1336-0036)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.