MIL-A-27261A(USAF)
AMENDMENT 4
9 Feb 87
SUPERSEDING
AMENDMENT 3
30 DEC 82

MILITARY SPECIFICATION

ACCELEROMETER, AIRCRAFT

This amendment forms a part of MIL-A-27261A(USAF), dated 8 NOV 66, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete "2.1" and add: "2.1 Government documents".

* Add: "2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

2.1 Under "SPECIFICATIONS, Federal", delete QQ-P-416 and add the following:

"PPP-B-601 Boxes, Wood, Cleated Plywood
PPP-B-636 Box, Shipping, Fiberboard"

Under "SPECIFICATIONS, Military", add:

"MIL-C-83488 Coating, Aluminum, Ion Vapor Deposited"

* Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

* Under "STANDARD, Military", delete "MIL-STD-831" and "change MIL-STD-100 to read DoD-STD-100; same title". Add "C" to the end of MIL-STD-810. Delete "MS33586" and its title and add: "MIL-STD-889 Dissimilar Metals".

* Add: 2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:25Z
Check the source to verify that this is the current version before use.

of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or information services.)"

3.3.5 Delete "MS33586" and add: "MIL-STD-889".

* Add: "3.3.8 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item."

PAGE 4

3.5.1 In line 2, delete "0.010" and add: "0.018". In line 3, delete "500 and 3,000 cpm" and add: "5 and 50 Hz".

* 3.6 Line 6 delete "MIL-STD-100" and add: "DoD-STD-100".

PAGE 5

* Delete "3.7" and add: "3.7 Case. The case shall be in accordance with figure 1 and the requirements specified herein. The design of the case shall be such that the mechanism may be removed from the case and replaced without the use of special tools and fixtures unless they are approved by the contracting activity."

* Delete "3.7.1" in its entirety.

PAGE 7

3.10.2 Last sentence: Delete "2-1/2 to 8 pounds" and add "3 ± 1 pounds".

3.11.2 add: "The force required to operate the locking device shall be 4.5 ± 1 pounds".

PAGE 8

3.17.2 Delete entire paragraph and add: "3.17.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by th cognizant engineerng activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

PAGE 10

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:25Z
Check the source to verify that this is the current version before use.

* Add: "4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted the government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the government to acceptance of defective material."

PAGE 11

* Delete "4.4.2".

* 4.5.1 Delete "d. Sealing" and add: "h. Locking Mechanism Operation".

PAGE 13

* Delete "4.6.4" in its entirety.

* 4.6.9 and 4.6.10 Line 4 add "C" after MIL-STD-810.

PAGE 15

4.6.12 In lines 14 and 15, delete "500 to 3,000 cpm" and add "5 to 50 Hz"; in line 20, delete "1,800 cpm: and add "30 Hz"; and in lines 24 and 26, delete "1,200 cpm" and add "20 Hz".

* 4.6.13 Line 3 add "C" after MIL-STD-810; delete "516" and add: "516.2".

* 4.6.15 Line 4 add: "C" after MIL-STD-810; delete "2" and add "6". Line 4 delete "504" and add "504.1".

* 4.6.16 Line 3 add "C" After MIL-STD-810. Line 4 delete "507" and add: "507.1, procedure I".

* 4.6.17 Line 3 add "C" after MIL-STD-810 and delete "508" add: "508.1" and remove the period before procedure.

* 4.6.19 Line 3 add "C" after MIL-STD-810. Line 4 delete "509" and add: "509.1".

PAGE 16

Add new paragraph: "4.6.22 Locking mechanism operation. The accelerometer shall be locked with the auxiliary pointers approximately 0.2g from the main pointer and the readings shall be noted. The accelerometer shall then be subject to the shock test specified in 4.6.13. At the conclusion of the shock test, the indications of the auxiliary pointers shall not be changed by more than 0.2g. The force required to look or unlock the mechanism shall be 4.5 ±1 pounds."

* Delete "4.7" and add: "4.7 Inspection of packaging. The inspection of the preservation-packaging and interior package marking shall be in accordance with group A and B quality conformance inspection requirements, section 4 of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:25Z
Check the source to verify that this is the current version before use.

The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129."

PAGE 17

Delete Section 5 in its entirety and add;

"5 PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Accelerometer shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Accelerometer shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each accelerometer shall be packaged in quantity unit packs of one each in accordance with Method 1C1 of sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the accelerometer when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each accelerometer shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The Industrial preservation of accelerometer shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Accelerometer packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistant with the protection required.

5.2.2 Level B. Accelerometer packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather resistant, unless otherwise specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:25Z
Check the source to verify that this is the current version before use.

immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged accelerometer shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

* Delete "6.3".

* Delete "6.5"

* Delete "6.6".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
AIR FORCE - 99

Preparing Activity:
AIR FORCE - 71

Project Number:
6610 - F137

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:25Z
Check the source to verify that this is the current version before use.