INCH-POUND
MIL-PRF-27208/10C
11 October 2006
SUPERSEDING
MIL-PRF-27208/10B
13 June 2001

PERFORMANCE SPECIFICATION SHEET


RESISTORS, VARIABLE, WIRE WOUND, (ADJUSTMENT TYPE, LEAD SCREW ACTUATED), STYLE RT26

This specification is approved for use by all Departments and agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for style RT26 adjustment type, lead screw actuated, wire wound, variable resistors.

* 1.2 Part or Identifying Number (PIN). Resistors covered by this specification are identified by a PIN which consists of a basis style and a coded number. The PIN is in the following form:



2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAT, Post Office Box 3990, Columbus Ohio 43218-3990, or emailed to resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:17Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

* 2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-27208 - Resistor, Variable, Wire wound, Nonprecision, General Specification for.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil or from the Standard Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document, and the references cited herein (except for associated specifications, specification sheets, or MS sheets); the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-27208.

3.2 Interface and physical dimensions. The resistors shall meet the interface and physical dimensions specified in figure 1.

3.3 Power rating. The power rating shall be 0.250 watt, based on full load operation at an ambient temperature of 85°C.

3.4 Nominal resistance value, maximum resolution, and maximum rated ac or dc working voltage. Nominal resistance values, maximum resolutions, and maximum rated ac or dc working voltages are specified in table I.

TABLE I. Nominal resistance value, maximum resolution, and maximum rated ac or dc working voltage.

Nominal resistance value	Maximum resolution 1/	Maximum rated ac or dc working voltage
Ohms	Percent	Volts
10	1.85	1.58
20	1.50	2.23
50	1.39	3.54
100	1.05	5.00
200	0.86	7.07
500	0.65	11.10
1,000	0.57	15.80
2,000 2/	0.44	22.30
5,000 3/	0.35	35.40

1/ Maximum resolution shown are theoretical.
2/ Value based on the use of wire having no less that a 0.001 inch nominal diameter.
3/ Value based on the use of wire having no less that a 0.0008 inch nominal diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:17Z
Check the source to verify that this is the current version before use.




FIGURE 1. Style RT26.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:17Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
0.001	0.03	0.016	0.41	0.040	1.02	0.115	2.92	0.175	4.45
0.003	0.08	0.018	0.46	0.050	1.27	0.125	3.18	0.250	6.35
0.010	0.25	0.020	0.51	0.075	1.91	0.165	4.19		
0.015	0.38	0.030	0.76	0.100	2.54	0.172	4.37		

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information.
3. Unless otherwise specified, tolerance is ±0.005 (0.13mm).
4. The entire slot of the actuating screw must be above the surface of the unit.

FIGURE 1. Style RT26 - Continued.

3.5 Actual effective electrical travel. The actual effective electrical travel shall be 10 turns minimum and 25 turns maximum.

3.6 Operating torque. The torque required to effect rotation shall be 3 inch-ounce maximum.

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-PRF-27208.

4.2 Dielectric withstanding voltage. In the dielectric withstanding voltage test, the applied potential shall be 600 volts rms at atmospheric pressure, and 250 volts rms at reduced barometric pressure.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:17Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The intended use specified in MIL-PRF-27208 is applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification, and the complete PIN (see 1.2).

* b. If not otherwise specified (see 2.1), the versions of the individual documents referenced will be those in effect on the date of release of the solicitation.

c. Packaging requirements (see 5.1).

6.3 Weight. The maximum weight is 1.3 grams.

* 6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force – 11
DLA - CC

Preparing activity:
DLA-CC

Review activities:
Army - AR, AT, AV, MI
Navy - MC, OS
Air Force - 19

(Project 5905-2006-056)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:17Z
Check the source to verify that this is the current version before use.