MIL-R-27208/2E
19 December 1969
SUPERSEDING
MIL-R-27208/2D
13 December 1968
(See section 6)

MILITARY SPECIFICATION

RESISTORS, VARIABLE, WIRE-WOUND

(ADJUSTMENT TYPE, LEAD-SCREW ACTUATED),

STYLE RT10

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the detail requirements for style RT10, adjustment type, lead-screw actuated, wire-wound, variable resistors.

2. APPLICABLE DOCUMENTS

2.1 The following document of the issue in effect on date of invitation for bids or request for proposal forms a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-R-27208 - Resistors, Variable, Wire-Wound (Adjustment Type), General Specification for.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-R-27208, and as specified herein.

3.2 Design and construction. Resistors shall be of the design, construction, and physical dimensions specified on figure.


3.3 Power rating. The power rating shall be 3/4 watt, based on full-load operation at an ambient temperature of 85° C.

3.4 Nominal resistance value, maximum resolution, and maximum rated ac or dc working voltage. Nominal resistance values, maximum resolutions, and maximum rated ac or dc working voltages are as specified in table I.


3.5 Actual effective electrical travel. Actual effective electrical travel shall be 12 turns minimum, and 18 turns maximum.

3.6 Operating torque. Operating torque shall be a maximum of 8 ounce-inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:15Z
Check the source to verify that this is the current version before use.



FLEXIBLE LEAD TERMINAL TYPE -L



PRINTED-CIRCUIT PIN TERMINAL TYPE -P

INCHES	MM
.003	.08
.010	.25
.015	.38
.020	.51
.025	.64
.028	.71
.031	.79
.032	.81
.050	1.27
.063	1.60
.080	2.03
.093	2.36
.100	2.54
.110	2.79
.115	2.92
.155	3.94
.160	4.06
.170	4.32
.180	4.57
.300	7.62
.315	8.00
.500	12.70
.600	15.24
.750	19.05
1.000	25.40

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.005 (.13 mm).
3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
4. The three leads shall be stranded wire, AWG size 28 to 30, having a minimum length of 6 (152.4 mm); they shall be insulated with polytetrafluoroethylene, stripped .250±.062 (6.35±1.57 mm) from the end, and color coded.

FIGURE 1. Style RT10 resistor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:15Z
Check the source to verify that this is the current version before use.

TABLE I. Nominal resistance value, maximum resolution, and maximum rated ac or dc working voltage.

Nominal resistance value (in ohms)	Maximum resolution 3/	Maximum rated ac or dc working voltage
Ohms	Percent	Volts
100	1.4	8.7
200	1.2	12.3
500	0.8	19.4
1,000	0.7	27.4
2,000	0.5	38.7
5,000 1/	0.4	61.3
10,000 2/	0.3	86.7

1/ Value based on the use of wire having no less than a 0.001-inch nominal diameter.

2/ Value based on the use of wire having no less than a 0.0008-inch nominal diameter.

3/ Maximum resolutions shown are theoretical.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection shall be in accordance with MIL-R-27208.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-R-27208.

6. NOTES

6.1 Notes. In addition to the notes specified herein, the notes specified in MIL-R-27208 are applicable to this specification.

* 6.2 Supersession data. This specification supersedes MIL-R-27208/2D, 13 December 1968.

* 6.3 Weight. The maximum weight is 3.7 grams.

* 6.4 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:15Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - MI, MU, EL
Navy - EC, AS, OS
Air Force - 11, 17, 85
DSA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Preparing activity:
Air Force - 11

Agent:
DSA-ES

(Project 5905-0693-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:15Z
Check the source to verify that this is the current version before use.