NOT MEASUREMENT SENSITIVE

MIL-I-14639/2D
15 July 1992
SUPERSEDING
MIL-I-14639/2C
6 October 1975

MILITARY SPECIFICATION SHEET

# INSIGNIA, GRADE, PRIVATE FIRST CLASS (E-3), ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-14639.




DASH NO.
-1: Subdued
-2: Bright

MATERIAL:
-1: Red brass, Yellow brass or zinc aluminum (as applicable)
-2: Red brass

FINISH:
-1: Baked flat black enamel
-2: Mirror-like polished

DIMENSIONS: As shown

THICKNESS: 0.055 inch ± 0.005 inch (0.139 cm ± 0.12 cm)

NOTES:

1. The prongs shall be located on a horizontal line 5/16 inch ± 1/16 inch (0.79 cm ± 0.16 cm) above the lowest point of the insignia, equidistant from each side and 11/16 inch ± 1/64 inch (1.75 cm ± 0.16 cm) on centers.

2. Insignia may be manufactured using 22 karat gold plate with nickel underplating for commercial sale only.

Custodian:
Army - IH

Preparing activities:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0675)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 202610-18T03:55Z
Check the source to verify that this is the current version before use.