NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-6106/26D(USAF)
29 April 1985
SUPERSEDING
MIL-R-6106/26C(USAF)
14 July 1983

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 50 AMPERES, SPST, NO,
WITH 5 AMPERE SPDT AUXILIARY, HERMETICALLY SEALED

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.





FIGURE 1. Relay, outline drawing.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:27Z
Check the source to verify that this is the current version before use.



CIRCUIT DIAGRAM
(OBSERVE POLARITY)

INCHES	MM	INCHES	MM
.005	0.13	.375	9.52
.010	0.25	.38	9.7
.06	1.5	.437	11.10
.100	2.54	.44	11.2
.11	2.8	1.91	48.5
.171	4.34	2.000	50.80
.203	5.16	2.44	62.0
.31	7.9	2.50	63.5

NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 (0.25 mm) for three place decimals and ±.03 (0.8 mm) for two place decimals.
4. Terminal numbers need not appear on the relay header providing there is affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified.
5. Suppression level - the maximum induced transient voltage (back EMF) shall be 50 volts, referenced to zero volts.
6. Terminal studs shall be rated at 171°C.

FIGURE 1. Relay, outline drawing - Continued.

Source: https://assist.dla.mil -- Downloaded: 202610-17T06:27Z
Check the source to verify that this is the current version before use.

TABLE I. Rated contact load (amperes per pole) (case grounded).

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac 3 phase			
		Main		Aux		Main(Hz)		Aux(Hz)		Main(Hz)		Aux(Hz)	
		NO	NC	NO	NC	400	50/60	400	50/60	400	50/60	400	50/60
Resistive	50	50	50	5	5	65	---	5	---	---	---	---	---
Inductive	50	---	---	3	3	65	---	3	---	---	---	---	---
Inductive	20	50	50	---	---	---	---	---	---	---	---	---	---
Motor	---	---	---	---	---	---	---	---	---	---	---	---	---
Lamp	---	---	---	---	---	---	---	---	---	---	---	---	---
Transfer, load	---	---	---	---	---	---	---	---	---	---	---	---	---
Mechanical life													
Reduced current	---	---	---	---	---	---	---	---	---	---	---	---	---
Min. current		APPLICABLE PER SPECIFICATION											

REQUIREMENTS·

COIL DATA

Nominal operating voltage: 28 V dc.

Maximum operating voltage: 29 V dc.

Pickup voltage 15 V dc, maximum, @ 25°C.

Dropout voltage. 1.5 @ 25°C.

Hold voltage 7 V dc @ 25°C.

Duty: Continuous.

Coil current 0 280 ampere, maximum, @ 28 V dc, 25°C.

OPERATIONAL DATA.

Operate time· 35 milliseconds maximum with nominal coil voltage.

Dropout time 25 milliseconds maximum from nominal coil voltage.

Contact load. See table I.

Contact bounce time: 5 milliseconds, maximum.

Contact drop: 150 millivolts, maximum, initially
175 millivolts, maximum, after life test.

Overload current· 400 amperes.

Rupture current 500 amperes.

PHYSICAL DATA

Weight 11 ounces, maximum.

Terminal strength· Applicable.

Finish Instrument black.

Source: https://assist.dla.mil -- Downloaded: 202640-17T06:27Z
Check the source to verify that this is the current version before use.

Seal. Hermetic.

Terminal barriers:

Base cover: Melamine Fiberglass, MIL-P-15037.

Barrier: Nylon 6/6, Type 1, grade A, class 1, black per L-P-395.

Can: Aluminum, fused tin plated.

ENVIRONMENTAL DATA

Temperature range. -55°C to+71°C.

Altitude: 60,000 feet.

Dielectric withstanding voltage (sea level):

	Initial	After life
Coil to case	1,000 V rms	1,000 V rms
Aux contacts	1,000 V rms	1,000 V rms
All other points	1,500 V rms	1,150 V rms

Dielectric withstanding voltage (altitude)

	60,000 feet	
Coil to case	500 V rms	500 V rms
Aux contacts	500 V rms	500 V rms
All other points	700 V rms	700 V rms

Insulation resistance 100 megohms, minimum @ 500 volts.

Vibration (sinusoidal). .06 D.A., 10 Hz to 55 Hz, 10 G's 55 Hz to 1,500 Hz, 15 G's, 55 Hz to 1,000 Hz.

Shock 25 G's for 11 milliseconds.

Acceleration: 10 G's

Part number M6106/26-001

Custodian:
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Agent:
DLA - ES

Preparing activity.
Air Force - 85

(Project 5945-F596-1)

Source: https://assist.dla.mil -- Downloaded: 202640-17T06:27Z
Check the source to verify that this is the currentversion before use.