NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-6106/38B
AMENDMENT 1
10 July 1999

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, TYPE I, MAGNETIC LATCH, PERMANENT MAGNET DRIVE, LOW LEVEL TO 5 AMPERES, 2PDT, HERMETICALLY SEALED

This amendment forms a part of MIL-PRF-6106/38B, dated 15 September 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* FIGURE 1, delete “Silicone Rubber Gasket AMS 3332, Shore Hardness 25 ±5 Thickness .040 ±.005” and substitute “See Note 10”

PAGE 5

* Note 9, delete and substitute “9. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals shall be gold plated. One system for gold plating that may be used is ASTM B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.”

* Add a Note 10, “10. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 25 ±5, thickness .040 ±.005. Gasket material according to AMS 3332 has been considered acceptable.”

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1058-10)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:31Z
Check the source to verify that this is the current version before use.