NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-6106/43A
AMENDMENT 1
10 July 1999

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 65 AMPERES, 1 PNO DOUBLE BREAK, HERMETICALLY SEALED, TYPE I

This amendment forms a part of MIL-PRF-6106/43A, dated 29 April 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* FIGURE 1, delete “Power Terminals No. .190-32 UNF-2A, Stud MS35338-43, Lockwasher AN961-10T, Flatwasher MS35650-305T,Nut,Hex, 2 Places and substitute “Power Terminals No. .190-32 UNF-2A; Stud; Lockwasher; Flatwasher;Nut, Hex, 2 Places”

* FIGURE 1, delete “Coil Terminals No. 138-32 UNC-2A, Stud MS35338-41, Lockwasher AN961-6T, Flatwasher MS35649-265T, Nut, Hex.” and substitute “Coil Terminals No. 138-32 UNC-2A; Stud; Lockwasher; Flatwasher; Nut, Hex.”

PAGE 4

* Terminal insulator, terminal barrier, delete and substitute:

“Terminal insulator: Nonconductive. One type of insulator for meeting this requirement is MIL-I-24768/1. The insulator shall enable the product to meet the performance requirements of this specification.

Terminal barrier: Nonconductive. One type of insulator for meeting this requirement is PA110 G43 A99900 KB207 UB090 PA176 E12 per ASTM D 4066-82. The insulator shall enable the product to meet the performance requirements of this specification.”

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1058-13)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:33Z
Check the source to verify that this is the current version before use.