INCH-POUND

MIL-PRF-6106/43B
AMENDMENT 1
19 July 2001

PERFORMANCE SPECIFICATION SHEET

RELAY, ELECTROMAGNETIC, 65 AMPERES, 1PNO DOUBLE BREAK, HERMETICALLY SEALED, TYPE I

This amendment forms a part of MIL-PRF-6106/43B, dated 10 November 2000, and is approved for use by all Departments and Agencies of the Department of Defense.

The attached insertable replacement page is listed below and is a replacement for the stipulated page. When the new page has been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
3	3

Custodians:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1137-03)

Review activities:
Air Force - 99

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:32Z
Check the source to verify that this is the current version before use.

TABLE I. Mounting, termination, and operating characteristics.

Dash no.	Coil	Coil data										Time (milliseconds-maximum) 2/							
		Nominal			Maximum		Max pickup voltage			Drop out volt-age 1/	Hold volt-age 1/	Coil sup. back EMF max	CKT. type	Oper-ate 2/	Re-lease 3/	Bounce			
																Main		Aux.	
		Volts	Freq Hz	Res Ω ±10%	Volts	Amp @ 25°C	Nom-inal 1/	High temp test	Cont curr-ent test							NO	NC	NO	NC
-001	X1X2	28	DC	200	29	.160	18	20	21	1.5	7.0	--	A	35	25	3	--	5	--
-002	X1X2	28	DC	200	29	.160	18	20	21	1.5	7.0	50	B	35	25	3	--	5	--

1/ Over temperature range.
2/ With nominal coil voltage.
3/ From nominal coil voltage.

TABLE II. Rated contact load (amperes per pole) case grounded.

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 1/			
		Main		Aux		Main		Aux		Main		Aux	
		NO	NC	NO	NC	400 Hz	50/60 Hz	400 Hz	60 Hz	400 Hz	50/60 Hz	400 Hz	60 Hz
Resistive	50	50	---	---	---	65	---	---	---	---	---	---	---
Inductive	20	50	---	---	---	---	---	---	---	---	---	---	---
Inductive	50	---	---	---	---	65	---	---	---	---	---	---	---
Lamp	50	17	---	---	---	---	---	---	---	---	---	---	---
Lamp	25	20	---	---	---	---	---	---	---	---	---	---	---
Transfer load		---	---	---	---	---	---	---	---	---	---	---	---
Mechanical life reduced current	200	7	---	---	---	---	---	---	---	---	---	---	---
Mixed loads	50	2.5	---	---	---	5	---	---	---	---	---	---	---

1/ Absence of value indicates relay is not rated for 3 phase.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:32Z
Check the source to verify that this is the current version before use.