MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, (INCLUDING ESTABLISHED RELIABILITY (ER) TYPES).
PERMANENT MAGNET DRIVE, LOW LEVEL TO 10 AMPERES, 3 POT,
ALL WELDED, HERMETICALLY SEALED

This amendment forms a part of MIL-R-6106/29B, dated 24 May 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

ELECTRICAL CHARACTERISTICS: Delete "Dielectric withstanding voltage (sea level):" in its entirety and substitute:

"Dielectric withstanding voltage (sea level):

	Initial	After life tests
Coil to case	1,000 V rms	750 V rms
Aux contacts	---	---
All other points	1,250 V rms	1,000 V rms "

Custodians:
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-0721)

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:28Z
Check the source to verify that this is the current version before use.