INCH-POUND

MIL-R-6106/42(USAF)
AMENDMENT 1
28 September 1990

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 3PDT MAIN
CONTACTS, 4PDT AUXILIARY CONTACTS, 135
AMPERES, 115/200 VOLTS, 400 HERTZ, GASKET SEALED

This amendment forms a part of MIL-R-6106/42(USAF), dated 14 July 1983, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

REQUIREMENTS, Electrical, Contact voltage drop (initial), delete and substitute the following:

"Mains: .150 volt average, .175 volt maximum at rated current.
Auxiliary: .300 volt average, .400 volt maximum at 5 amperes."

REQUIREMENTS, Electrical, After life test, delete and substitute the following:

"Mains: .175 volt average, .200 volt maximum at rated current.
Auxiliary: .400 volt average, .450 volt maximum at 5 amperes."

CONCLUDING MATERIAL

Custodian:
Air Force - 85

Preparing activity:
Air Force - 85

Agent:
DLA - ES

Review activities:
Air Force - 99
DLA - ES

(Project 5945-F719)

AMSC N/A

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:32Z
Check the source to verify that this is the current version before use.