INCH-POUND

MIL-R-6106/42(USAF)
AMENDMENT 2
10 Nov 1993
SUPERSEDING
AMENDMENT 1
28 September 1990

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, 3PDT, MAIN CONTACTS, 4PDT AUXILIARY CONTACTS, 135 AMPERES, 115/200 VOLTS, 400 HERTZ, GASKET SEALED

This amendment forms a part of MIL-R-6106/42(USAF), dated 14 July 1983 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

*FIGURE 1, Coil Transient Suppression Circuit: Delete "H" and substitute "N".

PAGE 3

REQUIREMENTS, Electrical, Contact voltage drop (initial), delete and substitute the following:
"Mains: .150 volt average, .175 volt maximum at rated current.
Auxiliary: .300 volt average, .400 volt maximum at 5 amperes."

REQUIREMENTS, Electrical, After life test, delete and substitute the following:
"Mains: .175 volt average, .200 volt maximum at rated current.
Auxiliary: .400 volt average, .450 volt maximum at 5 amperes."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodian:
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5945-F757)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T06:32Z
Check the source to verify that this is the current version before use.