MIL-E-1/1632B
25 MAR 1983
SUPERSEDING
MIL-E-1/1632A
30 January 1975

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6BZ6

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the electron tube described herein shall consist of this specification sheet and the latest issue of MIL-E-1.

DESCRIPTION: Pentode, miniature, semi-remote cutoff

Outline	---	5-2 (EIA)
Base	---	E7-1
Envelope	---	T5-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	g1	k	h	h	a	g2	g3 int sd

ABSOLUTE RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ec3	Ehk	Rgl	Pp	Pg2
Unit:	V	V dc	V dc	V dc	V dc	v	Meg	W	W
Maximum:	6.9	330	0	165	---	200	1.0	2.3	0.55
Minimum:	5.7	---	---	---	---	Note 1	Note 2	---	---
TEST CONDITIONS:	6.3	125	-1.0	125	0	0	---	---	---

GENERAL:

Qualification - Required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:09Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSP LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1								
1266	Total grid current	3	Ec1 = -2 V dc	0.65	II	Ic1	0	-1.5	µA dc
1306	Transconductance (1)			0.65	II	Sm	7,000	12,500	µmhos
1201	Short and discontinuity detection			0.4	II	---	---	---	---
	Quality conformance inspection, part 2								
1336	Heater-cathode leakage			4.0	II	Ihk	---	10	µA dc
1301	Heater current			4.0	Code G	If	275	325	mA
1256	Electrode current (anode)			4.0	Code G	Ib	10.0	25.0	mA dc
1256	Electrode current (screen grid)			4.0	Code G	Ic2	3.0	7.0	mA dc
1306	Transconductance (2)		Ef = 5.7 V	2.5	I	ΔSm Ef	---	18	%
1306	Transconductance (3)		Ec1 = -4.5 V dc	4.0	Code G	Sm	450	1,700	µmhos
1306	Transconductance (4)		Ec1 = -19 V dc	4.0	Code G	Sm	20	150	µmhos
1306	Transconductance (5)		Ec1 = -8 V dc	4.0	Code G	Sm	250	650	µmhos
1211	Insulation of electrodes			4.0	Code G	---	---	---	---
1246	Audio frequency noise	4	Esig = 700 mV ac; Ebb = 250 V dc; Ecc2 = 250 V dc; Rg1 = 0.1 Meg; Rg2 = 1.0 Meg; Rp = 0.2 Meg; Rk = 4,000 ohms; Ck = 25 µF	2.5	I	---	---	---	---
1331	Direct-interelectrode capacitance		No external shield	4.0	Code G	Cgp	---	0.025	pF
						Cin	5.8	7.6	pF
						Cout	2.0	2.5	pF
						Chk	3.0	4.6	pF
1031	Low-frequency vibration		Ec1 = -2 V dc; Rp = 2,000 ohms	2.5	Code G	Ep	---	250	mV ac

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:09Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSP LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 2-Continued								
1041	Shock		300 G	6.5	Note 5	---	---	---	---
1031	Vibration-fatigue			6.5	Note 5	---	---	---	---
---	Shock and vibration-fatigue-test end points:								
1031	Low-frequency vibration		Ec1 = -2 V dc; Rp = 2,000 ohms	---	---	Ep	---	400	mV ac
1336	Heater-cathode leakage			---	---	Ihk	---	20	µA dc
1306	Change in transconductance (1) of individual tubes			---	---	ΔSmt	---	20	%
2126	Envelope strain			2.5	I	---	---	---	---
1121	Base strain	6		---	---	---	---	---	---
1105	Permanence of marking			---	---	---	---	---	---

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3						
1501	Intermittent life		Group A; Eb = 200 V dc; Ec = 0; Ec2 = 150 V dc; Rk = 180 ohms; Rgl = 1.0 Meg; Ehk = +150 V dc with 117 V ac superimposed	---	---	---	---
---	Intermittent life-test end points: (500 hours)						
1266	Total grid current		Ec1 = -2 V dc	Ic1	0	-3.0	µA dc
1306	Transconductance (1)			Sm	6,000	---	µmhos

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:09Z
Check the source to verify that this is the current version before use.

NOTES:

1. Maximum rating for positive dc heater-cathode voltage shall be 100 V dc.
2. For fixed bias operation, the maximum rating for Rg1 shall be 0.25 megohm.
3. This test shall be performed at the conclusion of the holding period.
4. The rejection level shall be set at the VU meter reading obtained during calibration.
5. This test shall be conducted on the initial lot and thereafter on a lot approximately every 12 months. When one lot has passed, the 12-month rule shall apply. In the event of a lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes. MIL-STD-105, sample size code letter E, shall apply.
6. Not required for qualification.
7. Revision letters are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, OS, MC, CG, SH
Air Force - 11

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5960-3291)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:09Z
Check the source to verify that this is the current version before use.