NOTICE 1
23 October 2012

TEST OPERATIONS PROCEDURE

This Test Operations Procedure (TOP) has been archived per ATEC memorandum dated 18 October 2012.

Requests shall be referred to Headquarters, U.S. Army Test and Evaluation Command, 2202 Aberdeen Boulevard, Aberdeen Proving Ground, MD 21005-5055, usarmy.APG.atec.mbx.atec-standards@mail.mil

Custodians:
Army – TE

Preparing activity:
ATC

AREA ENVR

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY *(Corporate author)*

U. S. Army Test and Evaluation Command
Aberdeen Proving Ground, Maryland 21005

2a. REPORT SECURITY CLASSIFICATION

Unclassified

2b. GROUP

3. REPORT TITLE

U. S. Army Test and Evaluation Command Test Operations Procedure "Missile Support Vehicles"

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*

Final

5. AUTHOR(S) *(First name, middle initial, last name)*

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
21 March 1973	11	14

8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)
b. PROJECT NO.	TOP 2-2-040
c. AMCR 310-6	9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)*
d.	

10. DISTRIBUTION STATEMENT

Approved for public release; distribution unlimited.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
	Headquarters U. S. Army Test and Evaluation Command Aberdeen Proving Ground, Md. 21005

13. ABSTRACT

Provides guidance for evaluation of missile support vehicle physical and operational characteristics. Identifies supporting tests, facilities, and equipment required. Discusses preparation for test requirements. Provides procedures for initial inspection, servicing, vehicle characteristics, safety, endurance, durability, and reliability. Applicable to wheeled and tracked vehicles such as self-propelled launched, loader transporter, launched trailer, and missile support truck.

DD FORM 1 NOV 68 1473 REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED

Security Classification

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Launcher, Missile and Rocket						
Loading Rack (Missile Launcher)						
Missile Carrier						
Missile Guidance & Control						
Missile Launcher						
Missile Support Vehicle						
Trailer, Guided Missile System						
Vehicle, Special Purpose						

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

REFERENCE FILE

U. S. ARMY TEST AND EVALUATION COMMAND
DEVELOPMENT TEST II (ET) - SYSTEM TEST OPERATIONS PROCEDURES

AMSTE-RP-702-101
Test Operations Procedure 2-2-040
AD 764772

21 March 1973

MISSILE SUPPORT VEHICLES

		Paragraph	Page
Section I.	GENERAL		
	Purpose and Scope	1	1
	Background	2	1
	Equipment and Facilities	3	2
II.	TEST PROCEDURES		
	Supporting Tests	4	2
III.	SUPPLEMENTARY INSTRUCTIONS		
	Preparation for Test	5	4
	Initial Inspection and Servicing	6	6
	Vehicle Characteristics	7	7
	Safety Evaluation	8	7
	Endurance, Durability, and Reliability	9	7
APPENDIX.	REFERENCES		9

SECTION I
GENERAL

1. Purpose and Scope. This TOP provides guidance for planning tests of missile support vehicles to assure their conformance with Required Operational Capabilities (ROC's), Development Plans (DP's), and other guidance documents. Subtests suitable for meeting the requirements of development tests I, II, or III or other customer sponsored tests can be selected from those listed in section II.

2. Background. A missile support vehicle is either a tracked or wheeled vehicle designed to load, transport, or launch a missile or transport associated missile system equipment (electrical, mechanical, chemical, etc.). Missile support vehicles generally are categorized according to their specialized function, and they include:

a. Self-propelled launcher - a tracked or wheeled vehicle containing a launch fixture capable of transporting and launching the mounted missile. The vehicle normally features troop seats, missile fin containers, vehicle covers, and electrical firing and missile checkout equipment. The launch fixture generally consists of a chassis, traverse

Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

carriage, and launch beam. Elevation and traversing of the launcher for missile laying are performed manually and/or electrically. The vehicle may contain a suspension lockout system designed for use during missile firing or loading/unloading operations.

b. Loader transporter - a tracked or wheeled vehicle used to transport, load, and unload the missile and/or associated missile equipment.

c. Wheeled launcher trailer - a wheeled trailer used to transport and fire the missile. The launcher mounts on the trailer assembly. Without the launcher mounted, the trailer assembly is sometimes referred to as a mobility kit. The trailer assembly normally is towed by a truck.

d. Missile support truck - a truck with either a box type body or a body having integral sides and front panel. It is usually a flatbed capable of transporting missile equipment (including the missile and warhead containers). The truck is used to tow the wheeled launcher trailer.

3. Equipment and Facilities. Equipment and facilities are covered in the references of section II.

SECTION II
TEST PROCEDURES

4. Supporting Tests. Subtests to be considered in formulating a development test plan, with TOP/MTP and other references, are listed below. The list is generally in a preferred order of completion; factors to consider are discussed in paragraph 5c.

TEST SUBJECT TITLE	PUBLICATION NO.
a. Preparation for Test (refer to para 5)	
b. Automotive.	
Initial Inspection (refer to para 6)	2-2-502
Stowage	2-2-802
Vehicle Characteristics (refer to para 7)	2-2-500
Preliminary Operation	2-2-505
Safety Evaluation (refer to para 8)	2-2-508
Braking, Tracked Vehicles	2-2-627
Braking, Wheeled Vehicles	2-2-608
Steering	2-2-609
Center of Gravity	2-2-800
Gradeability and Side Slope Performance	2-2-610
Toxic Hazards	2-2-614
Winches	2-2-712
Acceleration - Maximum and Minimum Speeds	2-2-602
Standard Obstacles	2-2-611

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

TEST SUBJECT TITLE	PUBLICATION NO.
Night Performance of Combat Vehicles	2-2-616
Electromagnetic Interference (Noncommunications Equipment)	2-2-613
Electromagnetic Emissions (Electronic Equipment)	6-2-542
High and Low Temperatures	[a]2-2-816
Engine and Power Train Cooling Systems	2-2-607
Cold Starting and Warmup	2-2-650
Rain and Freezing Rain	2-2-815
High Altitude Effects	2-2-702
Load Distribution and Ground Pressure	2-2-801
Vehicle Fuel Consumption	2-2-603
Fuels and Lubricants	2-2-701
Tires	2-2-704
Tracks	2-2-705
Traction Devices	2-2-706
Tracked Vehicle Suspension Systems	2-2-714
Towing Resistance	2-2-605
Drawbar Pull	2-2-604
Fording	2-2-612
Noise	3-2-811
Field of Vision, Vehicles	3-2-812
Soft Soil Vehicle Mobility (Prepared Sites)	2-2-619
Off-Road Mobility (Natural Sites)	As determined by ROC, DP, test directive, and available terrain.
Field Shock and Vibration	2-2-808
Security from Detection (Vehicles)	2-2-615
Infrared Emissions from Vehicles	2-2-812
Communication Equipment (Vehicle)	2-2-709
Air Conditioners	10-2-145
Vehicle Heaters - Personnel	2-2-708
Electrical Systems (Automotive)	[b]2-2-601
Solar Radiation	4-2-826
High Humidity	4-2-820
Fungus Resistance	4-2-818
Salt Water and Salt-Laden Air	[a]1-2-604
Logistics-Over-The-Shore (LOTS)	2-2-520
Transportability	1-2-500
Cargo Loading Adaptability (CLA)	2-2-537
Field Tests of Automotive Engines	2-2-721
Radioactive Components	3-2-711
Air Transportability	2-2-512

[a]When published.
[b]When revised.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

TEST SUBJECT TITLE	PUBLICATION NO.
Vehicle Collision and Accident	2-2-621
Endurance Testing of Wheeled Vehicles	2-2-506
Endurance and Reliability (refer to para 9)	2-2-507, [b]2-1-001
Durability (refer to para 9)	1-2-502, [b]2-1-001
Human Factors Engineering	2-2-803
Maintenance Evaluation	[a]1-2-501, TECR 750-15
Value Engineering	In accordance with current directives
Overload Testing (Vehicle)	2-2-626
Missile Station, Erection	5-2-060
Missile Station, Guidance and Launching	5-2-061
Missile Carrier, Self-Propelled	5-2-120
c. Armament.	
Motors, Electrical	9-2-155
Power Generators	9-2-286
Radio Frequency Radiation Hazards to Electroexplosive Devices	[a]3-2-615
Radio Frequency Radiation Hazards to Personnel	3-2-616
Electrical Power Measurements for Vehicle Subsystems	[b]2-2-601
d. Vulnerability.	
Vulnerability to Nuclear Weapons	2-2-618

[a]When published.
[b]When revised.

SECTION III
SUPPLEMENTARY INSTRUCTIONS

5. Preparation for Test

a. Review of Test Guidance.

(1) The subtests that are selected by the test agency are governed by requirements in the ROC's, DP's, other guidance documents, and by test directives from supervising agencies. The levels of acceptable performance are usually stipulated. If adequate test guidance does not exist, the test plan writer will make appropriate inquiries to the responsible directorate at TECOM.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

(2) Certain important characteristics, especially those involving advanced engineering technology, may not be specifically covered by the requirements document but should nevertheless be included in the test plan and evaluated as a part of development test I, II, or III, per AR 1000-1. These may include such features as infrared emissions, shielding against fallout radiation, decontamination of CBR agents, noise measurements, transient voltages, and electromagnetic interference and emissions.

b. Safe Operations During Testing. All hazardous test operations must be covered by a standing operating procedure (SOP) that will provide compulsory safety measures to be followed (e.g., as required by APG Regulation 385-1 at Aberdeen Proving Ground). Some typical operations that are categorized as hazardous are: amphibious operations, carrying bulk quantities of fuel, longitudinal and side slope operation, operation in inclosed chambers (such as cold rooms), and transportation of explosives. Safety measures for routine operations are prescribed in local safety manuals. Lesser routine hazards are covered by internal operating procedures. If a hazardous test is contemplated, the test director should assure that a suitable SOP covers the testing. If none is available, he must write one and obtain approval for its use.

c. Sequence and Selection of Subtests. Of primary consideration in the sequencing of subtests is the need, in the early months of testing, to thoroughly investigate the "critical issues" listed in the Coordinated Test Plan (CTP) in time for the decision meeting. Otherwise sequencing of subtests should consider performing the high-risk, short-duration tests early and the low-risk, long-duration tests later in the test period. When required by a TECOM directive, a formalized assessment of the risk associated with each subtest will be made in accordance with TECR 70-34. The high-risk subtests are those in which a failure may lead to early termination of the vehicle test or justify an early judgment on critical performance parameters.

(1) Such items as stowage compartments, fording kits, cold weather kits, maintenance test packages, heaters, and air conditioners can be utilized and at least partially tested while the vehicle is undergoing endurance testing. Certain tests, such as those involving vulnerability and accident safety, should be scheduled late in the test program because of the possibility of damaging the vehicle. The type of test, availability of certain kits and similar equipment, and the nature of the possible effect of the test phase on the vehicle or equipment being tested are also factors. A safety evaluation, for instance, would be conducted immediately after the initial inspections and preliminary operation so that the safety aspects could be disseminated to interested agencies. Performance tests covering (e.g.) standard obstacles, drawbar pull, cooling, engine cold starting, and mobility should be conducted prior to or at intermediate endurance testing mileages. It is desirable to obtain the performance data before the engine, drive train, and chassis are subjected to the rigors of extensive endurance testing but

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

after adequate run-in. Comparisons of the performance of various vehicles over a number of years will thus be more valid since all will have been tested in generally the same physical condition.

(2) To test and evaluate a missile support vehicle a number of subtests apply. The selection of appropriate tests is dependent upon the type of test (e.g., development test I), the availability of test resources (e.g., number of vehicles, funding, test facilities), the time available for the test, the special characteristics of the vehicle, and the desires of the agency overseeing the test program. The possible test phases that may be included in test plans are listed in paragraph 4; rarely will a vehicle be subjected to all. Certain phases of the development test may require participation by the Boards just as in the past some engineering test phases were combined with the service test when directed by Headquarters, TECOM.

d. Sample Size. The test sample size is usually determined far in advance of testing by the number of vehicles on a production contract, the funds available for testing, or the nature of the test. When the test director has an input regarding the sample size, he should use available mathematical procedures, taking cognizance of stipulated confidence and reliability levels as explained in paragraph 9. Miles that each vehicle must travel are determined simultaneously with sample size.

e. Familiarization and Training. When a vehicle introduces new features, it may be necessary to train operators, maintenance personnel, and the test director. Such training will normally be given by TACOM or a contractor, and should be arranged at an early date.

6. Initial Inspection and Servicing.

a. An initial inspection is conducted to assure that the test items are in good condition and that major component serial numbers and other pretest data are recorded prior to initiation of the test program. These include:

(1) Serial numbers and other identification of vehicle and major components.

(2) Examination of maintenance test package for completeness.

(3) Electrical system output (per TOP/MTP 2-2-601).

(4) Odometer mileage and engine-hour readings.

(5) On-equipment materiel (OEM) stowage (per TOP/MTP 2-2-802).

b. The vehicle is completely serviced to include draining of fluids and refilling with standard fuel, lubricants, and other fluids. The identification and quantity of all fluids used are recorded, and attention is called to unusual quantities. If drain or fill times are

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

unreasonably long, these should be noted together with information on influencing factors such as size of drain plugs.

7. Vehicle Characteristics. Vehicle characteristics including physical dimensions are recorded in accordance with TOP/MTP 2-2-500. A characteristics photograph is taken, and a tabulation of important features is assembled also in accordance with TOP/MTP 2-2-500.

8. Safety Evaluation. An interim safety release should be generated within 60 days of test initiation. The interim safety release recommendation is given based on subtests performed early in the test. The subtests include, but are not limited to, preliminary operation, braking, steering, center of gravity, gradeability, side slopes, toxic hazards, winches, speed, obstacles, and night operations. The safety evaluation does not end with the issuance of the safety release: it is considered to be a continuing subtest throughout the test program and, when required, will include vehicle collision and accident safety.

9. Endurance, Durability, and Reliability.

a. Endurance is a general term that is concerned with the ability of a vehicle to perform satisfactorily under typical field conditions for long periods of time. Endurance tests of tracked vehicles are covered in TOP/MTP 2-2-507 which prescribes test courses and number of miles unless otherwise prescribed by the directive or guidance document. Endurance tests of wheeled vehicles are covered in TOP/MTP 2-2-506.

b. Durability is a precise term that relates to the mathematical probability that a vehicle will be able to operate under typical field conditions for a specified number of miles before requiring major overhaul. Since durability tests require many samples and considerable funding, they are seldom conducted; the endurance test, which is much more limited, is usually conducted instead. TOP 1-2-502 describes a durability test and provides guidance for selecting sample sizes and distances.

c. Reliability is defined as the probability that an item will perform its intended function for a specified time under specified conditions (i.e., the probability of successfully completing a mission without incurring a mission-aborting failure). The reliability requirement is usually expressed as a probability of success for one or more specified operational and environmental cycles or functional sequences (mission). This requirement may be expressed in several ways; e.g., as an acceptable mean-time-between-failure (MTBF). In the MTBF context "T" may be expressed as hours, cycles, rounds, miles, etc. Most of the data for the reliability determination are obtained from the endurance test, which simultaneously provides data for the maintenance evaluation.

d. The matter of endurance, durability, and reliability will be more fully covered in TOP/MTP 2-1-001 when revised.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

Recommended changes to this publication should be forwarded to Commander, U. S. Army Test and Evaluation Command, ATTN: AMSTE-ME, Aberdeen Proving Ground, Md. 21005. Technical information may be obtained from the preparing activity: Commander, Aberdeen Proving Ground, ATTN: STEAP-MT-M, Aberdeen Proving Ground, Md. 21005. Additional copies are available from the Defense Documentation Center, Cameron Station, Alexandria, Va. 22314. This document is identified by the accession number (AD No.) printed on the first page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

APPENDIX
REFERENCES

1. AR 70-38, "Research, Development, Test, and Evaluation of Materiel for Extreme Climatic Conditions."

2. AR 705-25, "Reliability Program for Materiel and Equipment."

3. AR 1000-1, "Basic Policies for Systems Acquisition by the Department of the Army."

4. AMC Supplement 1 to AR 70-10, "Test and Evaluation During Acquisition and Development of Materiel."

5. AMC Supplement 1 to AR 705-50, "Army Materiel Reliability and Maintainability."

6. AMCR 385-12, "Life Cycle Verification of Materiel Safety."

7. AMCP 702-3, "Reliability Handbook."

8. AMCP 706-134, "Maintainability Guide for Design."

9. TECR 70-23, "Equipment Performance Reports."

10. TECR 70-34, "Risk Analysis for Suitability Tests."

11. TECR 385-6, "Verification of Safety of Materiel During Testing."

12. TECR 750-15, "Maintenance Evaluation During Testing."

13. MIL-STD-721B, "Definition of Terms for Reliability Engineering, Human Factors, and Safety."

14. Bekker, M. G., "Introduction to Terrain Vehicle Systems," The University of Michigan Press, Ann Arbor, Michigan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:47Z
Check the source to verify that this is the current version before use.