# MILITARY SPECIFICATION

## CARTRIDGE, 9MM, BALL, NATO, XM882

This Amendment forms a part of Military Specification MIL-C-70508(AR), dated 7 February 1985 and is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Add, "(M882)" after "XM882".

1.1, Last line: Add "(M882)" after "XM882".

PAGE 2

2.1.2 under DRAWINGS 9345111: Add "(M822)" after "XM882".

2.2.1, Delete: "9354344 - Packaging and Marking, Cartridges, 9mm, Ball, NATO, XM882, Cartons, Box Ammunition, M2A1, Box Wirebound" and substitute, "9396206 - Packing and Marking for Box, Wirebound, for Cartridges, Small Caliber".

PAGE 3

3.6, second line: Delete "385" and substitute "375".

PAGE 4

Delete paragraph "3.12" in its entirety and substitute:

"3.12 Compressive force resistance. When subjected to a compressive force of 75 pounds, the average overall length of the sample cartridges shall not be less than 1.140 inches, and no individual cartridge shall be less than 1.125 inches."



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.

PAGE 11

* TABLE II, Delete Note "3" in its entirety and substitute:

"3/ Function and casualty defects shall not exceed the acceptance percentages specified in Table III. When testing submachine guns, the number of cartridges specified at ambient temperatures shall be equally divided between horizental and 80° depressed weapon firings. Failure of the cartridges to comply with the function and casualty requirements shall be cause for rejection of the lot, subject to testing of a second sample consisting of double the quantity of cartridges used in the first sample. For those defects for which the allowable acceptance percentage in Table III is 0.00, the occurrence of a defect of this type in the second sample shall be cause for rejection of the lot. For those defects for which the allowable acceptance percentage is greater than 0.00, failure of the cartridges in the combined first and second sample to comply with the requirements of Table III shall be cause for rejection of the lot."

PAGE 14

5.1 Last line: Delete "9354344" and substitute "9396206".

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AB88)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.