MIL-G-70477 (AR)
AMENDMENT 1
9 September 1985

MILITARY SPECIFICATON

GRENADES, GP: M42 AND M46, INERT
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-G-70477 (AR) dated 15 February 1985, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 11

4.4.2.6, Critical Defect 1: Add "(Grenade Cap, Fuze, Tape Stiffener Assembly) after "illegible""

PAGE 15

4.4.3.1: Delete in its entirety and substitute with the following:

"4.4.3.1 Weight of inert filler of body loading assembly (dwg: 9381453 or 9381456) Major defect. The weight of the inert material of the body loading assembly shall be determined on one assembly from each body loading machine at the start of production each day, and after every one hour of production or portion thereof. If the weight of any body loading assembly fails to comply with the drawing requirement, the body loading assemblies produced since the last satisfactory check shall be rejected. In addition, the necessary adjustments shall be made to the machine which will be verified by determining the weight of inert filler of two consecutively produced body loading assemblies. Testing shall be in accordance with paragraph 4.5.2."

4.5.2: Delete in its entirety and substitute with the following:

FSC 1330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:31Z
Check the source to verify that this is the current version before use.

"4.5.2 Weight of inert filler of body loading assembly The following procedure shall be used to determine the weight of the inert filler of the body loading assembly.

a. Prior to assembly, weigh body assembly with lead cup in air (grams).
b. Load with inert filler using normal production methods.
c. Weigh the assembly in air (grams).
d. Calculate the weight of inert filler in air (c) - (a).

The body assemblies with lead cup inserted shall be randomly selected prior to loading and identified as test samples. Each sample shall be marked clearly with its weight and the applicable inert material consolidation machine number. The samples must be retrieved after powder consolidation but prior to cone insertion."

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1330-A225)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:31Z
Check the source to verify that this is the current version before use.