MILITARY SPECIFICATION SHEET

SCALE, GRAPHICAL FIRING, HE M483A1, HIGH ANGLE, (155-AK-2), (P/N 11785434-32)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring this item described herein shall consist of this document and the latest issue of Specification MIL-S-64045

ACCURACY DATA

Charge	Range (meters)	Elevation (mils)	10m SI (mils)	Drift (mils)	Time of Flight (seconds)
1	2300	1230±1	1.3±0.1	81±1	37.0±0.5
	3300	996±1	9.1±0.1	34±1	32.8±0.5
3	3300	1270±1	0.8±0.1	94±1	47.7±0.5
	5400	950±1	16.0±0.1	30±1	40.4±0.5
5	5300	1277±1	0.8±0.1	93±1	61.9±0.5
	7000	1154±1	2.4±0.1	54±1	58.9±0.5
7	8400	1174±1	0.7±0.1	110±1	79.9±0.5
	13500	964±1	12.0±0.1	36±1	67.8±0.5

Custodian:
ARMY-AR

Preparing Activity
ARMY-AR

Project No. 1220-A293/32

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:13Z
Check the source to verify that this is the current version before use.