NOT MEASUREMENT SENSITIVE

MIL-L-11484/127B
14 January 1994
SUPERSEDING
MIL-L-11484/127A
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, DISTINGUISHED SERVICE MEDAL, UNIFORMED SERVICES, UNIVERSITY OF THE HEALTH SCIENCES

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Edge): 0.070 inch ± 0.010 inch (0.178 cm ± 0.025 cm)

FINISH: Gold Plated, Rose Gold Plated, Matte Finish, Polished Highlights

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-17T16:51Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

3. The design of the lapel button is identical to the design on the obverse of the miniature size medal except the lug shall be removed during the trimming operation.

4. The lapel button shall be completely coated with lacquer.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0745)

User activities:
Other - USUHS

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:51Z
Check the source to verify that this is the current version before use.