NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This standard has been approved by the Bureau of Naval Weapons Department of the Navy and is mandatory for use by the activity. All other military activities are required to employ this standard when suitable.

FED. SUP CLASS 5340

NOMINAL THREAD SIZE OF FINAL ASSEMBLY	PITCH DIAMETER OF TAPPED HOLE (REFERENCE)		MAJOR DIA. OF TAPPED HOLE, MINIMUM
	MIN.	MAX.	
.190 - 32 UNF	.2103	.2123	.2306
.250 - 28 UNF	.2732	.2754	.2964
.3125 - 24 UNF	.3395	.3421	.3666
.375 - 24 UNF	.4020	.4047	.4291
.4375 - 20 UNF	.4700	.4731	.5025
.500 - 20 UNF	.5325	.5357	.5650
.5625 - 18 UNF	.5986	.6020	.6347
.625 - 18 UNF	.6611	.6646	.6972
.750 - 16 UNF	.7906	.7945	.8312
.875 - 14 UNF	.9214	.9257	.9678
1.000 - 12 UNF	1.0542	1.0589	1.1083
.164 - 32 UNC	.1843	.1862	.2046
.190 - 24 UNC	.2170	.2192	.2441
.250 - 20 UNC	.2825	.2851	.3150
.3125 - 18 UNC	.3486	.3515	.3847
.375 - 16 UNC	.4156	.4189	.4562
.4375 - 14 UNC	.4839	.4875	.5303
.500 - 13 UNC	.5499	.5537	.5999
.5625 - 12 UNC	.6167	.6208	.6708
.625 - 11 UNC	.6841	.6885	.7431
.750 - 10 UNC	.8149	.8196	.8799
.875 - 9 UNC	.9471	.9522	1.0193
1.000 - 8 UNC	1.0812	1.0868	1.1624

NOTES:

1. WHEN THIS DESIGN STANDARD IS REFERENCED, THE MINIMUM MAJOR DIAMETERS LISTED HEREIN SUPERSEDE THOSE SHOWN IN DESIGN STANDARDS MS33537 AND MS33646, FOR COMPARABLE NOMINAL THREAD SIZES (OF THE FINAL ASSEMBLY) TABULATED ABOVE. THE DIMENSIONS SHOWN FOR THE MINIMUM MAJOR DIAMETERS ARE ALL IN ACCORDANCE WITH UNIFIED THREAD FORMULATIONS FOR THE REFERENCED PITCH DIAMETERS.

2. THE MIMUMUM MAJOR DIAMETERS LISTED IN THIS STANDARD ARE THE SUBJECT OF AN INTERNATIONAL STANDARDIZATION AGREEMENT, ABC AIR STANDARD 17/28. WHEN REVISION, OR CANCELLATION OF THIS STANDARD IS PROPOSED THE DEPARTMENTAL CUSTODIAN WILL INFORM THE COGNIZANT DEPARTMENTAL STANDARDIZATION OFFICE SO THAT APPROPRIATE ACTION MAY BE TAKEN RESPECTING THE INTERNATIONAL AGREEMENT CONCERNED.

THIS IS A DESIGN STANDARD. NOT TO BE USED AS A PART NUMBER.

APPROVED 28 March 1962 REVISED

P.A. WEP Other Cust	INTER-NATIONAL INTEREST	TITLE: INSERT, HELICAL COIL INSTALLATION THREAD; DESIGN STANDARD FOR	MILITARY STANDARD MS17820 (WEP)
Procurement Specification NONE		SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:09Z
Check the source to verify that this is the current version before use.