INCH-POUND


MS27387D
1 May 2013
SUPERSEDING
MS27387C
24 September 2003

DETAIL SPECIFICATION SHEET

ELBOW SUBASSEMBLY, FLARELESS, 45°, SWIVEL NUT

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-27272.



NOTES:

1. Dimension A, see table II, is measured between the hose end of the threaded section of the union and the free end of the insert at its centerline.
2. Dimension B, see table II, is measured between the centerline of the elbow and the free end of the insert at its centerline.
3. If required lockwire holes to be drilled on this side of subassembly in accordance with SAE-AS1043.
4. Any bent tube design of adapter components to the left of plane A-A is acceptable provided the dimensions A and B and the requirements of this specification sheet and the procurement specification are met.
5. The inside diameter (ID) of the elbow shall not be less than the ID of the nipple. Ovality shall not exceed 7.5 percent of the nominal tubing outside diameter. The minimum wall thickness at the elbow bend shall not be less than .034 inch for the -10 through -20 sizes, and .044 inch for the -24 size.

FIGURE 1. Elbow subassembly illustration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Elbow subassembly illustration, see figure 1.

Intended use. This part is a component of MS27382.

Materials. Material and material codes see table I. See applicable specification sheet and MIL-DTL-27272 for material of other components identified in table II for their material requirements.

TABLE I. Materials and PIN codes.

Material code	Material
Blank	Combination of aluminum alloy and corrosion-resistant steel (CRES)
C	CRES

Finish. Corrosion-resistant steel, do not passivate.
Aluminum alloy. Anodize in accordance with MIL-A-8625, type II, dye yellow.

TABLE II. Elbow subassembly composition.

Size and material code	Wire size and material code	Union, nipple size and material code	Elbow, nipple end size and material code	A ±.035	B ±.035
	MS27072 1/	MS27071 1/ 2/	MS27395 1/ 2/		
-10C	-10C	-10C	-10C	1.674	.725
-10		-10D	-10D		
-12C	-12C	-12C	-12C	2.114	.800
-12		-12D	-12D		
-16C	-16C	-16C	-16C	2.188	.854
-16		-16D	-16D		
-20C	-20C	-20C	-20C	2.445	.962
-20		-20D	-20D		
-24C	-24C	-24C	-24C	2.849	1.155
-24		-24D	-24D		

1/ MS27071, MS27072, and MS27395 shall be dry film lubricated in accordance with table III, dry film is applied in accordance with MS27071, MS27072, or MS27395 as applicable.
2/ Material code “D” aluminum alloy.

If required, lockwire holes to be drilled in accordance with SAE-AS1043 and suffix L added to PIN.

Threads on -10C through -24C shall be lubricated with dry-film lubricate in accordance with table III. MS27071, MS27072, and MS27395 parts shall be coated with the same type of dry film lubricant as indicated in the PIN, no mixing of dry film lubricants shall be used on an assembly unless it is of the types specified by the “blank” designator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:22Z
Check the source to verify that this is the current version before use.

NOTE: Avoid using graphite dry film lubes with aluminum unions and nipples because in a wet environment, graphite becomes corrosive to the aluminum.


TABLE III. Dry film designator.

Dry film designator	SAE class or type designator	Dry film characteristics
Blank	Any SAE class or type below	N/A
SAE-AS1701	SAE-AS1701 class	SAE-AS1701 temperature ranges °F (°C)
4	4	-65° to +1400°F (-54° to 760°C)
5	5	-65° to +850°F (-54° to 454°C)
6	6	-375° to +850°F (-226° to 454°C)
SAE-AS5272	SAE-AS5272 type	SAE-AS5272 temperature ranges. °F (°C)
7	Type I	-90° to 400°F (-68 to 204°C) endurance life of 250 min minimum
8	Type II	-90° to 400°F (-68° to 204°C) endurance life of 450 min minimum
9	Type III	Color 1 - Natural product color -90° to 400°F (-68 to 204°C) low Volatile organic compound with an endurance life of 450 min minimum
10	Type III	Color 2 - Black color -90° to 400°F (-68 to 204°C) low Volatile organic compound with an endurance life of 450 min minimum
Dry film designator	MIL classification	Dry film characteristics
MIL-PRF-46010 1/	---	MIL-PRF-46010 temperature ranges. °F (°C)
11	1	Color 1 natural product color, -90° to 400°F (-68 to 204°C) solvent resisting
12	2	Color 2 - Black color -90° to 400°F (-68 to 204°C) solvent resisting

1/ Not for aerospace usage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:22Z
Check the source to verify that this is the current version before use.

PIN: The PIN consists of prefix “MS”, the specification sheet number, dash number for 45° elbow subassembly assembly size, letter for material, blank or L for lockwire holes, and a blank or number for dry film lubricant. Unassigned PIN’s shall not be used.



PIN examples:

MS27387-8	indicates a 45° elbow subassembly size 8, with a combination of CRES and aluminum with dry film class designator “blank” “any temp range”.
MS27387-8CL4	indicates a 45° elbow subassembly size 8, CRES with lockwire holes and with dry film class designator 4.

Identification of product. The PIN and the manufacturer’s trademark shall be permanently marked on the part.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-27272, this document references the following:

MIL-A-8625	MS27395
MIL-PRF-46010	SAE-AS1043
MS27071	SAE-AS1701
MS27072	SAE-AS5272
MS27382	SAE-AS33514

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:22Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2013-032)

Review activities:
Army - AT, MI
Navy - MC, SA, SH
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:22Z
Check the source to verify that this is the current version before use.