MILITARY SPECIFICATION

CONVERTER, 200 AMPERE, CLASS B, NONREGULATED, AIRCRAFT, FAN COOLED

This amendment forms a part of MS28132J(AS), dated 30 September 1988, and is approved for use by the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete

MS PART NO.
MS28132-1

and substitute

MS PART NO.
MS28132-3 SUPERCEDES BOTH MS28132-1 AND MS28132-2

PAGE 3

1.2 Classification. Delete the class B requirements and add:

Class B: Converters which are self-cooled and conform to the ambient altitude-temperature requirements of MS33543, Curve I, except that the maximum ambient temperature shall not exceed 85°C, the maximum altitude shall not exceed 50,000 feet, and no operation shall be required below -55°C.

4.6 Quality conformance inspections. Add to the end of the second sentence: "except that the 500 percent load test shall not be performed."

4.7.2.2.2 Voltage regulation at maximum temperature-altitude conditions. Delete the +20°C, 65,000 feet requirement.

4.7.2.2.3 Voltage regulation at minimum temperature-altitude conditions. Delete the -55°C, 65,000 feet requirement and substitute -55°C, 50,000 feet.

FSC 6130

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:58Z
Check the source to verify that this is the current version before use.

4.7.2.10 Overload and short circuit capacity. Add to the end of the second sentence: "except that load currents in excess of 200 percent of rated load shall only be applied at room ambient, for one application only."

Preparing Activity:
Navy - AS
Project No. 6130-N339

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:58Z
Check the source to verify that this is the current version before use.