W-L-00111/37
April 21, 1975

INTERIM FEDERAL SPECIFICATION SHEET

LAMP, INCANDESCENT, MINIATURE

TRADE NO. PR-9, B-3 1/2 CLEAR BULB, SINGLE CONTACT MINIATURE FLANGED BASE, C-2R FILAMENT

(DETAIL SPECIFICATION)

The complete requirements for Lamp, Incandescent described herein shall consist of this document and W-L-00111D..

This Interim Federal Specification Sheet was developed by General Services Administration, Federal Supply Service, Mechanical and Electrical Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for change to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal specification Sheet as a valid exception to W-L-111C, dated February 11, 1958.

I. REQUIREMENTS:

Trade No.	Design volts	Design current (amperes)	Current Tolerance %	Initial spherical candle-power (SCP)	Initial SCP Tolerance %	Average Life (hours)
PR-9	2.70	.15	± 7	.25*	N.A.	45

A. Dimensions:

Each lamp shall conform to the manufacturer's standard shape, size, finish, filament type and dimensions as on file at the American National Standards Institute (ANSI) reference ANSI Standard C78.390.

B. Test Voltage - 2.70 Volts DC.

C. Acceptance Criteria Code - Code A.

* For information only.

N.A. - Not Applicable

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:23Z
Check the source to verify that this is the current version before use.