W-L-00111/58A

September 15, 1977

SUPERSEDING
W-L-00111/58
April 21, 1975

INTERIM FEDERAL SPECIFICATION SHEET

LAMP, INCANDESCENT, MINIATURE
Trade No. 1034, S-8 Clear Bulb Double
Contact Index Base

The complete requirements for Lamp, Incandescent described herein shall consist of this document and the latest issue of W-L-00111/GEN.

This Interim Federal Specification Sheet was developed by General Services Administration, Federal Supply Service, Mechanical and Electrical Division, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification Sheet as a valid exception to W-L-111C, dated February 11, 1958.

I REQUIREMENTS:

| Trade No. | Design volts | Design current (amperes) | Current Tolerance % | Initial spherical candle-power (SCP) | Initial SCP Tolerance % | Average Life (hours) |
|---|---|---|---|---|---|---|
| 1034 | 12.8<br>14.0 | 1.80<br>.59 | ± 5<br>± 8 | 32<br>3 | ± 10<br>± 12 | 200<br>5000* |

A. Dimensions:

Lamp Dimensions shall be in accordance with the requirements of SAE Std. J573 and shall be as specified for the Trade No. 1157 Lamp.

B. Electrical and Photometric Test Voltages: 12.8 and 14.0 Volts DC.

C. Life Test Voltage: 12.8 Volts AC or DC.

D. Acceptance Criteria Code: Code A.

* For Information only, life test to be conducted on major filament.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:23Z
Check the source to verify that this is the current version before use.