W-L-00111/66A

September 15, 1977

SUPERSEDING
W-L-00111/66
April 12, 1976

INTERIM FEDERAL SPECIFICATION SHEET

LAMP, INCANDESCENT, MINIATURE
Trade No. 89, G-6 Clear Bulb, Single Contact Bayonet Base, C-2P Filament

The complete requirements for Lamp, Incandescent described herein shall consist of this document and the latest issue of W-L-00111/GEN.

This Interim Federal Specification Sheet was developed by General Services Administration, Federal Supply Service, Mechanical and Electrical Division, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification Sheet as a valid exception to W-L-111C, dated February 11, 1958.

I REQUIREMENTS:

Trade No.	Design volts	Design current (amperes)	Current Tolerance %	Initial spherical candle-power (SCP)	Initial SCP Tolerance %	Average Life (hours)
89	13.0	.58	± 8	6.0	± 15	750

A. Dimensions:

Lamp Dimension shall be in accordance with the requirements of SAE STD. J573, with nominal light center length of 3/4 inch.

B. Electrical and Photometric Test Voltage: 13.0 Volts DC.

C. Life Test Voltage: 13.0 Volts AC or DC.

D. Acceptance Criteria Code: Code A.

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:23Z
Check the source to verify that this is the current version before use.