INCH-POUND

MIL-B-20179E
25 June 1992
SUPERSEDING
MIL-B-20179D(ME)
3 March 1986

MILITARY SPECIFICATION

# BAG, BAILEY BRIDGE PARTS AND TOOLS: CLOTH, COTTON DUCK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers a cotton duck bag with handles for transporting tools and small parts.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| A-A-52094 | - Thread. |
| T-R-605 | - Rope, Manila and Sisal. |
| FF-R-556 | - Rivet, Solid, Small; Rivet, Split, Small Rivet Tubular, Small; Burr and Cap, Rivet; General Purpose. |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir, Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5420

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:23Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| CCC-C-419 | - Cloth, Duck, Cotton, Unbleached, Plied Yarns (Army and Numbered). |
| CCC-D-950 | - Dyeing and Aftertreating Process for Cotton Cloth. |
| PPP-B-601 | - Boxes, Wood, Cleated-Plywood. |
| PPP-B-640 | - Box, Fiberboard, Corrugated, Triple Wall. |

MILITARY

| | |
|---|---|
| MIL-C-496 | - Clip, End Strap. |
| MIL-W-530 | - Webbing, Textile, Cotton, General Purpose Natural or in Color. |
| MIL-B-543 | - Buckles, Tongueless and Web Strap. |
| MIL-T-3530 | - Treatments, Mildew Resistant and Water Repellent for Thread and Twine. |
| MIL-L-10547 | - Liner, Case, and Sheet, Overwrap, Water Vaporproof or Waterproof Flexible. |

STANDARDS

FEDERAL

| | |
|---|---|
| FED-STD-751 | - Stitches, Seams, and Stitchings. |

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - Marking for Shipment and Storage. |
| MIL-STD-130 | - Identification Marking of US Military Property. |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government drawings. The following other Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

DRAWING

ME

| | |
|---|---|
| 13220E9185 | - Bag, Bailey Bridge, Parts and Tools. |

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir, Research, Development, and Engineering Center, ATTN: STRBE-JBS, Fort Belvoir, VA 22060-5606.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:23Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issue of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 153 - Zinc Coating (HotDip) on Iron and Steel Hardware.
D 3951 - Standard Practice for Commercial Packaging.
D 4675 - Selection and Use of Flat Strapping Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION INC. AGENT (NMFTA)

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., ATTN: Tariff Order Section, 220 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE AGENT (UCC)

Uniform Freight Classification Rules.

(Application for copies should be addressed to Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The bag shall be in accordance with drawing 13220E9185 and as specified herein.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:23Z
Check the source to verify that this is the current version before use.

3.1.1 Drawing. The drawing forming a part of this specification is an end product drawing. No deviation from the prescribed dimensions and tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawing to insure correct fit, assembly, and operation of the bag. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. When otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3 ) in accordance with 4.3.

3.3 Material. Material shall be as specified herein and on the applicable drawing. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Cotton duck. Cotton duck shall conform to CCC-C-419, type I, hard texture No. 1 or medium texture No. 1, and shall be dyed and treated in accordance with CCC-D-950, type II, class B, method 56, except that not less than 0.4 percent copper as metal from the inhibitor shall be used. The cotton duck shall be dyed olive drab 7.

3.3.2 Webbing. Cotton webbing shall conform to MIL-W-530, type IIa, class 4, except that not less than the maximum of 2.2 percent copper as metal from copper 8-quinolinate shall be deposited within the webbing. The webbing shall be dyed olive drab 7.

3.3.3 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the bag may be newly fabricated from recovered materials to the maximum extent practicable, provided the bag produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the bag.

3.4 Rope. Rope shall conform to T-R-605, type M, class 2. 2-1/4-inch circumference, and shall be mildew resistant.

3.5 Belt rivets and burrs. Belt rivets and burrs shall conform to FF-R-556, type I, class 2, grade A, size number 15, overall length as required.

3.6 Buckles. The buckles shall conform to MIL-B-543, type III, class 3, 1-1/2 inch size, and shall be zinc-coated in accordance with ASTM A 153.



Source: https://assist.dla.mil -- Downloaded: 202610-19T07:23Z
Check the source to verify that this is the current version before use.

3.7 End clips. End clips for the free end of the webbing shall conform to MIL-C-496, type I, 1-1/2 inch, steel, and shall be zinc-coated in accordance with ASTM A 153.

3.8 Thread. Thread shall conform to A-A-52094, type IV dyed olive drab 7, and shall be made mildew-resistant in conformance to MIL-T-3530, class I.

3.9 Identification marking. The bag shall be identified in accordance with MIL-STD-130 and as shown on the drawing.

3.10 Workmanship.

3.10.1 Sewing. All sewing shall be machine stitching with 4 or 5 stitches backstitched not less than 1 inch at each break. Stitches shall conform to FED-STD-751, type 301, and seams shall be type 301-SSe-3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet the requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specifications shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of know defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured in accordance with referenced specifications, standards, and drawings, as applicable.



Source: https://assist.dla.mil -- Downloaded: 202640-19T07:23Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection. The first article bag shall be examined as specified in 4.5.1. Presence of one or more defects will be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined in accordance with the applicable specification requirement and as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The bag shall be examined as specified herein for the following defects: Presence of one or more defects shall be cause for rejection.

101. Nonconformance to dimensions shown on the drawing (see 3.1.1).
102. Materials not as specified (see 3.3).
103. Color of cotton duck not as specified (see 3.3.1).
104. Webbing not as specified (see 3.3.2).
105. Used, rebuilt, or remanufactured components, pieces or parts incorporated in the bag (see 3.3.3).
106. Rope not as specified (see 3.4).
107. Rivets and burrs not as specified (see 3.5).
108. Buckles not as specified (see 3.6).
109. End clips not as specified (see 3.7).
110. Thread not as specified (see 3.8).
111. Identification marking missing or not as specified (see 3.9).
112. Sewing not as specified (see 3.10.1).

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:23Z
Check the source to verify that this is the current version before use.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects: Presence of one or more defects shall be cause for rejection.

| | |
|---|---|
| 113. | Bags not secured in the quantities and in the manner specified for levels A, B, or C (see 5.1.1, 5.1.2 and 5.1.3). |
| 114. | Boxes not as specified for levels A or B (see 5.1.1 and 5.1.2). |
| 115. | Case liner not provided for level A (see 5.1.1). |
| 116. | Boxes not closed and strapped as specified for levels A or B (see 5.1.1 and 5.1.2). |
| 117. | Marking missing, illegible, incorrect, or incomplete for levels A, B, or C (see 5.2). |

5. PACKAGING

5.1 Packing. Packing shall be level A, level B, or C as specified (see 6.2).

5.1.1 Level A. Fifty bags shall be squarely stacked flatwise with the ends of successive bags alternated. The stack shall be compressed to form a flat package and secured while under compression with two ties of cotton tape or twine. The ties shall be applied girthwise and spaced approximately 5 inches in from each end. The bags shall then be packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional. The box shall be provided with a case liner in accordance with MIL-L-10547, type IV, grade F. The box shall be closed and strapped in accordance with the appendix to the box specification. Strapping shall be in accordance with ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675.

5.1.2 Level B. Fifty bags shall be stacked, compressed, and secured as specified in 5.1.1 for level A. The bags shall then be packed in a close-fitting box conforming to PPP-B-640, class 2, style optional. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.1.3 Level C. Fifty bags shall be stacked, compressed, and secured as specified in 5.1.1 for level A. The bags shall then be packed to assure carrier acceptance and safe delivery to destination at lowest rating in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.2 Marking. In addition to any special marking specified in the contract or purchase order, marking shall be in accordance with MIL-STD-129.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:23Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The bag is intended to be used to transport small parts and tools during construction of the M2 panel bridge (bailey type).

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. For first article: When required, time frame for submission, and number of bags required (see 3.2).
d. Degree of packing required (see 5.1).

6.3 First article. When a first article inspection is required, the items should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.5 Subject term (key word listing).

Bag, bailey
Bridge parts and tools

Custodian:
Army - ME

Review activities:
Navy - MC
DLA - CS

Preparing activity:
Army - ME

Project 5420-0210



Source: https://assist.dla.mil -- Downloaded: 202610-19T07:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER<br>MIL-B-20179E | 2. DOCUMENT DATE (YYMMDD)<br>920625 |
|---|---|---|

3. DOCUMENT TITLE
Bag, Bailey Bridge Parts and Tools: Cloth, Cotton Duck

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

REASON FOR RECOMMENDATION

6. SUBMITTER

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial (if applicable)<br>(2) AUTOVON | 7. DATE SUBMITTED |

8. PREPARING ACTIVITY

| a. NAME<br>Geraldine F. Harlow | b. TELEPHONE (Include Area Code)<br>(1) Commercial (703) 704-3468<br>(2) AUTOVON 654-3468 |
|---|---|
| c. ADDRESS (Include Zip Code)<br>Army Belvoir RDE Center<br>ATTN: STRBE-TSE<br>Fort Belvoir, VA 22060-5606 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 |

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:23Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:23Z
Check the source to verify that this is the current version before use.