MIL-L-20111
18 September 1951

MILITARY SPECIFICATION

LAUNCHER, GRENADE, M8 (FOR CARBINE, CAL. .30)

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments, and supersedes the following specification:

Army 52-3-34
20 November 1944

This specification consists of this cover sheet and Specification 52-3-34, dated 20 November 1944, together with Amendment 1, dated 23 July 1945, attached hereto, without modification.

Copies of this specification may be obtained upon application to the Office, Chief of Ordnance, Washington 25, D.C.

When a request for this specification is received by a supplying activity it will be necessary to attach this cover sheet to the pertinent specification before issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:20Z
Check the source to verify that this is the current version before us

No. 52-3-34
20 NOVEMBER 1944

LAUNCHER, GRENADE, M8 (FOR CARBINE, CAL. .30)

A. APPLICABLE SPECIFICATIONS.

A–1. Ordnance Department Drawing No. C113709C, entitled "List of Drawings and Specifications, Launcher, Grenade, M8," lists the drawings and specifications necessary to complete the manufacture of the launcher.

A–2. All drawings and specifications listed on the above mentioned drawing, of the revision date indicated thereon, form a part of this specification.

B. TYPE.

B–1. This specification covers one type of launcher known as: "Launcher, Grenade, M8."

C. MATERIAL AND WORKMANSHIP.

C–1. *Material.*—Material shall be in accordance with applicable drawings and specifications. Material specified as "commercial quality" shall, unless otherwise specified, be in accordance with the requirements of U. S. Army Specification No. 52–0–1, General Specification Governing the Manufacture and Inspection of Small Arms Weapons, Spare and Replacement Parts, and Accessories.

C–2. *Workmanship.*—Finished launchers shall be free from defects that may affect serviceability or appearance.

D. GENERAL REQUIREMENTS.

D–1. *See detail requirements.*

E. DETAIL REQUIREMENTS.

E–1. *Components.*—Components shall conform to the dimensions within the tolerances, and shall be given the heat treatment and final finish specified on the drawings.

E–2. *Protective finish.*—Protective finishes shall be as prescribed on the drawings and shall conform with the requirements of U. S. Army Specification No. 57–0–2, Finishes, Protective, on Iron and Steel Parts.

E–3. *Marking.*—Unless otherwise specified, each accepted launcher shall be marked in accordance with applicable drawings.

E–4. *Firing.*—Each launcher shall be capable of withstanding the firing test prescribed in paragraph F–5.

E–5. *Launcher pull.*—Each launcher shall withstand the pull test prescribed in paragraph F–6.

E–6. *Strength of weld.*—The weld holding the clamp to the sleeve shall show no signs of weakening when tested as prescribed in paragraph F–7.

F. METHODS OF INSPECTION AND TEST.

F–1. *Inspection.*—Unless otherwise specified, inspection and tests shall be made at the place of manufacture. The inspector shall have free access at all times to all departments of the plant which concern the manufacture of the launchers. The inspector may subject all or part of any lot or lots of components or assemblies to such in-

Source: https://assist.dla.mil -- Do
Check the source to verify that this i

spection and gaging as he deems necessary to determine compliance with the requirements.

F–2. *Lots.*—Unless otherwise specified, the initial lot for inspection and test purposes shall be not more than 500 launchers, and subsequent lots not more than 2,000 launchers.

F–3. *Visual inspection.*—Each launcher shall be inspected visually for completeness of manufacture, assembly, finish, and workmanship.

F–4. *Gaging test.*—All components of the inspection samples of each lot shall be gaged for the requirements of paragraph E–1 by using applicable Ordnance gages which will be furnished by the contracting officer.

F–5. *Firing test.*—

F–5a. *First lot.*—Five sample launchers shall be selected by the inspector from the first lot under a contract, and tested by firing in sequence as follows:

20 rds. M11A2 practice grenades.
20 rds. Fragmentation grenade (without charge, unfuzed).
600 rds. Ball ammunition W/launcher.

F–5b. *Subsequent lots.*—From each succeeding lot one launcher shall be selected by the inspector and fired as follows:

2 rds. M11A2 practice grenades.
2 rds. Fragmentation grenades (without charge, unfuzed).
5 rds. Ball ammunition W/launcher.

F–6. *Pull test.*—Each launcher shall be submitted to a pull test, using a tube or cylinder of .868–.002-inch diameter, which is the diameter of the grenade tube. Each launcher shall be released from the tube by the exertion of a steady pull of not less than 5 pounds and not more than 15 pounds.

F–7. *Strength of weld test.*—At least 10 percent of all launchers shall be submitted to the following test:

With the assembled launcher held in a vertical position, the equivalent of 20 foot-pounds of pressure is applied to the clamp.

F–8. *Retests.*—Failure in any test shall render the lot subject to rejection. Rejected lots may be submitted for retest after conditioning, in which case twice the number of original samples shall be taken. Failure of any launcher in the retest shall render the lot subject to rejection.

G. PACKING AND MARKING.

G–1. Packing and marking shall be for export shipment in accordance with Ordnance Packaging Instruction P. S. 71.

H. NOTES.

H–1. This specification, if applicable, may be used in the procurement of launchers not listed in paragraph B–1.

H–2. The use of this specification, whenever applicable, is mandatory on all procuring agencies of the Army.

NOTICE.—This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the U. S. Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Source: https://assist.dla.mil -- Do
Check the source to verify that this is

NOTE.—Copies of this specification may be obtained from the Office, Chief of Ordnance, Army Service Forces, Washington 25, D. C.

[No. 52–3–34] U. S. GOVERNMENT PRINTING OFFICE: 1944

U. S. ARMY
SPECIFICATION

No. 52-3-34
20 November 1944
Amendment 1
23 July 1945

LAUNCHER, GRENADE, M8
(For Carbine, Cal. .30)

The following changes shall be made in Specification No. 52-3-34 dated 20 November 1944:

Page 2, paragraph F-7. Delete the paragraph and substitute the following:

"F-7. Strength of weld test. At least 10 percent of all launchers shall be submitted to the following test:

With the assembled launcher held in the vertical position, the equivalent of an impact load of 20 foot-pounds shall be applied to the clamp".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:20Z
Check the source to verify that this is the current version before use.