MIL-T-20193D(ME)
5 October 1978
SUPERSEDING
MIL-T-20193C
17 December 1970

MILITARY SPECIFICATION

TABLE, STEREOPLOTTER, PROJECTION:

MULTIPLEX, WITH CHEST

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is aviable for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a metal table and plywood chest for use with multiplex mapping equipment.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

FSC 6675

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:24Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-C-12044	- Chests, Plywood.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

DRAWINGS

ME

TA13204E2377	- Table, Stereoplotter, Projection: Multiplex.
TA13217E7464	- Chest, Table, Multiplex.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:24Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The table shall be in accordance with Top Assembly TA13204E2377 and as specified herein. The chest shall be in accordance with Top Assembly TA13217E7464, MIL-C-12044, and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the table and chest. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer of his designated representative.

3.2 First article (first produced table and chest). The contractor shall furnish one or more tables and chests as specified (see 6.2) for examination and testing within the time frame specified (see 6.2) to prove that his production methods will produce tables and chests that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of the specification (see 6.4).

3.4 Identification marking. The table and chest shall be identified in accordance with MIL-STD-130. The marking shall be applied to the table and chest on plates conforming to MIL-P-514, Type I, Style 2, Composition C, of Type I, Grade A, Class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.5 Workmanship. All parts, components, and assemblies of the table including castings, forgings, molded parts, machined surfaces, and welded parts shall be free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material. External surfaces and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:24Z
Check the source to verify that this is the current version before use.

edges of all finished members shall be free from sandholes, blowholes, cracks, shrinks, kinks, bends, and scratches.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.1.2 Disassembly inspection. Failure of any examination or test by the first produced table and chest shall be cause for disassembly, in the presence of a Government representative, of the first produced table and chest to the extent necessary to determine the cause of the failure. Each disassembled part shall be examined in detail for compliance with this specification and referenced drawings in regard to materials, dimensions, tolerances, and workmanship. Parts not complying with such requirements shall be rejected and shall be cause for rejection of the first produced table and chest. Reassembly with replacement parts and retesting shall be the responsibility of the contractor.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First produced table and chest inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:24Z
Check the source to verify that this is the current version before use.

4.3 First produced table and chest inspection.

4.3.1 Examination. The first produced table and chest shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection or for performing the disassembly inspection specified in 4.1.2.

4.3.2 Tests. The first produced table shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection or for performing the disassembly inspection specified in 4.1.2.

4.4 Quality conformance inspection.

4.4.1 Examination. Each table and chest shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.2 Tests. Each table shall be tested as specified in 4.5.2. Failure of this test shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The table and chest shall be examined as specified herein for the following defects:

101. Materials not as specified on the drawings.
102. Dimensions and tolerances not as specified on the drawings.
103. Components missing or not as specified.
104. Identification marking missing or illegible.
105. Workmanship not as specified.

4.5.2 Test. The table shall be assembled and leveled.

4.5.2.1 Table-top flatness. The table-top flatness test shall be conducted on the assembled table. A steel machinist's straightedge not less than 6 feet in length shall be used to check the flatness of the top. The straightedge shall be used to check positions along a line 1 inch in from each edge, across each centerline, and across each diagonal. Contact or lack of contact of the straightedge with the top shall be checked with feeler gages along the entire length of the plate surface. A deviation more than 0.002 inch between the straightedge and the surface of the table top shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:24Z
Check the source to verify that this is the current version before use.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

106.	Materials or containers not as specified for Level A or Level B. Each incorrect material or container shall constitute one defect.
107.	Components not placed and secured in the chest.
108.	Strapping not as specified.
109.	Marking illegible, incorrect, incomplete, or missing.

5. PACKAGING

5.1 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.1.1 Level A. The table components shall be placed and secured in the chest and the chest shall be packed in a close-fitting box conforming to PPP-B-621, Class 2, Style 2, or in a close-fitting box conforming to PPP-B-601, Overseas Type, style optional. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.1.2 Level B. The table components shall be placed and secured in the chest and the chest shall be packed as specified in 5.1.1 for Level A, except the boxes shall be Domestic Type and Class. Strapping shall be Finish A.

5.1.3 Commercial. The table components shall be packed in accordance with MIL-STD-1188.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:24Z
Check the source to verify that this is the current version before use.

5.2 Marking.

5.2.1 Military packaging. Marking shall be in accordance with MIL-STD-129.

5.2.2 Commercial packaging. Marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The table is intended for the use as a support for the multiplex frame, multiplex tracing table, and the drafting material upon which a map may be compiled.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of first produced table with chest, and number of units required (see 3.2).
(c) Degree of packing required (see 5.1).
(d) When Finish A strapping is required (see 5.1.1).

6.3 First produced tables and chests. Any changes or deviations of first produced tables and chests from the approved first produced table(s) and chest(s) during production will be subject to the approval of the contracting officer. Approval of the first produced table(s) and chest(s) will not relieve the contractor of his obligation to furnish tables and chests conforming to this specification.

6.4 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.3).

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA - GS

Project 6675-A218

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:24Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-T-20193D(ME) Table, Stereoplotter, Projection: Multiplex, with Chest

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:24Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:24Z
Check the source to verify that this is the current version before use.