NOT MEASUREMENT SENSITIVE

MIL-C-29584(AS)
30 September 1990

# MILITARY SPECIFICATION
# COMPOUND, CLEANING, WATER MISCIBLE FOR AIRCRAFT AUTOMATIC WEAPONS AND AIRCRAFT AUTOMATIC GUN SYSTEMS

This specification is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification establishes the requirements for a biodegradable, water miscible, low foaming cleaning compound.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Air Engineering Center, Systems Engineering and Standardization Department (SESD), Code 53, Lakehurst, New Jersey 08733-5100, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6850

DISTRIBUTION STATEMENT C. Distribution authorized to U.S. Government agencies and their contractors. Contains technical data that is potentially significant to military application as of 27 July 1990. Other requests for this document shall be referred to: Commanding Officer, Naval Air Engineering Center (Code 53), Lakehurst, New Jersey 08733-5100.

DESTRUCTION NOTICE. For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| PPP-P-704 | Pails, Metal: (Shipping, Steel, 1 through 12 Gallons) |
| PPP-D-705 | Drum, Shipping and Storage: Steel, 16 and 30 Gallon Capacity |
| PPP-D-729 | Drums, Shipping and Storage: Steel, 55-Gallon (208 Liters) |

MILITARY

| | |
|---|---|
| MIL-H-6875 | Heat Treatment of Steel, Process for |
| DOD-P-16232 | Phosphate Coating, Heavy, Manganese or Zinc Base (for Ferrous Metals) |
| MIL-C-83286 | Coating Urethane, Aliphatic Isocyanate, for Aerospace Applications |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | Marking for Shipment and Storage |
| MIL-STD-147 | Palletized Unit Loads |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

Code of Federal Regulations (CFR)
Title 29, Labor

(Copies of other Government documents, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society for Testing and Materials (ASTM)

| | |
|---|---|
| ASTM A109 | Steel, Strip, Carbon, Cold-Rolled |
| ASTM D56 | Flash Point by Tag Closed Tester |
| ASTM D93 | Flash Point by Pensky-Martens Closed Tester |
| ASTM D2667 | Biodegradability of Alkylbenzene Sulfonates |
| ASTM E70 | pH of Aqueous Solutions with the Glass Electrode |
| ASTM F483 | Total Immersion Corrosion Test for Aircraft Maintenance Chemicals |
| ASTM F485 | Effects of Cleaners on Unpainted Aircraft Surfaces |
| ASTM F502 | Effects of Cleaning and Chemical Maintenance Materials on Painted Aircraft Surfaces |
| ASTM F519 | Mechanical Hydrogen Embrittlement Testing of Plating Processes and Aircraft Maintenance Chemicals, Method for |
| ASTM F1104 | Preparing Aircraft Cleaning Compounds, Liquid Type, Water Base, for Storage Stability Testing |

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)



Source: https://assist.dla.mil -- Downloaded: 202610-21T00:16Z
Check the source to verify that this is the current version before use.

Society of Automotive Engineers

SAE J404 Chemical Compositions of SAE Alloy Steels

Aerospace Material Specifications

AMS 2470 Anodic Treatment of Aluminum Alloys, Chromic Acid Process

AMS 2475 Protective Treatments, Magnesium Alloys

AMS 4037 Aluminum Alloy Sheet and Plate, 4.4Cu-1.5Mg-0.60Mn (2024; -T3 Flat Sheet, - T351 Plate) Solution Heat Treated

AMS 4041 Aluminum Alloy Sheet and Plate, Alclad, 4.4Cu-1.5Mg-0.60Mn (Alclad 2024 and 1-1/2% Alclad 2024, - T3 Flat Sheet; 1-1/2% Alclad 2024-T351 Plate)

AMS 4049 Aluminum Alloy Sheet and Plate, Alclad, 5.6Zn-2.5Mg-1.6 Cu-0.23Cr (Alclad 7075; -T6 Sheet, -T651 Plate) Solution and Precipitation Heat Treated

AMS 4376 Magnesium Alloy Plate, 3.0Al - 1.0Zn (AZ31B-H26) Cold Rolled and Partially Annealed

AMS 4911 Titanium Alloy Sheet, Strip, and Plate (6A1-4V) Annealed

Aerospace Recommended Practices

ARP 1511 Corrosion of Low-Embrittling Cadmium Plate by Aircraft Maintenance Chemicals

ARP 1512 Corrosion of Aluminum Alloys by Aircraft Maintenance Chemicals, Sandwich Test

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents may be available in or through libraries or other informational services.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article acceptance inspection (see 6.3) in accordance with 4.5.

3.1.1 Practical cleaning. The cleaning compound shall remove 100 percent of carbonaceous soils, powder residues, oils, greases, and other oxidized organic residue associated with automatic gun firing operations.

3.2 Physical and chemical properties. The cleaning compound shall be low foaming and completely miscible in water.

3.2.1 Toxicity. The cleaning compound shall have no adverse effect on the health of personnel when used for its intended purpose. Questions pertinent to this effect shall be referred by the contracting activity to the appropriate departmental medical service who will act as an advisor to the contracting agency. The manufacturer shall certify that the cleaning compound contains no substance known to be toxic or carcinogenic to the user under normal conditions of use as determined in 29CFR 1900 (see 6.3 and 6.7).

3.3 Biodegradability. Ingredients used in the cleaning compound shall be not less than 90 percent biodegradable (see 6.3).

3.4 Flash point. The flash point shall be not lower than 140 degrees Fahrenheit (°F) (60 degrees Celsius (°C)).

3.5 pH value. The pH value shall be between 9 and 10.

3.6 Effect on metals. The cleaning compound shall contain no components which are corrosive to metals or metal alloys used in the gun and feeder mechanisms of aircraft automatic weapons systems.

3.6.1 Sandwich corrosion. Test coupon ratings shall be not worse than 1.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

3.6.2 Total immersion corrosion. Test panels shall not pit, corrode, or exhibit a weight change greater than the following:

| | PANEL | WEIGHT CHANGE (mg/cm²)/24hr |
|---|---|---|
| AMS 4037 | Aluminum Alloy, anodized in accordance with AMS 247 | 0.04 |
| AMS 4041 | Aluminum Alloy (Optional) | .04 |
| AMS 4049 | Aluminum Alloy | .04 |
| AMS 4376 | Magnesium Alloy, dichromate treated in accordance with AMS 2475 | .20 |
| AMS 4911 | Titanium Alloy | .04 |
| ASTM A109 | Carbon Steel, Temper No. 1 | .04 |
| SAE J404-4140 | Alloy Steel, tempered in accordance with MIL-H-6875, (C33-C35) Rockwell hardness with Manganese Phosphate Coating Type M Class 1 in accordance with DOD-P-16232 | .057 |

3.6.3 Low embrittling cadmium plate. Test panels coated with low-embrittling cadmium plate shall not show a weight change greater than 0.2 milligram per square centimeter (mg/cm²)/24 hours (hr).

3.6.4 Hydrogen embrittlement. Type 1d and Type 2a steel test panels shall show no hydrogen embrittlement in accordance with ASTM F519.

3.6.5 Effect on painted surfaces. For top coat paint conforming to MIL-C-83286, the cleaning compound shall cause no streaking, blistering, discoloration, or permanent decrease in film hardness greater than one pencil hardness level.

3.6.6 Effect on unpainted metal surfaces. The cleaning compound shall cause no streaking, stains, or deposits that cannot be easily removed with water.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

3.7 Stability.

3.7.1 Long term storage stability. The cleaning compound shall not separate, crystallize, deteriorate, precipitate, or cause distortion, leakage, or corrosion of the shipping container during storage periods of not greater than 12 months.

3.7.2 High temperature stability. The cleaning compound shall not layer nor separate after being exposed to a temperature of 140 ± 3°F (60 ± 2°C) for a period of 6 hours.

3.7.3 Low temperature stability. After freezing, the cleaning compound shall return to its original homogeneous condition at room temperature.

3.8 Workmanship. The cleaning compound shall be a homogeneous liquid free of foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform or witness any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material (see 6.3).



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.5).

b. Quality conformance inspection (see 4.6).

4.3 Toxicological product formulation. The contractor shall have the toxicological product formulations and associated information available for review by the contracting activity to evaluate the safety of the material for the proposed use.

4.4 Test sample dilution ratio. Unless otherwise specified, all tests shall be conducted with the as delivered concentrated cleaning compound and the strongest dilution ratio recommended by the manufacturer for actual cleaning.

4.5 First article inspection. Unless otherwise specified in the contract or purchase order (see 6.2), a first article sample shall be subjected to the first article inspection, which shall include all examinations and tests specified in 4.7.1 through 4.9. The first article inspection shall be conducted by the contractor at a test facility approved by the acquiring activity (see 6.2). The acquiring activity shall be advised 30 days in advance of when first article inspections are to be conducted so that a Government representative may be designated to witness the examinations, demonstrations, and tests. (See 6.2 and 6.3).

4.5.1 First article sample. Unless otherwise specified in the contract or purchase order (see 6.2), the first article sample shall consist of five gallons. The first article sample shall be representative of the methods, materials, processes, parts, design, and inspection methods the contractor proposes to use in production of the cleaning compound under the contract. The first article sample shall not be considered as deliverable under the contract.

4.5.2 Acceptance criteria. Failure of the first article sample to pass any portion of the first article inspection shall be cause for rejection of the first article sample (see 6.3).

4.5.3 First article approval. Approval of the first article sample shall be by the acquiring activity upon satisfactory completion of the first article inspection. No production cleaning compound shall be delivered prior to the approval of the first article sample. Any production of cleaning compound prior to the approval of the first article sample shall be at the contractor's risk.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

4.6 Quality conformance inspection. Unless otherwise specified in the contract or purchase order (see 6.2), a quality conformance inspection shall be performed on all cleaning compound offered for acceptance. The quality conformance inspection shall consist of all the examinations and tests required under this specification. No changes to the cleaning compound shall be performed during or after any examination, demonstration, or test. Failure of any cleaning compound to pass the quality conformance inspection shall be cause for rejection of that cleaning compound. The quality conformance inspection shall be conducted at a test facility approved by the acquiring activity (see 6.2). (See 6.3.)

4.6.1 Lot formation. A lot shall consist of all the cleaning compound produced by one manufacturer, at one plant, from the same materials and under the same conditions provided the operation is continuous and does not exceed a 24 hour period. In the event the process is a batch operation, each batch shall constitute a lot (see 6.6).

4.6.2 Quality conformance test samples. Unless otherwise specified, not less than a 5 gallon (see 6.4) (18.9 liters) container of the cleaning compound shall be selected at random from each lot and subjected to the tests specified in 4.6.

4.6.3 Inspection of materials and components. The contractor is responsible for ensuring that all materials and supplies used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or if none, in accordance with this specification.

4.7 Methods of inspection.

4.7.1 Practical cleaning tests. The practical cleaning tests shall consist of a visual examination performed by a field activity designated by the acquiring activity. A representative of the acquiring activity shall be present during the tests to verify the test results. The test shall consist of a field evaluation of the cleaning compound under service conditions using standard equipment and standard cleaning procedures on two or more aircraft automatic weapons that have been operationally soiled by firing 250 rounds or more. The dilution ratios of water to cleaning compound shall be those recommended by the cleaning compound manufacturer. Standard cleaning procedures and equipment shall be those authorized in the applicable weapons technical manuals.

4.7.2 Physical and chemical properties. The requirements of 3.2 shall be verified by demonstration.



Source: https://assist.dla.mil -- Downloaded: 202610-21T00:16Z
Check the source to verify that this is the current version before use.

4.7.2.1 Biodegradability. Biodegradability of the surfactants shall be determined in accordance with ASTM D2667.

4.7.3 Flash point. The flash point test sample shall be the concentrated as-received form. Determination of the flash point shall be in accordance with either ASTM D56 or ASTM D93 as appropriate to the viscosity of the sample material.

4.7.4 pH value. The pH of the cleaning compound shall be determined electrometrically using glass electrodes in accordance with ASTM E70.

4.7.5 Sandwich corrosion. The sandwich corrosion tests shall be conducted in accordance with ARP 1512.

4.7.6 Total immersion corrosion. The total immersion tests shall be conducted in accordance with ASTM F483. Test duration shall be 168 hours.

4.7.7 Low embrittling cadmium plate. The low embrittling cadmium plate test shall be conducted in accordance with ARP 1511.

4.7.8 Hydrogen embrittlement. The hydrogen embrittlement shall be determined in accordance with ASTM F519.

4.7.9 Effect on painted surfaces. The effect on painted surfaces conforming to MIL-C-83286 shall be determined in accordance with ASTM F502.

4.7.10 Effect on unpainted metal surfaces. The effect on unpainted metal surfaces shall be determined in accordance with ASTM F485.

4.7.11 Long term storage stability. The stability of the concentrated cleaning compound during long term storage shall be determined in accordance with ASTM F1104.

4.7.12 High temperature stability. Fifty mLs of the cleaning compound shall be placed in a 50mL glass, stoppered, graduated cylinder. The cylinder shall be placed in a water bath maintained at 60 ± 2°C (140 ± 3°F) for 6 hours. The depth of water in the bath shall cover 30 mLs of the cleaning compound. At the end of the test period, the sample shall be examined for evidence of separation or layering.

4.7.13 Low temperature stability. A 50 mL sample of the cleaning compound shall be placed in a test tube and cooled to 0 ± 9° F (-18 ± 5°C). This temperature shall be



Source: https://assist.dla.mil -- Downloaded: 202640-21T00:16Z
Check the source to verify that this is the current version before use.

maintained for 1 hour. The compound shall be allowed to reach room temperature. The container shall be inverted five times and examined for homogeneity.

4.8 Workmanship. The requirements of 3.8 shall be verified by examination.

4.9 Packaging inspection. The requirements of Section 5 shall be verified by examination.

5. PACKAGING

5.1 Packing. Unless otherwise specified in the contract or purchase order, packing shall be level A.

5.1.1 Level A. The cleaning compound shall be furnished in 5-gallon (18.9 liter), 15-gallon (56.8 liter), or 55-gallon (208.2 liter) quantities, as specified in the contract or purchase order (see 6.2). Unless otherwise specified in the contract or purchase order, the 5, 15, and 55-gallon quantities shall be packed in containers which conform to Type I, Class 3 of PPP-P-704, Type II of PPP-D-705, and Type II of PPP-D-729, respectively. The flanges and plugs shall each have three or more full threads. The plugs shall have a thread length such that three or more full threads are engaged when the plug is screwed tight with gaskets in place. The threads shall be American Standard modified pipe threads. The 5-gallon container shall have a flexible spout. The internal surfaces of all containers shall be lined with a material that shall not adversely affect nor be adversely affected by the cleaning compound.

5.2 Palletization. Unless otherwise specified (see 6.2), cleaning compound containers shall be palletized in accordance with MIL-STD-147 as listed below. For shipments destined for afloat units, the overall height shall not exceed 41 inches.

| CONTAINER SIZE | LOAD TYPE | BONDING METHOD | STORAGE AID |
|---|---|---|---|
| 5 Gal | III | C and D | 5 |
| 15 Gal | III | C and D | 5 |
| 55 Gal | XIIa | C and D | 5 |



Source: https://assist.dla.mil -- Downloaded: 202640-21T00:16Z
Check the source to verify that this is the currentversion before use.

5.3 Marking. All containers of cleaning compound shall be clearly labeled with the manufacturer's name, the product designation the recommended dilution ratio, the pH value, and date of manufacture. Shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129. In addition, all containers of cleaning compound shall be clearly labeled as follows:

CLEANING COMPOUND, AIRCRAFT AUTOMATIC WEAPONS AND AIRCRAFT AUTOMATIC GUN SYSTEMS - MIL-C-XXXX

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cleaning compound is intended for use in cleaning aircraft automatic weapons, gun systems, gun pods and loading equipment, and associated system components. This cleaning compound is not intended for use on aircraft.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.
b. When a first article is required (see 3.1.1, 4.5 and 6.5).
c. Quantity of cleaning compound required (see 5.1.1).
d. Responsibility for inspection, if different than 4.1.
e. Option for the Government to perform or witness any inspections (see 4.1).
f. Inspection of first article if different than 4.5.
g. Size of first article sample, if different than 4.5.1.
h. Facility approved to perform first article and quality conformance inspections (see 4.5 and 4.6).
i. Type and capacity of containers required (see 5.1.1).
j. Level of packing required, if different than 5.1.
k. When palletization is not required (see 5.2).
l. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) and military specification should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the documents are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

| Reference Paragraph | Document Number | Document Title | Suggested Tailoring |
|---|---|---|---|
| 3.2.1 & 3.2.2 | DI-MISC-80678 | Certification/Data Report | - |
| 4.5 | UDI-T-23790 | First Article Test Report | - |
| 4.5, 4.6, 4.6.2, 4.6.3 | DI-T-2072<br>MIL-T-18303 | Test Report<br>Test Procedures | -<br>- |
| 4.5.2, 4.6 | DI-RELI-80253<br>DI-RELI-80255 | Failed Item Analysis Report<br>Failure Summary and Analysis Report | -<br>- |

The above documents were those cleared as of the data of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 Unit of purchase. The unit of purchase for the cleaning compound is the U.S. gallon. A U.S. gallon of liquid occupies 231 cubic inches (3.785 liters) at 60°F (15.6°C).

6.5 First article. When a first article inspection is required, the cleaning compound should be a first article sample. The first article should consist of the amount of cleaning compound specified in the contract or purchase order but should not be less than 5-gallons (see 6.2). The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:16Z
Check the source to verify that this is the current version before use.

6.6 Batch. A batch is defined as that quantity of material which has been manufactured by some unit chemical process and subjected to some physical mixing operation intended to make the final product substantially uniform.

6.7 Material safety data sheets. Contracting officers should identify those activities requiring copies of completed Material Safety Data Sheets prepared in accordance with FED-STD-313. (See 3.2.1.)

6.8 Subject term (key word) listing.
Biodegradable
Cleaner, gun
Degreaser
Foaming, low

Preparing Activity
Navy AS
(Project No. 6850-N849)



Source: https://assist.dla.mil -- Downloaded: 202610-21T00:16Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | MIL-C-29584(AS) | -90/09/30 |

3. DOCUMENT TITLE
Compound, Cleaning, Water Miscible For Aircraft Automatic Weapons

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON<br>(If applicable) | 7. DATE SUBMITTED (YYMMDD) |

8. PREPARING ACTIVITY

| a. NAME | b. TELEPHONE (Include Area Code) | |
|---|---|---|
| Commanding Officer<br>Naval Air Engineering Center<br>SESD (Code 5314) | (1) Commercial<br>(908) 323-1280 | (2) AUTOVON<br>624-1280 |
| c. ADDRESS (Include Zip Code)<br>Lakehurst, NJ 08733-5100 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 | |

Source: https://assist.dla.mil -- Downloaded: 2025/06/21 00:16Z
Check the source to verify that this is the current version before use.