MIL-H-12340C
27 November 1981
SUPERSEDING
MIL-H-12340B
5 March 1971

MILITARY SPECIFICATION

HEATER, SPACE (YUKON, M-1950, WITH ACCESSORIES)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type and size space heater (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing
PPP-T-70	-	Tape, Packaging, Plastic Film

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Laboratories, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4520

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	-	Preservation-Packaging, Methods of
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-P-3420	-	Packaging Materials, Volatile Corrosion Inhibitor, Treated, Opaque
MIL-L-10547	-	Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment

DRAWINGS

US ARMY NATICK RESEARCH AND DEVELOPMENT LABORATORIES

2-9-306	-	Heater, Space (Yukon, M-1950 With Accessories)
2-9-307	-	Body Assembly
2-9-308	-	Body
2-9-309	-	Door Assembly
2-9-310	-	Legs
2-9-311	-	Burner Assembly
2-9-312	-	Grate
2-9-313	-	Pipe Assembly
2-9-314	-	Installation and Operating Instructions
2-9-315	-	Pipe Flue Assembly, Section No.1

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Alternate components. Components offered as equivalent to components specified herein and on the referenced drawings as a specific manufacturer's part number or equal shall be functionally equal, of equal or better quality with the manufacturer's part number identified. The incorporation and inclusion of such a component in the design of the specified end product shall not require modification or change to any other specified component, and shall not reduce ease of maintenance

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

to it or any other components, unless such modification or change is specifically approved by the contracting officer. Prior to manufacture of the first article, or if none is required, prior to commencing production, the contractor shall submit for the contracting officer's approval, a list identifying each alternate component, together with proof that each listed component complies with requirements specified herein. The contracting officer, at his option, may require a physical sample of the proposed substitution. Approval of the submitted listing, together with necessary supporting data does not relieve the contractor of the responsibility that these components perform in accordance with specified requirements when incorporated into the end product.

3.2 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.3).

3.3 Materials and components. The materials and components shall be as specified herein and on the applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this specification (see 6.4).

3.3.1 Steel sheets, blued. The blued steel sheets shall be made from commercial quality steel. They shall be processed as hot-rolled annealed or cold-rolled annealed sheets and oxidized to produce a uniform light blue or black color. The steel shall be blued in the basic sheet. The use of another steel finish and then bluing is not considered acceptable for this application.

3.3.2 Aluminum alloy castings. Aluminum alloy castings shall conform to the following chemical analysis (percentages):

Copper	- 0.5 to 1.0
Silicon	- 11.0 to 13.0
Iron	- 1.3 maximum
Magnesium	- 0.7 to 1.3
Manganese	- 0.05 maximum
Zinc	- 0.03 maximum
Nickel	- 2.2 to 2.8
Other elements	- 0.05 maximum
Aluminum	- Remainder

3.4 Design and construction. The design and construction of the heater shall be as specified herein and as shown on the drawings referenced in 2.1.

3.4.1 Burner assembly. The burner assembly cap and body shall be aligned so that the burner cap shall enter a ring gage, inside diameter of 4.455 inches $\pm$ 0.005.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the currentversion before use.

The cotter pins used in the burner assembly shall be bent and turned so as not to interfere with the ring gage. The burner body shall not pass through a ring gage, inside diameter of 4.405 inches ± 0.005. The burner cap below the rib shoulder shall not enter a ring gage, inside diameter of 4.405 inches ± 0.005. The burner retainers shall be mounted with a gap of 0.010 inches ± 0.005 between the burner cap and the inside diameter of the retainer adjacent to the self-tapping screws. The fuel tube with drip valve shall be screwed tightly into the burner cap with a commercial grade pipe joint compound, impervious to gasoline and fuel oil. The joint compound shall not obstruct the fuel passage of the fuel tube and burner cap assembly.

3.4.2 Heater, legs. The heater leg dimples shall contact the heater in the closed, retracted position. Sufficient friction shall be provided to prevent the legs from falling when tested as specified in 4.5.1.

3.4.3 Pipe, flue. Each pipe flue joint shall be fabricated from a single piece of blued sheet steel (see 3.3.1). The connection between the vertical pipe and that portion forming the branch for the space heater connection on the pipe (section No. 1) shall be fabricated with sufficient lap to form a rigid joint when spot welded in position. The spot welds shall be spaced not more than 3/4 inch on centers. The pipe bottom shall be made from commercial quality hot or cold rolled steel and shall be hot dipped galvanized after fabrication.

3.4.4 Instruction sheet. An instruction sheet with information on both sides from the illustration and typing shown on drawing 2-9-314 shall be printed on white bleached sulfate stock paper with a minimum basic weight of 140 pounds (25-1/2 x 30-1/2-500). The illustration and typing on the instruction sheet shall be as large as the sheet will permit.

3.4.5 Components and accessories. Each heater shall be furnished as specified in table I.

TABLE I.

Item	Quantity
Body assembly	1
Burner assembly	1
Pipe flue, assembly, five sections	1
Grate	1
Cap, flue, 4 inch, cylinderical	1
Hose, gasoline	12 feet
Adapter kit, gravity feed	1
Wrench (Item 8, on drawing 2-9-308)	1
Wrench (Item 9, on drawing 2-9-308)	1
Wrench (Item 10, on drawing 2-9-308)	1
Instruction sheet	1

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

3.5 Contract data requirements. The contract data requirements shall be as specified (see 6.2 and 6.2.1).

3.6 Marking.

3.6.1 Heater door. The letters "U S", the contractor's name, contract number and date of manufacture shall be indented on the door of the heater.

3.6.2 Pipe, flue sections. Each section of pipe shall have the number of the section embossed thereon and in addition shall have the contractor's name, contract number and date of manufacture.

3.6.3 Burner cap. The burner cap shall have the contractor's name, contract number and date of manufacture cast in raised letters on the burner cap.

3.7 Workmanship. The units shall be free from fractures, splits, punctures, tears, dents, creases, bows, miscasts, deteriorations or malformations. There shall be no sharp edges, burrs or slivers. The finish shall be free of blisters, peel, chipped areas or areas of no film. The finish shall be free from smudges, poor touch up, scale, scratches, stain, overspray sag, imprint or embedded foreign matter. Threaded fasteners shall not be broken, stripped or loose. Holes for rivets shall be accurately punched or drilled and any burrs that would prevent proper seating of the rivet be removed. Rivets shall completely fill the holes, with full size heads neatly furnished and in full contact with the surface of the riveted members and shall not be loose. The surfaces of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be continuous, sound, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale and flux deposits (when flux is used) shall be removed from the finished welds, and rough edges and projections shall be dressed smooth.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.2), it shall be examined for the defects specified in 4.4.3.1 and 4.4.3.2 and tested as specified in 4.5.1. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Burner body and cap. The burner body and cap shall be checked for fit with the 4.4050-inch ring gage. Any nonconformance with the 3.4.1 shall be considered a defect. The inspection level shall be S-4 and the acceptable quality level (AQL) shall be 0.65 defects per hundred units. The lot shall be the bodies and caps of all the burner units offered for inspection at one time. The sample unit shall be one burner body or cap as applicable.

4.4.1.2 Burner assembly. The burner assembly shall be checked for fit with the 4.4550-inch ring gage. Any nonconformance with 3.4.1 shall be considered a defect. The inspection level shall be S-4 and the AQL shall be 0.65 defects per hundred units. The lot shall be all burner units offered for inspection at one time. The sample unit shall be one burner assembly.

4.4.2 In-process inspection. The fuel tube and burner cap assembly shall be examined for obstruction of the fuel passage through the fuel tube by the joint compound. When any nonconformance with 3.4.1 is noted, correction shall be made to the affected items and operation.

4.4.3 End item inspection. The end item shall be inspected in accordance with 4.4.3.1, 4.4.3.2, and 4.4.3.3. The lot size shall be expressed in units of one heater. The sample unit shall be one complete heater.

4.4.3.1 Visual examination. The end item shall be examined for the defects listed in table II. The inspection level shall be S-2 and the AQL shall be 2.5 major and 6.5 minor defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

TABLE II. Visual defects

Examine	Defect	Classification Major	Minor
Finish	Not as specified	X	
Design, construction and workmanship general (applicable to all components and assemblies)	Any component or part missing or not specified type or size	X	
	Fractured, split, punctured, torn, dented, creased, deteriorated or malformed	X	
	Sharp burr or edge, or sliver	X	
Welding	Missing, incomplete, burn holes, cracked, fractured or not fused	X	
	Undercut, not smooth and uniform, or scale or flux deposits not removed		X
Rivets (when required)	Broken, not peened, or insufficiently peened or loose		X
Fasteners (bolts, nuts, screws, studs and other types of threaded fasteners)	Broken, stripped, fractured, or not tight		X
Marking	Missing, incomplete, not legible, not specified type or size, or not in the proper location		X

4.4.3.2 Dimensional examination. The end item shall be examined for conformance to the specified dimensions. Any measurement deviating from the specified dimension shall be classified as a defect. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

4.4.3.3 End item testing. The end item shall be tested as specified in 4.5.1. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing and marking comply with section 5. Defects shall be scored in accordance with table III. The sample unit shall be one shipping container fully packaged. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 6.5 defects per hundred units.

TABLE III. Packaging defects

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; or of improper size, location, sequence, or method of application
Preservative application	Preservative improperly applied or missing
Materials	Component missing, damaged, or otherwise defective affecting serviceability
Workmanship	Inadequate application of components such as incomplete closure of case liners, container flaps, loose strapping, inadequate stapling Bulged or distorted container Blocking and cushioning inadequate, improper, or missing

4.5 Methods of inspection.

4.5.1 Leg test. The heater body shall be suspended horizontally with the legs in the retracted position. While in this position, leg retention capability shall be checked. Any failure to meet the requirements of 3.4.2 shall constitute failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. All metal surfaces of the heater, components and accessories, except the gravity feed adapter kit and the 12 foot hose, shall be cleaned process C-1 of MIL-P-116 and thoroughly dried. Accessories shall not be cleaned if preservative application has been recently effected in accordance with their individual specifications and these requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

5.1.1.2 Preservative application.

5.1.1.2.1 Instruction sheet. The instruction sheet shall be preserved in accordance with method IC-1 of MIL-P-116. The width of the bag shall not exceed 9-1/2 inches.

5.1.1.2.2 Draft diverter. The draft diverter, cleaned as specified in 5.1.1.1, shall be coated with type P-7 preservative conforming to MIL-P-116 and thoroughly drained. (Note: Preservative application on the first 6 inches of guy line ends, tied to the guy line retainer loops will not be considered objectionable.) Each of the three guy lines shall be carefully and neatly folded or coiled into a small bundle and tied in the center with cotton twine or tape. The three bundled guy lines shall then be brought together and wrapped in barrier-material conforming to type II, grade A of MIL-B-121, and the wrap secured with gummed paper tape, minimum 2 inches in width conforming to type III, grade B of PPP-T-45. There shall be not more than 6 inches of the guy line exposed outside the wrap. The guy line retainer loop shall be folded against the bottom band and the wrapped guy lines placed within the diverter. The diverter shall then be completely wrapped with barrier-material and sealed with tape specified herein.

5.1.1.2.3 Pipe assembly. The five sections of the pipe assembly, including the bottom cap, cleaned as specified in 5.1.1.1, shall be lightly coated with preservative specified in 5.1.1.2.2 and thoroughly drained. The five pipe sections shall then be nested and the pipe bottom assembled thereto.

5.1.1.2.4 Burner assembly. The burner, completely assembled with fuel tube and drip valve, cleaned as specified in 5.1.1.1, shall be coated with preservative specified in 5.1.1.2.2, and thoroughly drained. The threads and valve openings shall be protected with commercial type thread protectors, or with tape conforming to PPP-T-70. The burner assembly shall then be form wrapped with barrier-material, and the wrap sealed as specified in 5.1.1.2.2.

5.1.1.2.5 Hose. The 12 foot hose section shall be coiled to a maximum outside diameter of 9 inches and the male and female couplings then connected to the full length of the threads. The coiled hose shall be tied with cotton tape or twine at two opposite places and the coil then completely wrapped in barrier-material and the wrap sealed as specified in 5.1.1.2.2.

5.1.1.2.6 Adapter kit, gravity feed. The adapter kit shall be disassembled by removing only the upper and lower vent tubes from the plug body. The upper vent tube, the lower vent tube, and the plug body with hose loop drip interceptor attached, shall be tied securely together with cotton tape or twine and then completely wrapped in barrier-material and the wrap sealed as specified in 5.1.1.2.2.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

5.1.1.2.7 Wrenches. The three wrenches, cleaned as specified in 5.1.1.1, shall be preserved together in accordance with method IC-1 of MIL-P-116.

5.1.1.2.8 Complete space heater. The grate with legs up shall be placed flat on the bottom of the space heater. The balance of the components and accessories specified in 3.4.5 shall be placed within the heater body in the most compact manner. Care shall be exercised to see that the coiled hose retains its shape. Shredded wax paper, or crumpled barrier-material specified in 5.1.1.2.2, shall be used to cushion and prevent movement of the contents while in transit. The legs shall be folded against the bottom of the space heater body, and the door closed and securely latched. The entire unit shall then be completely wrapped in material conforming to type I, class 1, style A of MIL-P-3420 (see 6.5) and the wrap unit sealed with gummed paper tape specified in 5.1.1.2.2.

5.1.1.3 Unit packing. Each complete heater prepared as specified in 5.1.1.2, shall be unit packed in a snug-fitting fiberboard box conforming to V3c or V3s, style RSC of PPP-B-636. Closure shall be in accordance with method V as specified in the appendix of PPP-B-636.

5.1.2 Commercial. The heaters with components and accessories shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Two complete heaters, preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to overseas type of PPP-B-601, or class 2, style 2 or 4 of PPP-B-621. Each shipping container shall be provided with a type I or II, grade B or C, case liner conforming to MIL-L-10547. Each shipping container shall be closed and reinforced with strapping in accordance with the appendix of the applicable container specification.

5.2.2 Level B packing. Each complete heater preserved as specified in 5.1, shall require no further packing.

5.2.3 Commercial packing. The heaters with components and accessories, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or MIL-STD-1188, as applicable.

5.3.1 Precautionary marking. The following information shall be legibly printed or stenciled on not less than 3 faces of each shipping container:

Volatile corrosion inhibitor treated paper
used herein. Do not open until ready for
use or inspection. (see 6.6).

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The heater is intended to be used for heating the 10 man arctic tent. The burner of this space heater will function with leaded or unleaded gasoline. The heater may be adapted for emergency limited use with solid fuels.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) When a first article is required (see 3.2, 4.2 and 6.3).
(c) Contract data requirements (see 3.5 and 6.2.1).
(d) Inspection record details (see 4.1).
(e) Selection of applicable levels of preservaton and packing (see 5.1 and 5.2).

6.2.1 Contract data requirements. Any data item to be delivered under any contract for items should be specifically called for in the contract in accordance with the applicable regulation of the procuring activity (see 3.5 and 6.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the DAR.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.5 Personnel handling. Personnel handling material covered by MIL-P-3420 should be instructed to wash their hands thoroughly before handling or eating food (see 5.1.1.2.8).

6.6 Heaters wrapped. Heaters wrapped in material as specified in 5.1.1.2.8 should be examined and re-preserved approximately 24 months from the date of the initial pack (see 5.3.1).

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD, ME
Navy - MS
DLA - CS

User activities:

Army - CE
Navy - MC

Preparing activity

Army - GL

Project No. 4520-0270

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS. This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE. This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-H-12340C Heater, Space (Yukon, M-1950, With Accessories)

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:43Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development
Laboratories
ATTN: DRDNA-ES
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:43Z
Check the source to verify that this is the current version before use.