MIL-P-12390E

29 June 1971
SUPERSEDING
MIL-P-12390D
~~11 October 1967~~

MILITARY SPECIFICATION

PREFLUSHING MACHINE, DISH

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of preflushing machine used in conjunction with a dishwashing machine.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

CC-M-636	-	Motors, Alternating-Current, (Fractional Horsepower).
TT-P-664	-	Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-636	-	Box, Fiberboard.
PPP-C-650	-	Crates, Wood, Open and Covered.
PPP-T-60	-	Tape: Pressure-Sensitive Adhesive; Waterproof, For Packaging.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-V-13811	-	Varnish, Waterproofing, Electrical, Ignition.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristics, Requirements for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, with Appropriate Test Methods.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring acitivty or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNDERWRITERS' LABORATORIES, INC. (UL)

Standard No. 73 - Motor-Operated Appliances

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 1285 Walt Whitman Road, Melville, Long Island, N.Y. 11746; 207 East Ohio Street, Chicago, Illinois 60611; or 1655 Scott Boulevard, Santa Clara, California 95050.)

NATIONAL SANITATION FOUNDATION (NSF)

Criteria C-2 - Special Equipment and/or Appurtenances

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, P. O. Box 1468, Ann Arbor, Michigan 48106.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

Specification A167-63 - Corrosion-Resisting Chromium Nickel Steel Plate, Sheet, and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article.- When specified (see 6.2), the supplier shall furnish a sample for first article inspection and approval (see 4.2 and 6.3).

3.2 Standard product.- The preflushing machines delivered under this specification shall be the manufacturer's standard commercial product, except for any changes necessary to meet specification requirements.

3.3 Standards.-

3.3.1 NSF standard.- The preflushing machine shall conform to the applicable requirements of NSF Criteria C-2.

3.3.1.1 NSF certification.- The supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the preflushing machine he proposes to furnish under this specification meets the applicable requirements of NSF Criteria C-2 as follows:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished preflushing machine shall be submitted prior to approval of the preproduction sample, if one is submitted, or prior to approval of the first shipment, or

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

(2) A certification for the preflushing machine issued by NSF under their special one-time evaluation/certification service shall be submitted prior to approval of the preproduction sample, if one is submitted, or prior to approval of the first shipment, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the preflushing machines are being procured, indicating that the dispensers have been tested and conform to NSF Criteria C-2, shall be submitted prior to approval of the preproduction sample, if one is submitted, or prior to commencing production.

3.3.2 UL standard.- The preflushing machine shall conform to the applicable requirements of UL Standard No. 73.

3.3.2.1 UL certification.- Prior to approval of the preproduction sample, if one is submitted, or prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the preflushing machine he proposes to furnish under this specification meets the requirements of UL Standard No. 73. Acceptable evidence of meeting the requirements of this standard shall be the UL label, UL listing mark, or a certified test report acceptable to the Government, from a recognized independent testing laboratory, indicating that the preflushing machine has been tested and conforms to the applicable requirements of UL Standard No. 73.

3.4 Materials.- Materials not definitely specified shall be of the quality normally used by the manufacturer for dish preflushing machines provided that the completed item complies with all provisions of this specification.

3.4.1 Corrosion-resisting steel.- Corrosion-resisting steel shall conform to the chemical composition of type 302 or 304 as specified in ASTM A167.

3.4.2 Bolts, nuts, and screws.- Material for bolts, nuts, and screws shall be brass, bronze, or corrosion-resisting steel.

3.5 Design.- The machine shall be designed for removing waste food particles from dishes and tableware before they are placed in a dishwashing machine. The machine shall consist of a rinsing tank and a gusher tube through which water of controlled temperature and quantity shall flow. Water shall be pumped through the gusher tube by an electric motor-driven pump. Soiled water shall collect in the tank, food waste shall be retained in a scrap basket, and grease particles shall be drained off through a center drainage pipe while the remaining water is recirculated and re-ejected from the gusher tube. Fresh hot and cold water shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

be supplied to a thermostatically controlled mixing valve which shall maintain water at a temperature of 115 F. plus or minus 5 F. Machine design shall include provisions for lubricating bearings, shafts, and other moving parts requiring lubrication.

3.5.1 Overall dimensions.- The preflusher shall be not greater than 33 inches wide from drive belt cover to mixing valve and not greater than 24 inches outside diameter at the tank top flange. Overall height from floor with legs adjusted to mid position shall be 33-3/4 inches.

3.6 Construction.-

3.6.1 Tank.- The tank shall be fabricated of minimum 0.0512-inch thick corrosion-resisting steel specified in 3.4.1. Inside diameter shall be 19 inches and inside depth shall be 24-1/8 inches with tolerances of plus or minus 1/4 inch applicable to both dimensions. The top of the tank side wall shall be flanged-out at 90 degrees. The flange shall be between 2 and 2-1/2 inches wide and shall be fitted with a polychloroprene gasket. The tank sidewall shall be indented around the circumference, or a ring shall be welded to the inside of the tank, to support the scrap basket. The bottom center of the tank shall be depressed and cut out to allow complete drainage when the drain pipe is removed. The tank shall not leak when tested as specified in 4.4.1.

3.6.2 Scrap basket.- The scrap basket shall be fabricated of corrosion-resisting steel specified in 3.4.1. The basket shall be 13 inches deep plus or minus 1/8 inch by 16-3/16 inches body diameter plus or minus 1/16 inch. The basket shall consist of a top ring, perforated sidewall, and solid bottom. Components shall be spotwelded together to form a rigid assembly. The basket shall fit into the tank and shall be held in place by the sidewall indentation or ring.

3.6.2.1 Top ring.- The top ring shall be minimum 0.0711 inch thick and shall measure 18-1/2 inches outside diameter plus or minus 1/16 inch. the ring shall be flanged out at the top approximately 20 degrees from horizontal. Two strap type lifting handles located 180 degrees apart shall be spotwelded to the flange. The lower portion of the ring shall be vertical for a distance to allow spotwelding to the perforated sidewall. The flange shall be notched approximately 90 degrees from handle locations to provide clearance for the gusher tube.

3.6.2.2 Sidewall.- The basket sidewall shall be fabricated of minimum 0.045-inch-thick perforated sheet. Perforations shall be 1/4 inch square on 3/8 inch centers. The sheet shall be rolled into a 16-inch diameter plus or minus 1/4 inch and lap seamed and spotwelded. The sidewall shall be spotwelded to the top

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

ring and bottom plate. The diameter of the sidewall shall be reduced directly below the flange notch to accommodate the gusher tube.

3.6.2.3 Bottom plate.- The bottom shall be formed of minimum 0.0711-inch-thick sheet. The plate shall be bent 90 degrees to allow spot welding of the sidewall.

3.6.3 Scrapping basin.- The inside top of the tank shall be fitted with a removable, funnel-shaped scrapping basin. The lowest point of the basin shall be cut out to allow water and food particles to enter the tableware trap. Cover shall be formed from minimum 0.0565 inch thick corrosion-resisting steel.

3.6.4 Tableware trap.- A container for trapping tableware and small dishes shall be welded to the underside of the basin. One side of the container shall be open to allow waste particles to overflow into the scrap basket. The trap shall be fabricated of minimum 0.045 inch thick corrosion-resisting steel.

3.6.5 Gusher tube.- The gusher tube shall be cast of aluminum or formed from copper tube. The inside cross-sectional area of the tube shall be approximately 1.25 square inches. The lower end of the tube shall be connected to the pump discharge fitting in a manner to allow removal. The tube shall extend up vertically between the side of the tank and the scrap basket and shall fit through the notch in the basket flange. The top of the tube shall fit an opening in the top cover and shall be secured to the tank by means of a wingnut or knurled screw. The top of the tube shall be offset to direct the water towards the opening in the top (see 4.4.3).

3.6.6 Drain tube.- A nominal 2-inch outside diameter brass drain tube with a nominal 1/8-inch wall thickness shall be provided at the bottom of the tank. Tube length shall be such that height of water in the tank will be maintained above pump suction elbow. The lower end shall fit into a brass or bronze tapered drain connection. The connection shall extend through the base and be secured by a brass or bronze lock nut. A gasket shall be located between the tank and the drain connection. When tested as specified in 4.4.1, there shall be no leakage at the drain connections. The drain tube shall have a brass or corrosion-resisting steel safety chain joining it to the pump suction elbow.

3.6.7 Base.- The tank and motor and pump assembly shall be mounted on a base. The base shall be cast or fabricated from aluminum and shall be provided with not less than three legs. At least one of the legs shall be located directly below the pump and motor. Each leg shall incorporate a solid aluminum or corrosion-resisting steel adjustable foot with at least 3 inches of adjustment.

3.6.8 Pump and motor mount.- The pump and motor mount shall be cast or fabricated as an integral part of the base or may be bolted to the base.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:46Z
Check the source to verify that this is the current version before use.

3.6.9 Pump.- The pump shall be a nonclogging, centrifugal type, capable of delivering at least 20 gallons of water per minute and a gusher stream not less than 5 inches nor more than 7 inches above the rim of the tank. Pump capacity and height of gusher stream shall be verified by the test specified in 4.4.3. Pump housing shall be bronze or cast iron and pump impeller shall be brass or bronze. Shaft shall be corrosion-resisting steel and shaft bearings shall be bronze or self-lubricating oilite bearings. The pump shall be bolted to the side of the tank and shall not leak when tested as specified in 4.4.1.

3.6.9.1 Suction elbow.- Pump suction elbow shall be cast brass or bronze. The elbow shall be secured to the pump housing by a gasketed connection.

3.6.9.2 Drive belt guard.- Pulleys and drive belt(s) shall be covered by an aluminum or corrosion-resisting steel removable guard. Material thickness shall be not less than 0.081 inch.

3.6.10 Electric motor.- Motor shall be rated not less than 1/6 horsepower and shall be dripproof, splashproof, or totally inclosed, continuous duty, conforming to CC-M-636. Unless otherwise specified (see 6.2), the motor shall be suitable for operation on a nominal 120-volt, 60-hertz, single-phase, alternating-current, power system. Motor shall have not more than one starting contact and shall be equipped with an internal overheating protective device. The motor shaft shall drive the pump shaft by means of pulleys and "Vee" belt(s). One of the pulleys shall be adjustable to vary pump output.

3.6.11 Water mixing valve.- The water-mixing valve shall be located approximately 4 inches down from the top of the tank. The valve shall automatically blend hot and cold incoming water to a temperature of 115 F. plus or minus 5 F. at a flow rate of 1-1/2 gallons per minute when tested as specified in 4.4.2. An auxiliary tank overflow shall be provided below the 115 F. water inlet. The mixing valve shall be so mounted that an air gap equal to at least twice the diameter of the incoming water pipe is provided between the mixing valve outlet and tank overflow. The valve outlet to the tank shall be bronze, brass, or corrosion-resisting steel. Hot and cold water inlets at the mixing valve shall be 1/2-inch taper pipe threads.

* 3.6.12 Electromagnetic compatibility.- When specified (see 6.2), preflushing machines procured under this specification shall be designed and equipped to meet the electromagnetic control requirements and test limits for class II B equipment as specified in MIL-STD-461 (see 4.4.4).

3.6.13 Repair and maintenance.- Construction shall allow adjustment, service, and replacement of electrical components, drive belt(s), pump, and pump components without removal or disassembly of other major components. In addition, there shall be free access to inspect, service, or adjust any other components as required for proper operation of the preflushing machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

3.7 Marking.- The preflushing machine shall be provided with a corrosion-resistant metal identification plate, permanently marked in accordance with MIL-STD-130. The plate shall be not less than 0.020 inch thick and shall be securely fastened to the tank in a plainly visible location.

3.8 Lubrication instructions.- A metal or decal lubricating chart shall be securely fastened to the tank. The chart shall state the type and grade of lubricant required and the time interval when lubrication should be performed.

3.9 Finish.- The preflushing machines shall be finished in accordance with NSF Criteria C-2.

3.10 Workmanship.- Burrs and rough or sharp edges shall be removed. Components shall be assembled in a neat manner. Bolts and screws shall be drawn tight and rivets shall be fully peened. Surfaces of parts to be welded or brazed shall be clean and free from scale. Welds and brazes shall be sound, smooth, and free from pits, cracks, and flashes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

★ 4.2 First article inspection.- When a preproduction sample is required, it shall be examined for the defects listed in table I and dimensions specified herein and tested as specified in 4.4.1 through 4.4.4, as applicable. The presence of any defects listed in table I, any dimension not within specified requirements or failure to pass any tests shall be cause for rejection of the preproduction sample.

4.3 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated herainafter.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:46Z
Check the source to verify that this is the current version before use.

4.3.2 End item inspection.- The inspection lot shall consist of all preflushing machines offered for inspection at one time. The sample unit for the inspection shall be one completely fabricated preflushing machine.

4.3.2.1 Visual examination.- Examination shall be made of the end item for defects in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I.- Classification of defects

Examine	Defect	Classification Major	Minor
Construction and workmanship (general)	Any component fractured, dented, or malformed	X	
	Any burr, or rough or sharp edges	X	
	Functioning component that requires abnormal force to operate		X
	Any component not connected or joined as specified or poorly accomplished	X	
	Adjustable assembly that cannot be adjusted	X	
	Adjustable assembly not properly adjusted to perform the intended function		X
	Component not accessible for servicing where required	X	
	Unit perceptibly out of square or alignment	X	
Welding and brazing	Not sound or contains cracks	X	
	Not smooth or contains pits, or flashes		X
	Flux or scale deposits not removed		X
Threaded fasteners	Missing, broken, stripped or loose		X
Construction (applicable to specific components)			
Tank	Top flange not as specified	X	
	Gasket missing		X
	Support does not retain scrap basket in position in tank (too loose)	X	
	Bottom depression does not allow complete drainage	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

TABLE I.- Classification of defects (cont'd)

Examine	Defect	Classification: Major	Minor
Construction (applicable to specific components) (cont'd)			
Scrap basket	Assembly not rigid	X	
Top ring	Not flanged as specified	X	
	Handles missing or not located as specified	X	
	Not notched or notch too small to clear gusher tube	X	
Sidewall	Not perforated	X	
	Seamed joint not as specified		X
Bottom plate	Not joined to sidewall as specified		X
Scrapping basin	Not shaped to direct water to tableware trap	X	
Tableware trap	Side not open	X	
Gusher tube	Not copper or aluminum	X	
	Tube not removable at pump		X
	Wingnut or knurled screw missing or does not hold tube securely		X
	Not offset as specified	X	
Drainage tube	Tube length not higher than suction elbow (check visually, measure if in doubt)	X	
	Not brass		X
	Fittings not as specified	X	
	Gasket missing		X
	Safety chain missing		X
Base	Not aluminum	X	
	One leg not located below pump and motor	X	
	Adjustable feet missing or not adjustable	X	

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:46Z
Check the source to verify that this is the current version before use.

TABLE I.- Classification of defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Construction (applicable to specific components) (cont'd)			
Pump	Not type specified	X	
	Not fastened to tank, as specified		X
	Elbow gasket missing		X
	Belt guard missing	X	
Motor	Drive not accomplished with pulleys and "Vee" belts.	X	
	Pulley not adjustable	X	
Mixing valve	Air gap not as specified (check visually, measure if in doubt)	X	
	Auxiliary overflow missing	X	
Identification marking and lubrication chart	Missing, incomplete, not legible		X

4.3.2.2 Dimensional examination.- Dimensional examination shall be made of the end item to determine compliance with this specification. Any dimension not within the specified requirement shall be classified a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.3.2.3 Testing of the end product.- Each preflushing machine shall be tested as specified in 4.4.1. When no preproduction sample is required, one machine from each production lot shall be tested as specified in 4.4.2, 4.4.3 and 4.4.4, as applicable.

4.3.3 Standards compliance.- Proof of compliance with UL and NSF requirements of 3.3 shall be submitted to the Government representative.

4.3.4 Examination of preparation for delivery.- Examination shall be made to determine that preservation, packaging, and marking as required by section

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

5 of this specification are complied with. Defects shall be as indicated in table II. The lot shall be the number of shipping containers offered for inspection at one time. The sample unit shall be one container fully prepared for delivery. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

TABLE II.- Examination of preparation for delivery

Examine	Defect
Markings	Missing; incorrect; illegible; or improper size, location, sequence, or method of application
Materials	Component missing, damaged, or otherwise defective

4.3.5 Examination of shipping containers.- When shipping containers are required to be in accordance with PPP-B-601 or PPP-C-650, examination for defects in closure and strapping shall be in accordance with the applicable container specification. Examination for defects in anchoring or blocking and bracing shall be in accordance with MIL-STD-1186.

4.4 Tests.-

4.4.1 Leakage.- Water shall be fed into the tank until it runs out the top of the drainage pipe. The tank, drainage fittings, and pump gasketed connection shall be examined to determine conformance with leakage requirements of 3.6.1, 3.6.6 and 3.6.9, respectively. Evidence of leakage shall constitute failure of the test.

4.4.2 Mixing valve.- The water temperature at the discharge side of the mixing valve shall be measured with a thermocouple or thermometer to determine conformance with blended water temperature requirements of 3.6.11. Inability of the mixing valve to blend water to the required temperature shall constitute failure of the test.

4.4.3 Pump.- The machine shall be connected to a power and water supply. The drain shall be plugged and the overflow connection shall be capped. Approximately 30 gallons of water shall be introduced into the tank. A minimum 30 gallon capacity container of a predetermined weight shall be placed in position under the

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:46Z
Check the source to verify that this is the current version before use.

gusher stream. The pump shall be started and the water from the gusher shall be caught in the container. The time shall be noted at the instant water starts entering the container. At the end of one-minute the container shall be removed and the container with water shall be weighed to determine that the pump delivers the water at the rate specified in 3.6.9. The gusher stream shall be measured by laying a straight edge across the top rim of the tank and projecting a ruler vertically from the rim level at the point of maximum gusher stream height to determine compliance with the gusher stream height requirements of 3.6.9. The gusher stream direction of flow shall be checked to determine conformance with 3.6.5. Inability of the pump to conform to the requirements of 3.6.5 shall constitute failure of the test.

* 4.4.4 Electromagnetic compatibility test.- The preproduction sample or initial unit of production, as applicable, shall be tested by the supplier in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or an independent testing agency. The supplier shall furnish the contracting officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic test report and the requirements meet MIL-STD-461.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.- Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Preservation.-

5.1.1.1.1 Belt and pulley.- The belt shall be removed from each machine. The pulley shall be cleaned process C-1 and dried in accordance with MIL-P-116. The pulley shall then be coated with primer conforming to TT-P-664 and thoroughly dried. The belt shall then be replaced and released from tension.

5.1.1.1.2 Sealing.- All openings into the electric motor, blender, and the inlet and overflow shall be sealed with tape conforming to PPP-T-60 and the tape overcoated with varnish conforming to MIL-V-13811. The threads on the drain connection shall be protected by a commercial thread protector. For motor openings, a caution tag shall be attached to the preflushing machine with the following inscription:

Caution: Remove protective tape from the exterior of the motor before operation of the preflushing machine.

5.1.1.2 Packaging.- The leg adjustments shall be removed from each machine and packaged method III of MIL-P-116 in a snug-fitting fiberboard box conforming

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Closure of the fiberboard box shall be in accordance with PPP-B-636. The fiberboard box shall be placed inside the scrap basket and secured to prevent movement while in transit. The scrap basket and scrapping plate shall be secured in place to prevent movement while in transit.

5.1.2 Level C.- Each preflushing machine shall be preserved and packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Each preflushing machine, preserved and packaged as specified in 5.1, shall be packed in a cleated-plywood shipping container conforming to overseas type of PPP-B-601. The machine shall be positioned within the container so that the motor fits in one corner. Additional floor members shall be added to the container to provide a firm base for the machine. Lumber blocking shall be applied between the machine and the container base to provide a minimum clearance of 3/4 inch between the legs of the machine and the base of the container and to provide support for the pump and motor mount. The machine shall be secured by blocking and bracing or anchoring in accordance with MIL-STD-1186. Closure and strapping shall be in accordance with PPP-B-601.

5.2.2 Level B.- Each preflushing machine, preserved and packaged as specified in 5.1, shall be packed in a wood crate conforming to style B, type I of PPP-C-650. The contents shall be covered with a shroud as specified in the appendix of PPP-C-650. Anchoring or blocking and bracing and additional floor members shall be as specified in 5.2.1.

5.2.3 Level C.- Preflushing machines, preserved and packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers and packing shall comply with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.- In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The preflushing machine covered herein is intended for use in removing waste food particles from dishes and tableware before they are placed in a mechanical dishwashing machine.

Source: https://assist.dla.mil -- Downloaded: 20260-17T22:46Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a first article is required (see 3.1, 4.2 and 6.3).
(c) Electrical characteristics, if other than specified herein (see 3.6.10).
(d) When electromagnetic compatibility is required (see 3.6.12).
(e) Selection of the applicable levels of preservation and packaging, and packing (see 5.1 and 5.2).

6.3 First article.- When a first article is required, it shall be inspected and approved under the approriate provisions of paragraph 7-104.55 of the ASPR's. The first article should be a preproduction sample. The first article should consist of one unit. The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for inspection and approval of the first article.

6.4 Contract data requirements.- Any requirements for equipment manuals for the item covered by this specification should be included in DD Form 1423 Contract Data Requirements List and cited in the contract.

6.5 The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activity:

Army - MD

User activity:

Army - CE

Preparing activity:

Army - GL

Project No. 7320-0364

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R[illegible]

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

Preflushing Machine, Dish MIL-P-12390E

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-17T22:46Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-BQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:46Z
Check the source to verify that this is the current version before use.