MIL-C-11347E
16 March 1977
SUPERSEDING
MIL-C-11347D
11 January 1971

MILITARY SPECIFICATION

CASES, BATTERY AND LIGHTING ACCESSORY,

FOR SURVEYING EQUIPMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a battery case complete with connector cord and plugs, and a lighting accessory case complete with miniature incandescent electric lamps and a connector cord with plugs.

1.2 Classification. The cases shall be of the following types, as specified (see 6.2):

Type I - Battery case.
Type II - Lighting accessory case.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.

FSC 6675

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:57Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.

DRAWINGS

ME

TA13217E6199	- Cases, Battery and Lighting Accessory.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:57Z
Check the source to verify that this is the current version before use.

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The battery and lighting accessory cases (hereinafter called "cases") shall be in accordance with Top Assembly TA13217E6199 for Type I and Type II, and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the cases. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (first-produced cases). The contractor shall furnish one or more cases as specified (see 6.2) for examination and testing within the time frame specified (see 6.2) to prove that his production methods will produce cases that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as shown on the applicable drawings. Materials not specified shall be selected by the contractor, shall be nonmagnetic, and shall be subject to all provisions of this specification (see 6.4).

3.4 Identification marking. The cases shall be identified in accordance with MIL-STD-130.

3.5 Treatment and painting. The portions of the cases normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, Type A, color as specified (see 6.2).

3.6 Workmanship. All parts, components, and assemblies of the cases including molded parts, stampings, machined surfaces, and welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material.

Source: https://assist.dla.mil -- Downloaded: 202640-17T15:57Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.1.2 Disassembly inspection. Failure of any examination or test by the first-produced case shall be cause for disassembly, in the presence of a Government representative, of the first-produced case to the extent necessary to determine the cause of the failure. Each disassembled part shall be examined in detail for compliance with this specification and referenced drawings in regard to materials, dimensions, tolerances, and workmanship. Parts not complying with such requirements shall be rejected and shall be cause for rejection of the first-produced case. Reassembly with replacement parts and retesting shall be the responsibility of the contractor.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First-produced cases inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First-produced cases inspection.

4.3.1 Examination. The first-produced cases shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection or for performing the disassembly inspection specified in 4.1.2.

4.3.2 Test. The first-produced cases shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection or for performing the disassembly inspection specified in 4.1.2.

Source: https://assist.dla.mil -- Downloaded: 202640-17T15:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for the defects specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The cases shall be examined as specified herein for the following defects:

Major

101. Cases not constructed as specified.
102. Material not as specified.
103. Workmanship not as specified.

Minor

201. Identification marking missing, incomplete, or illegible.
202. Treatment and painting not as specified.

4.5.2 Test. The cases and the connector cords with plugs shall be connected to an electrical circuit and tested for operation. Inability of the rheostat to vary the light intensity to the instrument receptacle or to give full intensity to the lamp receptacle shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:57Z
Check the source to verify that this is the current version before use.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following major defects. AQL shall be 2.5 percent defective.

104.	Materials, methods, and containers not as specified for Levels A and B. Each incorrect material, method, or container shall constitute one defect.
105.	Each case not individually boxed and the case not immobilized within the box as specified for Level A.
106.	Method of box closure not as specified for Level A.
107.	Cases of unlike description packed together for Level A or Level B.
108.	Strapping not as specified for Level A.
109.	Marking illegible, incorrect, incomplete, or missing for Level A, Level B, or Commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each battery case and each lighting accessory case shall be individually placed in a close-fitting box conforming to PPP-B-636, W5c or W6c, style optional. Each case shall be immobilized within the box to prevent damage. Box closure shall be as specified for Method V in the appendix to the box specification.

5.1.2 Commercial. Each battery case and each lighting accessory case shall be preserved to afford protection against damage from the contractor to the initial destination.

5.2 Packing. Packing shall be Level A, Level B, or Commercial, as specified (see 6.2).

5.2.1 Level A. Cases of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, style optional, in quantities not to exceed the weight limitation of the box specification. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:57Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Cases of like description, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-636, V3c or V3s, style optional, in quantities not to exceed the size and weight limitations of the box specification.

5.2.3 Commercial. Cases, preserved as specified in 5.1, shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in fiberboard containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall reflect as a minimum, the item name, federal stock number, quantity, contract or purchase order number, and appropriate address markings on the shipping container. The marking shall be applied with a waterproof material, shall be legible, and shall provide a definite contrast.

6. NOTES

6.1 Intended use. The cases are intended for use with tripod-mounted, night-illuminated surveying instruments.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type case required (see 1.2).
(c) Time frame required for submission of first-produced cases and number of cases required (see 3.2).
(d) Color cases are required to be painted (see 3.5).
(e) Degree of preservation and degree of packing required (see 5.1 and 5.2).
(f) When other than Finish B strapping is required (see 5.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:57Z
Check the source to verify that this is the current version before use.

6.3 First-produced case. Any changes or deviations of production cases from the approved first-produced case during production will be subject to the approval of the contracting officer. Approval of the first-produced case will not relieve the contractor of his obligation to furnish cases conforming to this specification.

6.4 It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification.

Custodians:
Army - ME
Air Force - 99

Review activity:
DSA - GS

Preparing activity:
Army - ME

Project 6675-0641

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-11347E Cases, Battery & Lighting Accessory, for Surveying Equipment

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:57Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:57Z
Check the source to verify that this is the current version before use.