MILITARY SPECIFICATION

PRIMER, ELECTRIC, M59, PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for, loading, assembling and packing for one type of primer, designated as Primer, Electric, M59, for use in Photoflash Cartridges.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified (see 6.2), the following specification and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	- Preservation - Packaging, Method Of
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1169	- Packaging, Packing, and Marking for Shipment of Inert Ammunition Components

FSC 1390

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

8848644	- Primer, Electric, M59, Assembly
8853703	- Boxes, Set-up, Packing Ammunition, Inner and Outer, for Primer Electric, M59 Assembly, Details and Packing and Marking
8853702	- Box, Packing Ammunition, for Primer, Electric, M59, Assembly Details and Packing
9226356	- Primer, Electric, M59, Parts Arrangement

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings, specifications and standards.

3.2 Parts. The parts shall comply with all requirements specified on drawing (dwg. 9226356), and with all requirements specified in applicable specifications.

3.3 Assembly. The primers shall comply with all requirements specified on drawing (dwg.) 8848644, and with all requirements specified in applicable specifications.

3.4 Moisture content of igniter mixture. The moisture content of the igniting mixture, at the time of loading, shall not exceed 0.30 percent.

3.5 Functioning.

3.5.1 All-Fire. The primer assembly shall fire when a 1.8 ampere maximum (max.) current is applied to the electrode.

3.5.2 No-Fire. The primer assembly shall not fire when a 0.70 ampere minimum (min) current is applied to the electrode.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

3.6 First Article Inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship (Metal Parts). All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surfaces coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. (Required packing shall be dry)

3.8 Workmanship (Plastic Parts). All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner and all manufacturing, processing and assembly operations shall be correctly performed. They shall be free of burrs, chips, sharp edges, cracks, crazes, unblended radii, porosity, warpage, burn marks, checks, chipped edges, blisters, excess flash, dirt, grease, rust, salt deposits, visible raised cement seams, solder splash, corrosion products, and other defects and foreign matter which would affect their serviceability. The cleaning method used shall not be injurious to any part or assembly nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat, legible and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer. The first article sample shall consist of twenty-five (25) complete sets of parts and sub-assemblies (i.e., 25 each of every component and sub-assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

including at least five (5) items from each cavity used to produce molded parts and be so identified as to permit tracing each item to the cavity in which it was molded) and three hundred (300) complete primer assemblies. The first article shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Primer, Electric, M59, Inert Parts and Complete Assemblies				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Inert Parts				
	(Dwg. 9226356)				
	Examination for defects	25a		3.2	4.4.2.1 to 4.4.2.5
	Body and Electrode Assembly	c		3.2	4.4.5.1
	(Dwg. 8848643)				
	Primers (Complete Assemblies)				
	(Dwg. 8848644)				
	Examination for Defects	50b		3.3	4.4.2.6 to 4.4.2.7
	Tests				
	Electrical Resistance				
	((Dwg. 8848644)	300	100%		4.5.3
	No-Fire	150		3.5.2	4.5.2.2
	All-Fire	150		3.5.1	4.5.2.1
	Packaging and Marking				
	(Dwg. 8853703)				
	Examination for Defects	50(b)		3.3	4.4.2.9 to 4.4.2.11

NOTES:
a. 25 each and every inert component and subassembly.
b. Randomly selected from the 300 to be functioned
c. See 4.3.1

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation. See MIL-A-48078. Lot numbering as required shall be in accordance with MIL-STD-1168. In addition, inspection lots of Primer Assemblies shall contain.

a. Parts of one lot interfix number from one manufacturer.
b. Igniter mixture from one batch or blending of batches which results in homogeneity of all igniter mixture used in loading the entire primer lot.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Electrode		8848639
			NEXT HIGHER ASSEMBLY
			9226356

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of small diameter		0.40%	3.2	Gage
Minor					
201	Large diameter(s)		0.65%	3.2	Gage
202	Small diameter at end		0.65%	3.2	Gage
203	Diameter between two large diameters		0.65%	3.2	Gage
204	Length of large diameter at pin end		0.65%	3.2	Gage
205	Finish improper		0.65%	3.2	Visual
206	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Ring				8848641
					NEXT HIGHER ASSEMBLY 9226356
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Concentricity of hole with outside diameter		0.40%	3.2	Gage
Minor					
201	Diameter of hole		0.65%	3.2	Gage
202	Distance across projections		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Outside diameter		0.65%	3.2	Gage
205	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Ring and Filament Assembly				9230471
					NEXT HIGHER ASSEMBLY 9226356
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Filament missing		0.40%	3.2	Visual
Minor					
201	Weld of filament to ring defective		0.65%	3.2	Visual/Manual
202	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Body, Prior to Machining		8848643
			NEXT HIGHER ASSEMBLY 9226356

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Concentricity of electrode with thread		0.40%	3.2	Gage
Minor 201	Length of electrode (cavity end)		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Body and Electrode Assembly		8848643
			NEXT HIGHER ASSEMBLY 9226356

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Electrode above flush		0.65%	3.2	Visual
202	Length of electrode (cavity end)		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Assembly, prior to Inserting Primer Charge				9226356
					NEXT HIGHER ASSEMBLY
					8848644
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Filament not secured to electrode		0.40%	3.3	Visual
102	Body filament cavity cracked		0.40%	3.3	Visual
Minor					
201	Evidence of poor workmanship		1.00%	3.7 & 3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Assembly, prior to Inserting Closing Disc	1 OF 1	8848644
			NEXT HIGHER ASSEMBLY 8848644

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Primer charge missing		0.40%	3.3	Visual
102	Length, max.		0.40%	3.3	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7 & 3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Primer Electric, M59		8848644
			NEXT HIGHER ASSEMBLY 8848644

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Electrical resistance		100%	3.3	4.5.3
102	All fire test		4.4.3.2	3.3	4.5.2.1
103	No fire test		4.4.3.2	3.3	4.5.2.2
Minor					
201	Filament assembly loose to finger pressure		0.65%	3.3	Manual
202	Closing disc missing or loose		0.65%	3.3	Visual/Manual
203	Evidence of poor workmanship		1.00%	3.7 & 3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Box, Set-up, Inner and Outer, Prior to Sealing	1 OF 1	8853703
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect number of assemblies in box		0.40%	3.3	Visual
Minor					
201	Die-cut tray damaged to extent that primers are loose or touch each other		0.65%	3.3	Visual
202	Primer missing		0.65%	3.3	Visual
203	Inner boxes are loose in outer boxes		0.65%	3.3	Visual
204	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	Set-up Box, Inner and Outer, Sealed	1	1	8858703
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Sealing compound incomplete		0.40%	3.3	Visual
102	Box damaged to extent that the contents are exposed or likely to become exposed in subsequent handling		0.40%	3.3	Visual
103	Sealing tape torn, incomplete or not securely sealed to the carton		0.40%	3.3	Visual
Minor					
201	Marking misleading or unidentifiable		0.65%	3.3	Visual
202	Contents loose		0.65%	3.3	Manual
203	Box torn, cut or punctured		0.65%	3.3	Visual
204	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Sealed Barrier Bag		8853703
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of barrier bag destroyed by rupture, puncture, or separation of heat seal		0.40%	3.3	Visual
102	Evidence of crushed box		0.40%	3.3	Visual
	NOTE: Package should be opened if there is evidence of crushing				
Minor					
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.3	Visual
202	Marking of bag misleading or undentifiable		0.65%	3.3	Visual
203	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Wood Packing Box Prior to Sealing		8853702
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Incorrect number of boxes		0.40%	3.3	Visual
Minor 201	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil - Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Wood Packing Box, Sealed				8853702
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged to the extent that the contents are exposed or likely to become exposed in subsequent handling		0.40%	3.3	Visual
102	Hardware or strapping broken or loose		0.40%	3.3	Visual
Minor					
201	Hardware or strapping incorrectly assembled		0.65%	3.3	Visual
202	Metallic seal unsealed or improperly positioned		0.65%	3.3	Visual/Manual
203	Contents loose		0.65%	3.3	Manual
204	Marking misleading or unidentifiable		0.65%	3.3	Visual
205	Evidence of poor workmanship		1.00%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Moisture content of igniter mixture (see 3.4) - Major defect. The contractor shall provide adequate controls to insure compliance with the requirements, and shall test for verification at least one sample of igniter mixture from each eight (8) hours production of primer assemblies. Composite samples shall not be used. If the moisture content of a sample exceeds the requirement, and loading has not begun, the quantity of material represented by the sample shall be rejected. If assemblies have been loaded with material containing excessive moisture, the remaining material that is represented by the sample together with all assemblies loaded with the non-conforming material shall be rejected. The test shall be performed as specified in 4.5.1.

4.4.3.2 Functioning

4.4.3.2.1 All-Fire (see 3.5.1).

4.4.3.2.1.1 First three lots. Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria specified, two hundred (200), primer assemblies shall be selected from each lot for this test. The lot shall be rejected if three (3) or more primer assemblies fail to comply with the requirement. The test shall be performed as specified in 4.5.2.1 using test equipment specified in 4.4.4.

4.4.3.2.1.2 After three lots. After three consecutive lots have complied with the criteria of 4.4.3.2.1.1 eighty (80) primer assemblies shall be selected from each lot for this test. The lot shall be rejected if two (2) or more primer assemblies fail to comply with the requirement. The test shall be performed as specified in 4.5.2.1 using test equipment specified in 4.4.4.

4.4.3.2.2 No-Fire (see 3.5.2).

4.4.3.2.2.1 First three lots. Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance criteria specified, two hundred (200) primer assemblies shall be selected from each lot for this test. The lot shall be rejected if one or more primer assemblies fails to comply with the requirement. The test shall be performed as specified in 4.5.2.2 using test equipment specified in 4.4.4.

4.4.3.2.2.2 After three lots. After three consecutive lots have complied with the criteria of 4.4.3.2.2.1 eighty (80) primer assemblies shall be selected from each lot for this test. The lot shall be rejected if one or more primer assemblies fails to comply with the requirement. The test shall be performed as specified in 4.5.2.2 using test equipment specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

4.4.3.3 Electrical resistance (see dwg. 8848644) - This test shall be conducted 100 percent. Any primer which fails to comply with the applicable requirement shall be classed defective and removed from the lot. The test shall be performed as specified in 4.5.3 using equipment in accordance with 4.4.4.

4.4.3.4 Resistance of filament (see dwg. 8848638 covering a detail of dwg. 9226356) - Each roll of wire shall be tested before using. If any roll fails to meet the requirement it shall be classed defective and shall not be used for manufacturing filaments covered by this specification. The test shall be performed as specified in 4.5.4.

4.4.3.5 Heat seal test of sealed barrier bag (see dwg. 8853703) Sampling, acceptance criteria and test procedures for this test shall be as specified in MIL-P-116. (Destructive test).

4.4.4 Inspection Equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.4). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.2 herein.

4.4.5 Dimensional control of molded parts. In place of normal sampling and inspections associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (see Note 1) a sample of five (5) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification, when more than one cavity is used in production. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraph 4.4.5.1 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the five (5) samples one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective parts shall be removed from production. Further, the portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and and AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may after reworking be returned to production providing they pass the qualification test above. The contractor

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request. Contractor design of gages and test equipment required to perform the inspections listed herein shall be forwarded to Commander, ARRADCOM, Dover, New Jersey 07801, ATTN: DRDAR-QAT-I for approval prior to manufacture of equipment. The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

Note 1 - In establishing the curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to ARRADCOM, Dover, New Jersey 07801 ATTN: DRDAR-QAT-M. If any new change in material, cycle time, a reworked cavity, or a new cavity is used, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-11329E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8848643
4.4.5.1	Body and Electrode Assembly				NEXT HIGHER ASSEMBLY 9226356
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread, max.	(a)	0.40%	3.2	Gage
102	Major diameter of thread, max.		0.40%	3.2	Gage
103	Concentricity of filament assembly cavity with pitch diameter of thread		0.40%	3.2	Gage
Minor					
201	Pitch diamter of thread, min.		0.65%	3.2	Gage
202	Major diamter of thread, min.		0.65%	3.2	Gage
203	Total length		0.65%	3.2	Gage
204	Depth of filament assembly cavity		0.65%	3.2	Gage
205	Diameter of filament assembly cavity		0.65%	3.2	Gage
206	Length to thread (cavity end)		0.65%	3.2	Gage
207	Length of thread, min.		0.65%	3.2	Gage
208	Wrench holes missing or inadequate		0.65%	3.2	Visual
209	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

a. For sample size see 4.3.1 and 4.4.5

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

4.5 Test Methods and Procedures

4.5.1 Moisture content of igniter mixture. An accurately weighed portion of 0.40 to 0.70 grams of the sample shall be dried to a constant weight in a desiccator containing calcium chloride maintained at a temperature of 70 plus or minus 5 degrees Centigrade. Calculate the loss in weight as percent moisture.

4.5.2 Functioning

4.5.2.1 All-Fire. The primer assembly shall be assembled in an approved fixture as specified in 4.4.4 and the all-fire current applied. The primer shall be observed for compliance with the requirement. (Destructive Test)

4.5.2.2 No-Fire. The primer assembly shall be tested as specified in 4.5.2.1 except that the no-fire current shall be applied as specified in 3.5.2. Primer assemblies subjected to this test shall not be returned to the lot. (Destructive test)

4.5.3 Electrical Resistance. The primer shall be assembled in an approved test fixture as specified in 4.4.4. A constant load of 125 pounds shall be applied to the upper terminal and the resistance measured between the face of the ring and the central electrode of the primer. The resistance shall be determined to the nearest .01 ohm. The max. safe current flow in the test circuit shall be not greater than 10 milliamperes. Precaution shall be taken in the test apparatus to avoid inductive voltages that might cause functioning of the primer. (Non-Destructive test)

4.5.4 Resistance of filament. An accurately measured piece of wire approximately 6 inches in length shall be used. The resistance of the wire shall be determined using a resistance meter capable of measuring resistance from 0 to 200 ohms. The resistance per foot shall be calculated as follows:

$$\text{Ohms per foot} = \frac{12A}{B}$$

where:
A = resistance measured (ohms)
B = length in inches

5. PACKAGING

5.1 Preservation and packaging

5.1.1 Level C. The primers shall be preserved and packaged in accordance with dwg. 8853703.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

5.1.2 Level C. Primer Parts - Packaging shall be in accordance with MIL-STD-1169 requirements.

5.2 Packing

5.2.1 Level C. The primer boxes shall be packed in accordance with dwg. 8853702.

5.2.2 Level C. Primer parts shall be packed in accordance with MIL-STD-1169 requirements.

5.3 Marking. Primer containers and bags shall be marked in accordance with instructions contained in dwgs. 8853702 and 8853703. Primer parts containers shall be marked in accordance with MIL-STD-1169 requirements.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use in the M112 Photoflash Cartridge.

6.2 Ordering Data. See MIL-A-48078

6.3 Submission of Inspection Equipment Designs for Approval. See MIL-A-48078. Submit equipment designs as required to Commander: ARRADCOM, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, US Army ARRADCOM, ATTN: DRDAR-QAT-M, Dover, New Jersey 07801.

6.5 Check test for possible deterioration. The following test is designed to prevent primers that have deteriorated being assembled into major ammunition items. The test shall be performed on primers from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the primers are assembled does not require that the check test be performed, the contracting officer should insert in the contract a provision for the performance of the check test. The contracting officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration. Primer assemblies shall be selected from each lot for this test.

6.6 Functioning test for possible deterioration. A sample of 80 primers shall be selected from each lot. If three (3) or more primers fail to comply with the specified requirements, the lot shall be rejected. The test shall be performed as specified in 4.5.2, using test equipment as specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

6.7 Changes from Previous Issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A394)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN: DRDAR-QAT
DOVER, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-11329E	PRIMER, ELECTRIC, M59, PARTS FOR AND LOADING, ASSEMBLING AND PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://... 2026-10-17T15:56Z
Check the source to verify that this is the current version before use.