MIL-D-14140C (PA)
7 May 1975
Superseding
MIL-D-14140B (MU)
17 August 1964 and
MIL-D-46287A (MU)
17 August 1964
(See 6.6)

MILITARY SPECIFICATION

DETONATOR, FLASH, M80
PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for and the loading, assembling and packing for one type of detonator designated as Detonator, Flash, M80.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-P-48250 - Primers, Stab M55
*MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

MIL-STD-650 - Explosive; Sampling Inspection and Testing
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

*(For meaning of asterisk (*) see paragraph 6.5).

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

8798756 - Cup, Detonator
8798757 - Disc, Detonator Closing
8798754 - Disc, Detonator
8798731 - Detonator, M80, Assembly
*9258182 - Box, Set-Up, Packing, Ammunition, Inner for Small Explosive Components
*9258183 - Box, Set-Up, Packing, Ammunition, Outer for Small Explosive Components
*9258184 - Box, Packing, Ammunition for Small Explosive Components

*INSPECTION EQUIPMENT DRAWINGS

9200602 - Bushing
8816368 - Disc, Lead
8816367 - Holder, Firing Pin
8827934 - Ball, Steel
8867811 - Holder, Primer
8827828 - Sleeve, Centering
9200012 - Pin, Firing
8802085 - Fixture, Testing

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM Designation E300 - Industrial Chemicals, Recommended Practice for Sampling

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Penn. 19103).

3. REQUIREMENTS

3.1 Material. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts. - The parts shall comply with all requirements specified on Drawings (dwgs.) 8798756, 8798757 and 8798754 as applicable and with all requirements specified in applicable specifications.

3.3 Detonator. - The detonators shall comply with all requirements specified on Drawing (dwg.) 8798731, and with all requirements specified in applicable specifications.

3.4 Moisture content of lead azide. - The moisture content of the lead azide used in loading the detonators shall not exceed 0.50 percent.

3.5 Functioning.

3.5.1 Output. - The detonators shall function on the first attempt and shall cause a 7/32 inch diameter perforation in a .131 inch min. thick lead disc.

3.5.2 Waterproofness. - The detonators shall be waterproof as evidenced by normal functioning, as specified in 3.5.1 after being immersed in water maintained at 70 degrees Fahrenheit (F.) plus or minus 10 degrees F., at a depth of 2 inches minimum for not less than 48 hours.

3.6 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

3.7 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection

*4.3.1 Submission. - The contractor shall submit a first article sample (see 6.1b) as designated by the Contracting Officer. The first article sample shall consist of fifty (50) complete sets of parts (i.e. fifty (50) of each and every component). The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3.

*4.3.2 Inspections to be performed. - See MIL-A-48078, paragraphs 4.4.2.1 through 4.4.2.2 and Table I specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-14140C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#	Detonator, Flash, M80, Metal Parts				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Metal Parts (Dwg. 8798757, 8798754 & 8798756) Examination for Defects NOTE: (a) 50 each of every component	50(a)		3.2	4.4.2.1 & 4.4.2.2

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

*4.3.3 Rejection. - (See MIL-A-48078).

4.4 Quality conformance inspection.

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of detonators shall contain:

a. Parts of one interfix lot number from one manufacturer.

b. Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plants.

c. RDX from one batch or a blending of batches which results in homogeneity of all explosives used in loading a lot.

4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-D-14140C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Disc, Detonator and Disc, Closing				8798757 & 8798754
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131	Diameter		0.40%	3.2	Gage
132	Thickness		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

7

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-D-14140C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#4.4.2.2	Cup, Detonator				8798756
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Crack or split		100.0%	3.2	Visual
Major B					
131	Diameter of flash hole, min.		0.40%	3.2	Gage
132	Total length		0.40%	3.2	Gage
133	Thickness through bottom, min.		0.40%	3.2	Gage
134	Concentricity of flash hole with outside diameter		0.40%	3.2	Gage
135	Inside diameter, min.		0.40%	3.2	Gage
136	Outside diameter, max.		0.40%	3.2	Gage
137	Cup damaged		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-14140C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.3	Assembly Prior to Loading				8798731
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Coating on interior of cup missing or inadequate		100.0%	3.3	Visual
Major B					
131	Coating compound or lacquer on exposed surface of disc		0.40%	3.3	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
#4.4.2.4	Assembly		8798731
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cup cracked, split or cut		100.0%	3.3	Visual
Major B					
131	Length		0.40%	3.3	Gage
132	Diameter, max.		0.40%	3.3	Gage
133	Color of lacquer incorrect (either end)		0.40%	3.3	Visual
134	Crimp not full 360 degrees		0.40%	3.3	Visual
135	Disc loose		0.40%	3.3	Visual/Manual
136	Disc punctured or torn		0.40%	3.3	Visual
137	Cup damaged		0.40%	3.3	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9258182
*4.4.2.5	Box, Set-Up, Inner, After Loading and Prior to Closing Slide Cover				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Filler and cushion assembly missing		100.0%	3.3	Visual
2	Filler and cushion assembly improperly assembled		100.0%	3.3	Visual
3	Stiffner missing		100.0%	3.3	Visual
4	Slide cover assembled reversed		100.0%	3.3	Visual
Major A					
101	Release paper missing		0.40%	3.3	Visual
Minor					
201	Marking missing, incomplete or illegible		0.65%	3.3	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.1.6	Box, Set-Up, Outer, with Inner Set-Up Boxes Assembled and Prior to Assembling Top	1 OF 1	9258183
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
Critical					
1	Red surface on inner set-up boxes do not alternate on same side of outer set-up boxes		100.0%	3.3	Visual
2	Stiffner not facing one direction		100.0%	3.3	Visual
Major A					
101	Inner box does not fit properly in outer box		0.40%	3.3	Visual
102	Fillers missing		0.40%	3.3	Visual
Major B					
103	Label not securely applied to box		0.40%	3.3	Visual
Minor					
201	Marking missing, incomplete or illegible		0.65%	3.3	Visual
202	Box improperly taped		0.65%	3.3	Visual
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.7	Sealed Packed Barrier Bag, Prior to Packing in Box				9258183
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Waterproofness of barrier bag destroyed by rupture, puncture or separation of heat seal		0.40%	3.3	Visual
102	Evidence of crushed box		0.40%	3.3	Visual
NOTE:	Package should be opened if there is evidence of crushing				
Minor					
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.3	Visual
202	Marking of bag misleading or unidentifiable		0.65%	3.3	Visual
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567, FEB-74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.8	Box, Packing, Ammunition Prior to Assembling Cover and Strapping				9258184
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
131	Bag containing set-up boxes damaged		0.40%	3.3	Visual
132	Cushioning material incomplete or missing from around outer set-up boxes		0.40%	3.3	Visual
133	Marking missing, misleading or unidentifiable		0.40%	3.3	Visual
134	Bottom cushioning missing or of incorrect thickness		0.40%	3.3	Visual
Minor					
201	Contents loose within box		0.65%	3.3	Visual-Manual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-14140C (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
#4.4.2.9	Box, Packing, Ammunition				9258184
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major A					
101	Strapping missing, broken, loose or improperly fastened		0.40%	3.3	Visual/Manual
102	Box damaged		0.40%	3.3	Visual
103	Marking missing, incomplete or illegible		0.40%	3.3	Visual
Minor					
201	Wooden box cover nailed to box		0.65%	3.3	Visual
202	Metallic seal missing		0.65%	3.3	Visual
203	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Chemical sampling. - A representative sample shall be randomly selected for the chemical tests specified in 4.5. The procedure described in ASTM E300 should be used to withdraw the samples. The chemical tests in 4.5 shall be performed using prescribed analytical procedure for replicate determination given in standard analytical textbooks.

4.4.3.2 Moisture.

*4.4.3.2.1 Moisture content of lead azide (see 3.4) - Major A defect. - The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample in sufficient quantity to perform the test detailed in 4.5.1 shall be selected and tested as specified in 4.5.1. If the moisture content is in excess of the percentage specified and loading has not begun, the lot of lead azide shall be rejected. If loading has begun, action on the unloaded lead azide shall be as specified above and all detonators loaded with questionable lead azide shall be rejected.

4.4.3.3 Binder-lubricant content of RDX (see dwg. 8798731) - Major A defect. - The binder-lubricant content of the RDX shall be determined for each lot at the time of loading. A sample of 5 grams shall be selected from each lot and tested as specified in 4.5.2. If the binder-lubricant content is in excess of the percentage specified and if loading has not begun, the lot of RDX shall be rejected until proper corrective action has been accomplished as verified by repeating the binder-lubricant determination specified in 4.5.2. If loading has begun, action on the unloaded RDX shall be as specified above and all detonators loaded with the questionable RDX shall be rejected.

4.4.3.4 Functioning

4.4.3.4.1 Output (see 3.5.1) Major A defect. - A sample of 315 detonators shall be selected at random from each lot. If 3 or more detonators fail to comply with the requirements specified, the lot shall be rejected. If one or two defectives are found, a second sample of 315 detonators shall be selected at random and tested. If in the combined first and second sample a total of 4 or more defectives are found the lot shall be rejected. The test shall be performed as specified in 4.5.3.2 using test equipment as specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

4.4.3.4.2 Waterproofness (see 3.5.2) Major A defect. - A sample of 25 detonators shall be selected at random from each lot. If one or more detonators fail to comply with the requirement specified the lot shall be rejected. The test shall be performed as specified in 4.5.3.2 using test equipment as specified in 4.4.4.

4.4.3.5 Heat seal test of sealed bag (see dwg. 9258183) Major A defect. - Sampling, acceptance criteria and test procedures for this test shall be as specified in MIL-P-116.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and section 6.2 herein.

4.5 Test methods and procedures.

4.5.1 Moisture content of lead azide. - The moisture content of lead azide shall be determined in accordance with MIL STD-650, Method 101.5 except, use a two gram sample and cover the dish with a sheet of polytetrafluoroethylene when weighing.

4.5.2 Determination of binder-lubricant content of RDX. - The calcium resinate, graphite and total binder-lubricant content of RDX shall be determined as follows:

4.5.2.1 Calcium resinate. - An accurately weighed portion of 5 grams of the sample shall be transferred to a tared medium porosity, sintered-glass crucible. The sample shall be extracted with three 20 milliliters (ml.) portions of chloroform which have been previously saturated with RDX, maintaining each portion in contact with the residue for approximately 5 minutes before applying suction. Any lumps which may persist shall be broken up by stirring occasionally and the sides of the crucible washed down with each 20 ml. portion of chloroform to insure complete removal of the calcium resinate. The residue shall be aspirated until the odor of chloroform is no longer detectable; the crucible and contents shall be placed in an oven at 100 degrees Centigrade (C.) to 105 degrees C. for 1/2 hour, cooled in a desiccator and weighed. The above extraction shall be repeated, drying and

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

weighing with individual 20 ml. portions of chloroform until the loss in weight on a subsequent extraction totals less than 0.003 grams. The loss in weight of the crucible plus contents shall be calculated to percent calcium resinate in the sample on a moisture free basis as follows:

$$\text{Percentage of Calcium Resinate} = \frac{100A}{W}$$

where:
A = loss in weight of the crucible plus contents.
W = weight of sample on a moisture free basis.

4.5.2.2 Graphite. - The crucible and contents remaining after the removal of calcium resinate shall be washed with a minimum of three 20 ml portions of acetone, each portion maintained in contact with the residue for approximately 1 minute with continuous stirring before applying suction, until the subsequent test for RDX in the acetone washings is negative. The crucible and contents shall be washed with a minimum of 3 ml portions of acetone, each portion maintained in contact with the residue for approximately 1 minute with continuous stirring before applying suction, until the following qualitative test for RDX in the acetone washings is negative. The acetone filtrate shall be transferred to a 25 ml beaker, evaporated to dryness on a steam bath and several drops of a solution of chromotropic acid added in 36 N sulfuric acid. The formation of a reddish-brown color, as compared to a pink color obtained by a blank prepared in an identical manner indicates the presence of RDX. The residue shall be aspirated until the odor of acetone is no longer detectable; the crucible and contents shall be placed in a drying oven at 95-105 degrees C for 1/2 hour, cooled in a desiccator and weighed. The weight of the residue in the crucible shall be calculated to the percentage of graphite in the sample on a moisture free basis as follows:

$$\text{Percentage of Graphite} = \frac{100A}{W}$$

Where:
A = increase in weight of filtering crucible.
W = weight of sample on a moisture-free basis.

4.5.2.3 Total binder-lubricant. - The percentage of total binder-lubricant in the sample shall be calculated by adding the percentages of calcium resinate and graphite found.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

4.5.3 Functioning.

4.5.3.1 Output. - The detonator shall be assembled to the applicable test fixture specified in 4.4.4 and functioned by dropping a steel ball 1-3/16 inch in diameter and weighing 3.95 ounces, maximum, on the firing pin from a height of 8 inches, maximum, to function the M55 primer. The M55 primer shall function to fire the detonator. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A detonator that fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective. Method of inspection shall be in accordance with dwgs. 9200602, 8816368, 8816367, 8827934, 8867811, 8827828, 9200012, and 8802085.

4.5.3.2 Waterproofness. - The detonator shall be immersed under water as specified for the time specified. Within one hour after removal from the water the detonator shall be subjected to the output test specified in 4.5.3.1. Any detonator which fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective. Method of inspection shall be in accordance with dwgs. in 4.5.3.1.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

*5.1.1 Level C. - The detonators shall be packaged in accordance with dwg. 9258182 and dwg. 9258183.

*5.1.2 Level C. - The detonator parts shall be packaged in accordance with MIL-STD-1169 requirements.

5.2 Packing.

*5.2.1 Level C. - The detonators shall be packed in accordance with dwg. 9258184.

*5.2.2 Level C. - The detonator parts shall be packed in accordance with MIL-STD-1169 requirements.

*5.3 Marking. - Detonator containers and bags shall be marked in accordance with instructions contained in dwgs. 9258182, 9258183 and 9258184. Detonator parts containers shall be marked in accordance with MIL-STD-1169 requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

6.2 Submission of Inspection Equipment Designs for Approval. - (See MIL-A-48078). Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T Dover, New Jersey 07801.

6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

6.4 Check test for possible deterioration. - The following test is designed to prevent detonators that have deteriorated from being assembled into major ammunition items. The test shall be performed on detonators from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration. Detonator assemblies shall be selected from each lot for this test.

6.4.1 Output. - A sample of 315 detonators shall be selected at random from each lot. If 4 or more detonators fail to comply with the requirement specified, the lot shall be rejected. If one or two defectives are found, a second sample of 315 shall be selected at random and tested. If in the combined first and second sample a total of 5 or more defectives are found the lot shall be rejected. The test shall be performed as specified in 4.5.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.6 Supersession data. - This specification includes the requirements of MIL-D-46287A (MU) dated 17 August 1964.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-140

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.