MILITARY SPECIFICATION

FILTER, BANDPASS

(FILTER KITS MK-123( )/TRC, MK-124( )/TRC, MK-228( )/GRC AND MK-236( )/GRC, UNITS OF)

Page 1, paragraph 2.1: Replace with:

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Page 1, under "SPECIFICATIONS, FEDERAL", delete QQ-S-571.

Page 1 under "SPECIFICATIONS, MILITARY", and on page 4, paragraph 3.3, delete MIL-G-3278 and replace with MIL-G-23827.

Page 2, under "STANDARDS MILITARY", delete MIL-STD-169 and MIL-STD-170. Add MIL-STD-454, "STANDARD GENERAL REQUIREMENTS FOR ELECTRONIC EQUIPMENT" and MIL-STD-810, "ENVIRONMENTAL TEST METHODS."

Page 2, under "DRAWINGS, SIGNAL CORPS", and on page 3, paragraph 3.2, under "MK-236( )/GRC (A Band), change drawing reference as follows:

From	To	For
SC-DL-63300	SC-DL-116862	Filter, Bandpass F-238( )/U
SC-DL-63302	SC-DL-116863	Filter, Bandpass F-239( )/U
SC-DL-63307	SC-DL-116864	Filter, Bandpass F-240( )/U
SC-DL-63620	SC-DL-116865	Filter, Bandpass F-241( )/U
SC-DL-63344	SC-DL-116866	Filter, Bandpass F-242( )/U
SC-DL-63320	SC-DL-116867	Filter, Bandpass F-243( )/U

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:53Z
Check the source to verify that this is the current version before use.

Page 2, delete "(copies of specifications, standards, - - - by the contracting officer)", and replace with: (Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer. Both the title and number or symbol should be stipulated when requesting copies.)

Page 2, paragraph 2.2: Replace with:

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Page 3, paragraph 2.2: Delete: No. 4, Rule No. 21, No. A-3 and No. 14.

Page 4, paragraph 3.4: Add to paragraph: The final paint film on front panel of filters shall be gray, semigloss enamel. The final paint film on Case, Accessories CY-1344(*)/TRC and all type I surfaces shall be green color (olive drab) semigloss enamel. The final paint films shall match color chips provided by the procuring agency. (See 6.7.)

Page 4, paragraph 3.5: Add to paragraph: Adhesive-backed, metal foil, nameplates shall be permitted on the bandpass filters, provided they are subjected to and pass the temperature and moisture-resistance tests of paragraph 4.10 and 4.11.

Page 4, paragraph 3.6: Delete in its entirety and replace with: "3.6 Soldering - Soldering shall be in accordance with Requirement 5 of MIL-STD-454."

Page 5, paragraph 3.8 and subparagraphs: Replace with:

3.8 Interchangeability. Like units, assemblies, subassemblies and replaceable parts shall conform to Requirement 7 of MIL-STD-454 and shall be physically and functionally interchangeable without modification of such items.

Pages 5 and 6, paragraph 3.9.2: Change values, in the tables listed below, as indicated:

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:53Z
Check the source to verify that this is the current version before use.

Table 1a, Filter F-239( )/U, under

"Loss at F -8% and Loss +8% replace "26. ±3 and 27. ±3" with 24. ±3.

Table 1b, Filter F-197( )/U, under "Useful Frequency Range" replace "205-206" with 205-225.

Table 1c, under "Useful Frequency Range" as follows:

Filter	From	To
F-199( )/U	223-253	225-254
F-200( )/U	253-283	254-284
F-201( )/U	283-313	284-314
F-202( )/U	313-343	314-344
F-203( )/U	343-373	344-374
F-204( )/U	373-403	374-400

Page 7 paragraph 3.10.1: Delete in its entirety and replace with the following:

3.10.1 Temperature.-

3.10.1.1 Low.- During testing as specified in 4.10.1, the equipment shall meet the following requirements:

Paragraph	Measurement	Performance
3.9.2	4.9.2	Table VI

After testing, the equipment shall meet full specification performance for these measurements.

3.10.1.2 High. - During testing as specified in 4.10.2, the equipment shall meet the following requirements:

Paragraph	Measurement	Performance
3.9.2	4.9.2	Table VI

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:33Z
Check the source to verify that this is the current version before use.

After testing, the equipment shall meet full specification performance for these measurements.

Page 7, paragraph 3.10.2: Delete in its entirety and replace with the following:

3.10.2 Humidity (moisture-resistance). - During testing as specified in 4.11, the equipment shall meet the following requirements:

Paragraph	Measurement	Performance
3.9.2	4.9.2	Table VI

After testing, the equipment shall meet full specification performance for these measurements.

Page 7, subparagraph "3.10.4": Delete.

Page 7, paragraph 3.13: Replace with:

3.13 Preproduction samples. The contractor shall furnish 2 preproduction samples of equipment on order for approval, if required by the invitation for bids and contract. (See 4.3.)

Page 8, paragraph 4.1: Replace with:

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Page 10, subparagraph 4.4.2.1: Delete.

Page 11, paragraph 4.4.5: Delete.

Page 18, paragraph 4.10: Replace with:

4.10 Temperature test.-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.

4.10.1 Low Temperature.- The equipment shall be tested in accordance with Method 502, Procedure I of MIL-STD-810. The low storage temperature shall be -80°F, but shall not exceed 24 hours at any one time. The low operating temperature shall be -40°F, but shall not exceed 72 hours at any one time. Prior to testing, the equipment shall meet full specification performance for the measurements specified in 3.10.1.1.

4.10.2 High Temperature.- The equipment shall be tested in accordance with Method 501, Procedure II of MIL-STD-810. The high temperature storage shall be -160°F, but shall not exceed 4 hours at any one time. The high operating temperature shall be +150°F but shall not exceed 4 hours at any one time. Prior to testing, the equipment shall meet full specification performance for the measurements specified in 3.10.1.2.

Page 18, paragraph 4.11: Replace with:

4.11 Humidity (moisture-resistance) test.- The equipment shall be tested in accordance with Method 507, Procedure II of MIL-STD-810. Prior to testing, the equipment shall meet full specification performance for the measurements specified in 3.10.2. Measurements shall be made during the periods shown on the figure for the cycle. Do not move equipment from the humidity chamber for measurements, and do not leave power on after measurements have been completed. If any equipment fails to meet the specified performance during cycling, it shall be realigned or readjusted once and the test continued. No repair or replacement of parts shall be permitted. If the equipment still fails to meet the specified performance during cycling, or fails subsequently, it does not pass the test. In addition, if the equipment fails to meet specified requirements after final conditioning and adjustment, it does not pass the test.

Page 21, subparagraph 6.1(e)(1): Delete.

Page 22, add the following paragraph:

6.7 Color. The color chips furnished by the procuring agency (3.4) will be color chips No. 26152 (gray) and No. X24087 (green), and may be obtained upon request to Commanding General, Aberdeen Proving Ground, ATTN: Coating and Chemical Laboratory, Maryland 21005.

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:53Z
Check the source to verify that this is the current version before use.

Page 23, "NOTICE": Delete.

Custodians:

Army - EL

Preparing activity:

Army - EL

Project No. 5915-A021

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:53Z
Check the source to verify that this is the current version before use.