MIL-P-14117 (Ord)
12 July 1955
SUPERSEDING
WTVPD 198A
1 June 1955

MILITARY SPECIFICATION

PACKAGING OF GAGE, BARREL EROSION, 20MM, T23

1. SCOPE

1.1 This specification covers the requirements for packaging, packing and marking of Gage, Barrel Erosion, 20MM, T23 for each level of protection (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards and drawings of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATIONS

Federal:

- NN-B-591 - Boxes, Wood, Cleated-Fiberboard
- NN-B-621 - Boxes, Wood, Nailed and Lock-Corner
- LLL-F-291 - Fiberboard; Corrugated, Single Face (Flexible)
- PPP-B-601 - Boxes, Wood, Cleated-Plywood
- PPP-T-76 - Tape, Paper, Water Resistant, Pressure-Sensitive

Military:

- JAN-P-100 - Packaging and Packing for Overseas Shipment General Specification
- JAN-P-106 - Boxes; Wood, Nailed (Overseas Type)
- JAN-P-108 - Boxes, Fiberboard, Corrugated and Solid (Military Type)
- MIL-P-116 - Preservation, Methods of
- JAN-P-125 - Packaging and Packing for Overseas Shipment Barrier-Materials, Waterproof, Flexible
- JAN-P-127 - Packaging and Packing for Overseas Shipment Tape, Adhesive, Pressure-Sensitive, Water-Resistant
- JAN-P-138 - Boxes, Wood, Fiberboard Lined
- MIL-B-107 - Boxes, Wood, Wirebound
- MIL-B-131 - Barrier-Material; Water Vaporproof, Flexible
- MIL-L-644 - Lubricating-Oil, Preservative, Special
- MIL-L-3150 - Lubricating Oil, Preservative, Medium

STANDARDS

Military:

- MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
- MIL-STD-129 - Marking for Shipment and Storage

FSC 5220

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:52Z
Check the source to verify that this is the current version before use.

DRAWINGS
Ordnance Corps:
F7249507 - Case, Carrying

(Copies of specifications, standards and drawing required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and methods.- The materials, methods, and procedures used in the packaging of items shall be in accordance with this specification. Materials and methods not covered by a specification shall be suited to the intended use and subject to the approval of the arsenal having technical responsibility for the packaged item.

3.2 Cleaning.- The instructions of Specification MIL-P-116 concerning cleaning procedures shall be followed.

3.2.1 Cleaning before preservation.- All metallic surfaces of gage assembly and spare collet shall be cleaned by process C-1 of Specification MIL-P-116. Non-metallic surfaces shall be cleaned only by wiping with a clean, dry cloth.

3.3 Drying.- Immediately after cleaning, all items shall be dried in accordance with Specification MIL-P-116.

3.3.1 Drying by wiping.- This procedure of drying shall be used only when other methods are not practicable.

3.4 Preservation.- The method of preservative application shall be in accordance with Specification MIL-P-116. Preservative shall not be applied to non-metallic parts or assemblies. Preservative oils shall be thoroughly drained before packaging.

3.4.1 Level A - Military package.- All metallic surfaces of the gage assembly and spare collet shall be preserved with a medium oil conforming to Specification MIL-L-3150.

3.4.2 Level B - Military package.- All metallic surfaces of the gage assembly and spare collet shall be preserved with a special oil conforming to Specification MIL-L-644.

3.4.3 Level C - Minimum military package.- No preservative application is required.

3.5 Packaging.

3.5.1 Level A - Military package.- The gage assembly and spare collet shall be packaged method IA-8 in accordance with Specification MIL-P-116 and the following: The preserved gage assembly and spare collet shall be inserted into the carrying case and the case closed. The carrying handle and corners at each end of the case shall be cushioned with flexible, single face, corrugaged fiberboard conforming to Specification LLL-F-291. The fiberboard shall be secured in position with pressure-sensitive tape conforming to Specification PPP-T-76 or type II or III of Specification JAN-P-127. The cushioned case shall then be inserted into bag fabricated of material conforming to class 1, Specification MIL-B-131. Sufficient material shall be allowed for 2 additional heat seals after initial sealing of the bag. The bag shall be closed by heat sealing. The wrapped case shall then be inserted into a fiberboard sleeve fabricated of material conforming to W-Board, Specification JAN-P-108. The ends of the bag shall be covered with pressure-sensitive tape to prevent abrasion of the barrier material during packing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:52Z
Check the source to verify that this is the current version before use.

3.5.2 Level B - Limited military package.- The gage assembly and spare collet shall be packaged method IC in accordance with Specification MIL-P-116 and the following: The preserved gage assembly and spare collet shall be inserted into the carrying case and the case closed. The closed case shall be completely covered with a layer of waterproof barrier-material conforming to type C-1 or C-2, Specification JAN-P-125. All seams and edges of the wrap shall be sealed with pressure-sensitive tape conforming to Specification PPP-T-76 or type I or III of Specification JAN-P-127. The wrapped case shall then be inserted into a fiberboard sleeve fabricated of material conforming to W-Board, Specification JAN-P-108.

3.5.3 Level C - Minimum military package.- The gage assembly and spare collet shall be inserted into the carrying case and the case closed. The closed case shall be inserted into a fiberboard sleeve fabricated of material conforming to W-Board, Specification JAN-P-108.

3.6 Packing.

3.6.1 Level A - Military pack.- The packaged gage shall be packed in an exterior container conforming to Specification PPP-B-601 (Overseas type), JAN-P-106, MIL-B-107 or JAN-P-138.

3.6.2 Level B - Limited military pack.-The packaged gage shall be packed in an exterior container conforming to Specification NN-B-631, PPP-B-601 (Domestic type), NN-B-591 or NN-B-621.

3.6.3 Level C - Minimum military pack.- Packing shall be as specified in 3.6.2.

3.7 Marking.

3.7.1 Interior marking.- The gage package shall be marked in accordance with Standard MIL-STD-129 and shall include the following applicable data:

Contract or Order Number
Method of Preservation

3.7.2 Shipping container.- The shipping container shall be marked in accordance with Standard MIL-STD-129 and shall include the following applicable data.

3.7.2.1 Oversea shipment.- The following additional markings, applicable to oversea shipment only, shall be applied by both depots and contractors.

3.7.2.1.1 Service color corner marking.- At two diagonally opposite corners of the container top in the indicated service color, an equal size triangle shall be painted on each adjacent face. Size of marking shall be proportionate to the size of the container.

3.7.2.1.2 Method of preservation.- Preservative markings will be stencilled on the exterior container as part of the basic marking.

3.7.2.1.3 Marking protection.- All oversea exterior container markings shall be protected with a coating of transparent waterproof material.

3.7.2.2 Levels of packing.- Unit packages and exterior containers containing items packaged for level B shall be clearly marked "LTD MIL PKG". Exterior containers containing items packaged for level C shall be clearly marked "MIN MIL PKG".

3.8 Pilot pack.- Pilot packs shall be submitted to the Government inspector to determine conformance with this specification.

3.9 Workmanship.

3.9.1 Each coating of preservative, wax, paint, or plastic shall be free from shop contaminants or foreign particles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:52Z
Check the source to verify that this is the current version before use.

3.9.2 Indiscriminate use of preservative, wax, paint, plastic, wrapping and cushioning materials shall be avoided.

3.9.3 Wraps shall be neat, conforming and firmly secured.

3.9.4 Shipping containers shall be free from damage, protruding nails, and debris. Irrelevant markings shall be neatly obliterated.

3.9.5 Marking shall be uniform and readily legible.

3.9.6 Strapping shall be applied perpendicular to the container sides, and shall not cover any markings.

4. QUALITY ASSURANCE PROVISIONS

4.1 General.- The tests shall be accomplished by the contractor or his agent under supervision of the Government inspectors. Inspection and test procedures shall be conducted in process.

4.2 Lot sizes.- The lot size submitted for acceptance purposes shall be determined by the procuring activity or Government inspection agency and shall be as large as practicable, consistent with available facilities.

4.3 Sampling.

4.3.1 For inspection.- Sampling for inspection shall be conducted in accordance with inspection level I of Standard MIL-STD-105.

4.3.2 For tests.- Sampling for tests for packages shall be conducted in accordance with Table I.

TABLE I - Sampling for Packaging Tests

Lot Size Packages	Sample Size	Rejection Number
3 to 50	3	1
51 to 500	5	1
501 to 1000	10	2
1001 and over	15	3

4.4 Inspection.

4.4.1 Classification of defects.- Visual inspection for defects established in Table II shall apply to each item of the applicable sample of interior packages or exterior containers.

TABLE II - Classification of Defects

Defects	AQL(%)
Illegible marking	1.0
Incorrect marking	1.0
Improper closure of interior packages	2.5
Inadequate blocking	2.5
Improper packing (insufficient clearance between contents and container; container oversize; inadequate or excessive cushioning material, etc.)	2.5
Non-adherence to the requirements of prescribed shipping container specification	2.5

4.5 Tests.

4.5.1 Rough handling test.- The pilot pack shall be subjected to the rough handling test in accordance with the requirements of Specification JAN-P-100. Applicable only to level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:52Z
Check the source to verify that this is the current version before use.

4.5.2 Packaging tests.- Each package in the applicable sample of Table I shall be subjected to the packaging tests of Specification MIL-P-116 that pertain to packaging Method IA-8.

4.6 Acceptance and rejection.

4.6.1 Final acceptance.

4.6.1.1 Inspection.- Lots shall be accepted when the applicable samples have met the requirements of Standard MIL-STD-105 for the inspection of defects established in Table II.

4.6.1.2 Tests for packages.- Lots shall be accepted when the defective units found during tests are less than the rejection number shown in Table I.

4.6.2 Rejection.- Any defective package or pack found during the sampling inspection or tests shall be cause for corrective action by the contractor, whether or not the lot is accepted.

5. PREPARATION FOR DELIVERY

5.1 There are no applicable requirements.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Level of protection required.

Patent notice: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian
Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:52Z
Check the source to verify that this is the current version before use.